Projection conique conforme de Lambert; LCS parallèles 49 30, 57 30; LCH parallèles 45 30, 52 00.

FRÉQUENCES DE COMMUNICATION POUR UN ESPACE AÉRIEN DE CLASSE G

LORSQUE DES AÉRONEFS EXÉCUTENT DES VOLS IFR OU VFR SPÉCIAUX NON CONTRÔLÉS OU DANS UN ESPACE AÉRIEN DE CLASSE G, DIFFUSER LES COMPTES RENDUS DE POSITION, LES CHANGEMENTS D'ALTITUDE, LES DÉPARTS ET LES INTENTIONS D'APPROCHE, ET RESTER À L'ÉCOUTE DES AUTRES AÉRONEFS SUR LA FRÉQUENCE 126.7 MHz. À MOINS QU'UNE AUTRE FRÉQUENCE SOIT DÉSIGNÉE POUR L'ESPACE AÉRIEN NON CONTRÔLÉ EN QUESTION.

Référez au Supplément de vol (CFS) (SS) pour renseignements complets sur les communications.

▲ Dpt Hrs Note

CENTRES DE CONTRÔLE RÉGIONAL et UNITÉ DE CONTRÔLE TERMINAL avec stations périphériques.

MONTRÉAL CYUL 124.45 134.85 126.15 128.8
CYBG 135.75 118.4 (RED) 360.2 384.4
Lac Supérieur – 132.1
TAKATA – 128.9 360.2

CODES ABRÉGÉS et LES NUMÉROS DU RÉSEAU TÉLÉPHONIQUE PUBLIC COMMUTÉ (RTPC)

FSS Gatineau-Kenilworth	613	1-866-WX-BRIEF	FSS Sept-Îles	418	1-866-WX-BRIEF
FSS Iqaluit (Hr Limitées)	867	1-866-991-3201	FSS de Stephenville	709	1-866-WX-BRIEF
FSS Lac Supérieur	807	1-866-WX-BRIEF	FSS de Terre-Neuve	709	1-866-WX-BRIEF
FSS de Moncton	506	1-866-WX-BRIEF	FSS de Gander/Intl	709	1-866-WX-BRIEF
FSS de Montréal	514	1-866-WX-BRIEF	FSS de Deer Lake	709	1-866-WX-BRIEF

◂ LO 3
LO 3 ▸

◂ LO 4
27 NOVEMBRE 2025
27 NOVEMBRE 2025 ▸
LO 4 ▸

NAV CANADA

EN ROUTE NIVEAU INFÉRIEUR

CANADA ET ATLANTIQUE NORD

AIR NAVIGATION CHART
Partie 2 - En route (ENR)
Le Ministère de la Défense nationale l'LIP GPH 206

Pour utilisation jusqu'à 15,000' ASL non inclusivement dans l'espace aérien intérieur du Canada and Atlantique Nord. Les cartes ne sont pas destinées à être utilisées dans les espaces aériens du Canada suivants la responsabilité d'assurer des services de contrôle de la circulation aérienne.

Avertissement: Prière de vous référer aux cartes et aux publications d'information de vol actuelles des Relevé pour les renseignements les plus récents des Etats-Unis.

EN VIGUEUR 0901Z

27 NOVEMBRE 2025
JUSQU'À 0901Z 27 JANVIER 2026

ATTENTION
Le contenu de la présente publication est susceptible de modification par NOTAM ou Supplément d'AIP

DONNÉES RÉVISÉES

LO 3 - Aucun changement.

LO 4 - Aucun changement.

Publié par NAV CANADA en vertu des Annexes 4 et 15 de la Convention relative à l'aviation civile internationale de l'OACI.
Cartographie et impression © 2025 NAV CANADA
Ce produit ne peut être reproduit en tout ou en partie sans autorisation écrite préalable de NAV CANADA. Tous droits réservés.
Sources des données aéronautiques militaires canadiennes
Ce produit est approuvé par le Chef d'état-major de la Défense et fini sous direction du Canada

LEGEND

AERONAUTICAL

AERODROMES: Civil; Joint Civil/Military; Military; Water; Heliport; Abandoned/Unlicensed; Aerodrome symbols may be offset for display purposes.

Land aerodrome name shown only when different from associated city name.

Water aerodrome name shown only when different from associated city name.

AERODROME DATA

- Elevation given in feet above sea level.
- Runway lighting available.
- ATC/FIS.
- Lat hrs in UTC: see CFS
- Hard surface runway.
- Length of longest runway (metres available in hundreds) / Width of runway (metres).
- Runway direction to nearest 10°.
- Water aerodrome data not shown.

RADIO AIDS TO NAVIGATION AND COMMUNICATION BOXES

RADIO AIDS TO NAVIGATION

Radio/Navigation Facilities not operated by NAV CANADA are shown in italics.

VHF/UHF Aids are displayed in BLACK. L/MF Aids are displayed in GREEN.

COMPASS ROSE: Oriented to True North. Magnetic Variation at Facility. Magnetic Variation Annual Change. Last Updated on True or Grid. Grid Variation. Grid Variation Annual Change. Last Updated on Grid.

VOR ○ VOR/DME ⬡ VORTAC ⬡ TACAN

Symbols may be displaced for sake of clarity. Compass Rose may be omitted for sake of clarity.

DME — L/F/MF NDB

RADIO AIDS TO NAVIGATION DATA BOXES

YXXX VOR/DME 113.6 YXX 115.5 CHN 111	L/F/MF aids not located at aerodrome. Identification on aeronautical charts. Type of aid. Frequency. Hours of operation. Name. Channel.
YXXX VOR/DME 113.6 CHN 111	VHF/UHF aids co-located at aerodrome. Name/Co-ordinates.
YXXX DN 60 34'N 112 47'W 114.3 CHN 115.3	VHF aids. Declination at facility. Name/Co-ordinates.
YXX 108.75 MAG 21.0° 2005	DME aids. Magnetic variation for VOR must be shown.
YXXX 113.6	L/F/MF aids. Unidentified or unmonitored. Name/Co-ordinates.
YXXX 113.6	Radio Control Aerodrome Traffic Frequency (RCATF).
YXXX 113.6	Aeradio or unicharted radio facility.

AIRWAYS AND ROUTES

VHF/UHF data is displayed in BLACK. L/MF data is displayed in GREEN.

Airways and routes are plotted on the basis on L/F/MF facility (L/F) and normally VHF/UHF facility (VOR). Airways and routes based on L/F/MF facility (L/F) are displayed in green.

- L/F/MF airway centre line and identification
- L/F/MF airway centre line and identification
- Unscheduled air route and identification
- Commonly used track or transition.
- Unscheduled track/ transition/ track
- Controlled/non land fixed track/ transition
- Magnetic bearing to/from L/F/MF facility
- Radial from a VHF/UHF radio aid.
- Magnetic Bearing to an L/F/MF facility.
- Southern Domestic L/F/MF outbound and inbound airways. Southern Domestic L/F/MF outbound and inbound Diverge are calculated at 25 NM from the facility.
- Pacific Oceanic west-bound route is the formation of an intersected 3 letter designator.
- Pacific Oceanic east-bound route is the formation of an intersected 3 letter designator.
- Westage transition point.
- Barrow SMR 1L
- Barrow SMR 1L route mileage.
- Barrow SMR 1L Unmonitored mileage shown when different from above.
- Track mileage between radio aids.
- Mileage between other reporting points, or between radio aid and reporting point.
- MEA (Minimum Enroute Altitude).
- MOCA (Minimum Obstruction Clearance Altitude). MOCA omitted when same as MEA.
- Change in MEA or MOCA at an intermediate point on an airway or route segment.
- Changeover point with mileage. Normally midway between navigation facilities.

U.S.A. (including ALASKA)

- MEA (Minimum Enroute Altitude).
- MRA (Minimum Reception Altitude).
- MAA (Maximum Authorized Altitude).

REPORTING POINTS

- Compulsory
- On request
- VHF/UHF radio facility (fix) designated in support of the Basic RNP 10 route.
- Reporting point with Mandatory Frequency (MF).

ROADGRAPHICS

- Provincial Boundaries/ Regions.
- Area IFR Tow Trucks.
- Air Defence Identification Zone.
- Grants Area (GTA) Separation.
- Downtown Toronto/west Universal Integrated Airspace.
- International Boundary.
- Minimum Safe Altitude Warning (MSAW) Area.
- Class 'W' control zone with ceiling 3000 feet ASL (lesser elevation in parenthesis).
- Class 'C' control zone with ceiling 3000 feet ASL (lesser elevation in parenthesis) and Mode C veil.
- NOTE: CZ data will not be displayed on LO charts when CZ ceiling is above 3000' ASL.

SPECIAL USE AIRSPACE

- Prohibited Area with identification code.
- Restricted Area with identification code.
- CYR - Restricted
- CYD - Dangerous
- MOA (Military Operations Area) or Exercise Area with activities from the surface up to and including 18,000 feet ASL (unless otherwise specified).
- U.S.A. (including ALASKA) Military Operations Area (MOA) or Warning Area.

WIND/TEMPERATURE

- Wind/temperature station.
- Holding pattern with published indications required for operational reasons. Indicated on speed charts.
- Holding pattern with published indications required for operational reasons. Indicated on speed charts.

MISCELLANEOUS

- Distance in nautical miles and True bearing (magnetic except in the Northern Domestic Airspace and Arctic Control Area).
- All altitudes are in hundreds of feet above mean sea level unless otherwise indicated. Altitudes underlined denote mandatory minimum altitudes.
- Class areas (airfields) indicate controlled airspace.
- Shaded areas (green) indicate uncontrolled airspace.
- Controlled airspace above 12500 MSL in Canada.
- MEA (Minimum Enroute Altitude).
- MRA (Minimum Reception Altitude).

CRUISING ALTITUDES - CANADA

CRUISING ALTITUDES - U.S.A.

AEROSPACE AND ROUTE INFORMATION

SPECIAL USE AIRSPACE

- Prohibited Area with identification code.
- Restricted Area with identification code.
- CYR - Restricted
- CYD - Dangerous
- MOA (Military Operations Area) or Exercise Area with activities from the surface up to and including 18,000 feet ASL (unless otherwise specified).
- U.S.A. (including ALASKA) Military Operations Area (MOA) or Warning Area.

WIND/TEMPERATURE

- Wind/temperature station.
- Holding pattern with published indications required for operational reasons. Indicated on speed charts.
- Holding pattern with published indications required for operational reasons. Indicated on speed charts.

MISCELLANEOUS

- Distance in nautical miles and True bearing (magnetic except in the Northern Domestic Airspace and Arctic Control Area).
- All altitudes are in hundreds of feet above mean sea level unless otherwise indicated. Altitudes underlined denote mandatory minimum altitudes.
- Class areas (airfields) indicate controlled airspace.
- Shaded areas (green) indicate uncontrolled airspace.
- Controlled airspace above 12500 MSL in Canada.
- MEA (Minimum Enroute Altitude).
- MRA (Minimum Reception Altitude).
- MAA (Maximum Authorized Altitude).

CRUISING ALTITUDES - CANADA

CRUISING ALTITUDES - U.S.A.

AIRSPACE AND ROUTE INFORMATION

AIRWAYS AND ROUTES

VHF/UHF data is displayed in BLACK. L/MF data is displayed in GREEN.

Airways and routes are plotted on the basis on L/F/MF facility (L/F) and normally VHF/UHF facility (VOR). Airways and routes based on L/F/MF facility (L/F) are displayed in green.

- L/F/MF airway centre line and identification
- L/F/MF airway centre line and identification
- Unscheduled air route and identification
- Commonly used track or transition.
- Unscheduled track/ transition/ track
- Controlled/non land fixed track/ transition
- Magnetic bearing to/from L/F/MF facility
- Radial from a VHF/UHF radio aid.
- Magnetic Bearing to an L/F/MF facility.
- Southern Domestic L/F/MF outbound and inbound airways. Southern Domestic L/F/MF outbound and inbound Diverge are calculated at 25 NM from the facility.
- Pacific Oceanic west-bound route is the formation of an intersected 3 letter designator.
- Pacific Oceanic east-bound route is the formation of an intersected 3 letter designator.
- Westage transition point.
- Barrow SMR 1L
- Barrow SMR 1L route mileage.
- Barrow SMR 1L Unmonitored mileage shown when different from above.
- Track mileage between radio aids.
- Mileage between other reporting points, or between radio aid and reporting point.
- MEA (Minimum Enroute Altitude).
- MOCA (Minimum Obstruction Clearance Altitude). MOCA omitted when same as MEA.
- Change in MEA or MOCA at an intermediate point on an airway or route segment.
- Changeover point with mileage. Normally midway between navigation facilities.

U.S.A. (including ALASKA)

- MEA (Minimum Enroute Altitude).
- MRA (Minimum Reception Altitude).
- MAA (Maximum Authorized Altitude).

REPORTING POINTS

- Compulsory
- On request
- VHF/UHF radio facility (fix) designated in support of the Basic RNP 10 route.
- Reporting point with Mandatory Frequency (MF).

ROADGRAPHICS

- Provincial Boundaries/ Regions.
- Area IFR Tow Trucks.
- Air Defence Identification Zone.
- Grants Area (GTA) Separation.
- Downtown Toronto/west Universal Integrated Airspace.
- International Boundary.
- Minimum Safe Altitude Warning (MSAW) Area.
- Class 'W' control zone with ceiling 3000 feet ASL (lesser elevation in parenthesis).
- Class 'C' control zone with ceiling 3000 feet ASL (lesser elevation in parenthesis) and Mode C veil.
- NOTE: CZ data will not be displayed on LO charts when CZ ceiling is above 3000' ASL.

SPECIAL USE AIRSPACE

- Prohibited Area with identification code.
- Restricted Area with identification code.
- CYR - Restricted
- CYD - Dangerous
- MOA (Military Operations Area) or Exercise Area with activities from the surface up to and including 18,000 feet ASL (unless otherwise specified).
- U.S.A. (including ALASKA) Military Operations Area (MOA) or Warning Area.

WIND/TEMPERATURE

- Wind/temperature station.
- Holding pattern with published indications required for operational reasons. Indicated on speed charts.
- Holding pattern with published indications required for operational reasons. Indicated on speed charts.

MISCELLANEOUS

- Distance in nautical miles and True bearing (magnetic except in the Northern Domestic Airspace and Arctic Control Area).
- All altitudes are in hundreds of feet above mean sea level unless otherwise indicated. Altitudes underlined denote mandatory minimum altitudes.
- Class areas (airfields) indicate controlled airspace.
- Shaded areas (green) indicate uncontrolled airspace.
- Controlled airspace above 12500 MSL in Canada.
- MEA (Minimum Enroute Altitude).
- MRA (Minimum Reception Altitude).
- MAA (Maximum Authorized Altitude).

AERODROME DATA

- Elevation given in feet above sea level.
- Runway lighting available.
- ATC/FIS.
- Lat hrs in UTC: see CFS
- Hard surface runway.
- Length of longest runway (metres available in hundreds) / Width of runway (metres).
- Runway direction to nearest 10°.
- Water aerodrome data not shown.

RADIO AIDS TO NAVIGATION AND COMMUNICATION BOXES

AIR/GROUND COMMUNICATION BOXES

24HR 128.8	HEAVY LINE BOXES indicate TDS and Aerodrome Control Frequencies. Normal use is by pilots to communicate with ATS. Frequencies are given access first by the aerodrome control tower, then by the Terminal Control Unit.
1200 – 2400 QUEBEC 126.7	Aeradio Communication Boxes. Normal use is by pilots to communicate with Aeradio. Frequencies are given access first by the Aeradio station, then by the Flight Information Centre.
1200 – 0	Aeradio Communication Boxes. Normal use is by pilots to communicate with Aeradio. Frequencies are given access first by the Aeradio station, then by the Flight Information Centre.
YXXXTOP 123.4 (MAUS)	RCO or CRCO not associated with an aerodrome.
FSS YXXX 123.4	(RCO) Remote Communications Outlet.
CARS 123.4	Remote Communications Facility (RCF).
1200 – 2400	Private aground station (AG).
	U.S.A. (including ALASKA)
123.45 122.8 USA 6	HEAVY LINE BOXES indicate Flight Service Station (FSS) and Tower frequencies. Normal use is by pilots to communicate with FSS and tell pilots where to contact next. Frequencies are given access first by FSS.
	Aeronautical Weather Broadcast
	Frequencies published in the Airport/Facility Directory are receivable 25 NM. Other frequencies at 50 NM and above may be receivable.
CHARLESTON 122.95	Aeradio or unicharted radio facility.
122.95	THIN LINE BOX without frequencies and controlling agency indicates that the Tower frequencies are shown in the Airport/Facility Directory.
WASHINGTON 21	Aeradio or unicharted radio facility. FSS Name.

AIRSPACE AND ROUTE INFORMATION

AIRWAYS AND ROUTES

VHF/UHF data is displayed in BLACK. L/MF data is displayed in GREEN.

Airways and routes are plotted on the basis on L/F/MF facility (L/F) and normally VHF/UHF facility (VOR). Airways and routes based on L/F/MF facility (L/F) are displayed in green.

- L/F/MF airway centre line and identification
- L/F/MF airway centre line and identification
- Unscheduled air route and identification
- Commonly used track or transition.
- Unscheduled track/ transition/ track
- Controlled/non land fixed track/ transition
- Magnetic bearing to/from L/F/MF facility
- Radial from a VHF/UHF radio aid.
- Magnetic Bearing to an L/F/MF facility.
- Southern Domestic L/F/MF outbound and inbound airways. Southern Domestic L/F/MF outbound and inbound Diverge are calculated at 25 NM from the facility.
- Pacific Oceanic west-bound route is the formation of an intersected 3 letter designator.
- Pacific Oceanic east-bound route is the formation of an intersected 3 letter designator.
- Westage transition point.
- Barrow SMR 1L
- Barrow SMR 1L route mileage.
- Barrow SMR 1L Unmonitored mileage shown when different from above.
- Track mileage between radio aids.
- Mileage between other reporting points, or between radio aid and reporting point.
- MEA (Minimum Enroute Altitude).
- MOCA (Minimum Obstruction Clearance Altitude). MOCA omitted when same as MEA.
- Change in MEA or MOCA at an intermediate point on an airway or route segment.
- Changeover point with mileage. Normally midway between navigation facilities.

U.S.A. (including ALASKA)

- MEA (Minimum Enroute Altitude).
- MRA (Minimum Reception Altitude).
- MAA (Maximum Authorized Altitude).

REPORTING POINTS

- Compulsory
- On request
- VHF/UHF radio facility (fix) designated in support of the Basic RNP 10 route.
- Reporting point with Mandatory Frequency (MF).

ROADGRAPHICS

- Provincial Boundaries/ Regions.
- Area IFR Tow Trucks.
- Air Defence Identification Zone.
- Grants Area (GTA) Separation.
- Downtown Toronto/west Universal Integrated Airspace.
- International Boundary.
- Minimum Safe Altitude Warning (MSAW) Area.
- Class 'W' control zone with ceiling 3000 feet ASL (lesser elevation in parenthesis).
- Class 'C' control zone with ceiling 3000 feet ASL (lesser elevation in parenthesis) and Mode C veil.
- NOTE: CZ data will not be displayed on LO charts when CZ ceiling is above 3000' ASL.

SPECIAL USE AIRSPACE

- Prohibited Area with identification code.
- Restricted Area with identification code.
- CYR - Restricted
- CYD - Dangerous
- MOA (Military Operations Area) or Exercise Area with activities from the surface up to and including 18,000 feet ASL (unless otherwise specified).
- U.S.A. (including ALASKA) Military Operations Area (MOA) or Warning Area.

WIND/TEMPERATURE

- Wind/temperature station.
- Holding pattern with published indications required for operational reasons. Indicated on speed charts.
- Holding pattern with published indications required for operational reasons. Indicated on speed charts.

MISCELLANEOUS

- Distance in nautical miles and True bearing (magnetic except in the Northern Domestic Airspace and Arctic Control Area).
- All altitudes are in hundreds of feet above mean sea level unless otherwise indicated. Altitudes underlined denote mandatory minimum altitudes.
- Class areas (airfields) indicate controlled airspace.
- Shaded areas (green) indicate uncontrolled airspace.
- Controlled airspace above 12500 MSL in Canada.
- MEA (Minimum Enroute Altitude).
- MRA (Minimum Reception Altitude).
- MAA (Maximum Authorized Altitude).

CRUISING ALTITUDES - CANADA

CRUISING ALTITUDES - U.S.A.