


# STANDARD ARRIVAL CHART-INSTRUMENT

VAR5° W

ATIS 127.85  
APP01 120.45(124.75)  
APP02 119.125(124.75)  
TWR 118.35(123.65)

ZBSJ SHIJIAZHUANG/Zhengding  
RWY33

BEARINGS ARE MAGNETIC  
ALTITUDES, ELEVATIONS  
AND HEIGHTS IN METERS  
DME DISTANCES IN  
NAUTICAL MILES  
DISTANCES IN KM



NOT TO SCALE

Initial approach MAX IAS 380kmH

Holding MAX IAS 425kmH

TL 3600  
TA 3000  
3300(QNH≥1031hPa)  
2700(QNH≤979hPa)

LARAD  
N39 08.8  
E114 36.2

D36.0SJW  
3000

D36.0SJW  
3000

ZANGANGZHEN  
403 JB  
N39 02.6E116 11.9

SAKOD  
N38 40.4  
E115 09.8

D26.0SJW  
2400

ENGIL  
N38 46.5  
E115 26.8

XINGTANG  
235 OC  
N38 27.3E114 33.3

ISGOD  
D27.4SJW  
N38 17.1  
E114 05.4  
2700

TAIYUAN  
113.1 TYN  
CH 78X  
N37 44.9E112 37.2

ZHENGding  
117.7 SJW  
CH 124X  
N38 16.8E114 41.9

WUJI  
272 FL  
N38 14.9E114 53.3

URKED  
D24.2SJW  
N38 11.0  
E115 11.7

D33.7SJW  
2400

BORGI  
N37 54.6  
E115 29.8

HENGSHUI  
350 HG  
N37 43.0E115 42.3


IAF  
D25.0SJW  
2400

64 305°  
HG-04A  
(by ATC)

IAF 1200

IAF 1200

LMM  
377 F  
...



Changes: Add HG-02A, HG-04A(by ATC).