

STANDARD DEPARTURE CHART-INSTRUMENT

VAR 4° W

D-ATIS(DEP) 126.2
TWR01 124.35(118.1)


ZHHH WUHAN/Tianhe
RNP RWY22R

BEARINGS ARE MAGNETIC
ALTITUDES, ELEVATIONS
AND HEIGHTS IN METERS
DME DISTANCES IN
NAUTICAL MILES
DISTANCES IN KM

APP01	121.2(119.15)
APP02	126.3(125.6)
APP03	119.575(119.15)

1. RNP1
2. GNSS REQUIRED

TL	3600
TA	3000
	3300(QNH ≥ 1031hPa)
	2700(QNH ≤ 979hPa)



NOT TO SCALE

HH456
3600
(for XSH-17D,BIVIP-17D)-

HH556
1800

HEBAOHU
114.45 DHB
... ..

N30 41.9E113 58.3

269°

HH554
550

136°

21

24

~~22~~

N3

Not

1. W

turn
2. T


3. D

Note:

1. While simultaneous operation implemented, turn LEFT after take-off shall be permitted by ATC.

2. Turning is forbidden before DER.

3. Departure turn at HH554 MAX IAS 390kmH.



MSA 46km

Changes: Speed limits at HH554.