

D-ATIS 127.85	APP01 120.3(119.75)	APP07 121.1(119.75)
TWR01 118.8(118.325) 17L/35R, 17R/35L	APP02 125.4(124.05)	APP08 127.75(124.05)
TWR02 118.4(118.725) 16L/34R, 16R/34L	APP03 125.85(119.2)	APP09 121.375(128.05)
TWR03 124.35(118.325) 17L/35R	APP04 123.8(119.2)	APP10 125.625(120.65)
TWR04 118.575(118.725) 16R/34L	APP05 126.65(128.05)	APP11 119.075(128.05)
	APP06 126.3(120.65)	

STANDARD DEPARTURE
CHART-INSTRUMENT

VAR5.8°W

ZSPD SHANGHAI/Pudong
RWY34L/34R/35L/35R
(AND, HSN)

BEARINGS ARE MAGNETIC
ALTITUDES, ELEVATIONS
AND HEIGHTS IN METERS
DME DISTANCES IN
NAUTICAL MILES
DISTANCES IN KM




NOT TO SCALE

Departure turn MAX460km/h

1. Departure turn before DER is forbidden.
2. AND-22D, HSN-22D departure average climb gradient $\geq 5.5\%$
if interception point 'R142°/D12.0HSH' required 2100.

TL 3600
TA 3000
3300(QNH ≥ 1031 hPa)
2700(QNH ≤ 979 hPa)



Changes: New chart.

