

CAC

CAUTION: THE INFORMATION IN THIS
PUBLICATION MAY BE SUPERSEDED
BY NOTAM OR AIP SUPPLEMENT

ATTENTION : LE CONTENU
DE LA PRÉSENTE PUBLICATION
PEUT ÊTRE REMPLACÉ PAR
NOTAM OU SUPPLÉMENT D'AIP

EFFECTIVE | EN VIGUEUR

0901Z **2 OCTOBER | OCTOBRE 2025**

TO | AU

0901Z 27 NOVEMBER | NOVEMBRE 2025

CANADIAN AIRPORT CHARTS

CARTES DES AÉROPORTS CANADIENS

Serving a world in motion
Au service d'un
monde en mouvement
navcanada.ca



CANADIAN AIRPORT CHARTS

CARTES DES AÉROPORTS CANADIENS



The information in the Canadian Airport Charts provides pictorial displays of Canadian airport manoeuvring areas found in the Canada Air Pilot or the military GPH 200, and may be reproduced for the sole purpose of assisting pilots during aircraft ground movement operations. Up-to-date information on flight planning procedures and airport services, including fuel, lighting, and local prohibitions or procedures is found in the Canada Flight Supplement.

L'information qui se trouve dans les Cartes des aéroports canadiens contient des indicateurs topographiques des aires de manœuvre des aéroports canadiens provenant du Canada Air Pilot ou du GPH 200 militaire et peut être reproduite à seule fin d'aider les pilotes durant les mouvements d'aéronefs au sol. De l'information à jour sur les procédures de préparation de plans de vol et les services d'aéroport, y compris le carburant, le balisage, ainsi que les interdictions et les procédures locales, se trouve dans le Supplément de vol Canada.

Published by NAV CANADA in accordance with ICAO Annexes 4 and 15 of the Convention on International Civil Aviation

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

Source of Canadian Military Aeronautical Data:

His Majesty the King in Right of Canada Department of National Defence

Publié par NAV CANADA en vertu des Annexes 4 et 15 de la Convention relative à l'aviation civile internationale de l'OACI

Source des données aéronautiques civiles canadiennes : © 2025 NAV CANADA Tous droits réservés

Source des données aéronautiques militaires canadiennes :

Ministère de la Défense Nationale de Sa Majesté le Roi aux droits du Canada

Preface

NAV CANADA, as the office responsible for the publication and distribution of aeronautical information, has decided to make aerodrome diagrams readily available to general aviation pilots through its website. This move will contribute to enhance aviation safety and will help to mitigate some of the risks associated with runway incursions.

Hot Spot: A location on an aerodrome movement area with a high risk of collision or runway incursion, and where heightened attention by pilots/drivers is necessary.

Hot Spots are found on applicable Canadian Aerodrome Charts.


Préface

NAV CANADA, en tant que responsable de la publication et de la distribution de l'information aéronautique, a décidé de mettre les schémas d'aérodrome à la disponibilité des pilotes d'aviation générale par l'intermédiaire de son site Web. Cette décision contribuera à accroître la sécurité aérienne et aidera à atténuer certains des risques associés aux incursions sur piste.

Point chaud : Endroit sur l'aire de mouvement d'un aérodrome où il y a un risque accru de collision ou d'incursion sur piste et où une attention soutenue de la part du pilote/conducteur est requise.

Les points chauds se trouvent sur les cartes d'aérodrome canadiennes applicables.

All graphics presented here are for explanatory purposes only and are not intended to be used for navigation.



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART LEGEND

Aerodrome Chart Legend

- | | |
|--------------------------------------|---------------------------------------|
| 1 Declared Distance Night | 22 Obstruction |
| 2 Take Off Run Available | 23 Building |
| 3 Take Off Distance Available | 24 Threshold Elevation |
| 4 Accelerate Stop Distance Available | 25 Runway Number |
| 5 Landing Distance Available | 26 CAT I Holding Bar |
| 6 Landing Distance Available Table | 27 Apron Identification |
| 7 Magnetic Variation | 28 Runway |
| 8 Latitude Coordinate | 29 Departure Procedure |
| 9 Threshold Displacement Note | 30 Runway Slope Gradient* |
| 10 Visual Glide Slope Indicator | 31 NAVAID within AD Limit |
| 11 Displaced Runway Threshold | 32 Operational Notes |
| 12 Turnaround Bay | 33 Control Tower |
| 13 Centreline Light | 34 Longitude Coordinate |
| 14 Runway Bearing | 35 Construction Area |
| 15 RVR Sensor | 36 Departure Climb Rate Table |
| 16 Approach Lighting | 37 Reduced Visibility Operation Table |
| 17 Wind Direction Indicator | 38 Low Visibility Operation Table |
| 18 Taxiway | 39 Take-off Minima Box |
| 19 Taxiway Identification | 40 Scale Bar |
| 20 Aerodrome Reference Point | 41 Geographic Grid |
| 21 Runway Dimensions | 42 Hot Spot |


* If only one value for runway slope is provided, it can be assumed that the runway has a constant slope for the length indicated and the slope direction is reversed in the opposing runway direction. If no length is indicated, this means the provided slope applies for the entire runway length. For example, for a published slope of RWY 04 DOWN 0.36%, it can be assumed that the slope for RWY 22 is UP 0.36% and that this applies for the entire runway length.

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART LEGEND

LÉGENDE DES CARTES D'AERODROME

Toute illustration n'est présentée ici qu'à titre indicatif et ne doit pas être utilisée pour la navigation.



LÉGENDE DES CARTES D'AERODROME

LÉGENDE DES CARTES D'AERODROME

Légende des cartes d'aerodrome


- | | |
|--|--|
| 1 Distance déclarée (nuit) | 23 Bâtisse |
| 2 Longueur de roulement utilisable au décollage | 24 Altitude du seuil |
| 3 Distance de décollage utilisable | 25 Numéro de piste |
| 4 Distance utilisable pour l'accélération-arrêt | 26 Barre d'attente d'ILS CAT I |
| 5 Distance d'atterrissage utilisable | 27 Identification de l'aire de trafic |
| 6 Tableau des distances d'atterrissage utilisables | 28 Piste |
| 7 Déclinaison magnétique | 29 Procédure de départ |
| 8 Coordonnée de latitude | 30 Pente de la piste* |
| 9 Note sur le décalage du seuil | 31 NAVAID sur l'aérodrome |
| 10 Indicateur visuel de pente d'approche | 32 Notes opérationnelles |
| 11 Seuil de piste décalé | 33 Tour de contrôle |
| 12 Aire de demi-tour | 34 Coordonnée de longitude |
| 13 Feux de l'axe de piste | 35 Zone de construction |
| 14 Relèvement de la piste | 36 Tableau des taux de montée de départ |
| 15 Capteur RVR | 37 Tableau des opérations par visibilité réduite |
| 16 Balisage lumineux d'approche | 38 Tableau des opérations par faible visibilité |
| 17 Indicateur de direction du vent | 39 Case des minimums de décollage |
| 18 Voie de circulation | 40 Barre d'échelle |
| Indicatif de voie de circulation | 41 Grille géographique |
| 20 Point de référence d'aérodrome | 42 Point chaud |
| 21 Dimensions de la piste | |
| 22 Obstruction | |

* Si une seule valeur de pente de piste est donnée, on peut supposer que la pente est constante sur la longueur indiquée et que la direction de la pente est inversée dans la direction de la piste opposée. Si aucune longueur n'est indiquée, la pente donnée s'applique à toute la longueur de la piste. Par exemple, pour une pente publiée de PISTE 04 DESCEND 0,36 %, on peut supposer que la pente de PISTE 22 MONTE 0,36 % et que cette valeur s'applique à toute la longueur de la piste.

Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

LÉGENDE DES CARTES D'AERODROME

		APRT RADIO – 122.1 TFC – 122.1				CTR Edmonton – 132.4		
						MF		
DECL	DISTS	14	32					
TORA		3002	3002					
TODA		3199	3199					
ASDA		3002	3002					
LDA		3002	3002					



ALERT, NU
CYLT


CYLT



CYLT

CYLT-AD

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

CYAB

ARVIAT, NU
CYEK

AERODROME CHART

AWOS – 128.7				● APRT RADIO – 122.1 ● TFC – 122.1			
DECL DIST	15	33					
TORA	4000	4000					
TODA	4984	4500					
ASDA	4000	4000					
LDA	4000	4000					



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 8 SEP 22

CYEK

CYEK-AD

AERODROME CHART




AERODROME CHART

CYBK

AERODROME CHART

● AWOS – 128.7				● APRT RADIO – 122.1			
				● TFC – 122.1		MF	
DECL DIST	11	29					
TORA	5006	5006					
TODA	5203	5203					
ASDA	5006	5006					
LDA	5006	5006					




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 5 OCT 23

AERODROME CHART




AERODROME CHART

EFF 29 DEC 22

CYCB

AERODROME CHART

				APRT RADIO – 122.1 TFC – 122.1		MF	
DECL DIST	12	30					
TORA	3600	3600					
TODA	4584	4584					
ASDA	3600	3600					
LDA	3600	3600					



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 8 SEP 22

CYCS

AERODROME CHART

AWOS – 124.6				APRT RADIO – 122.1			
				TFC – 122.1		MF	
DECL DIST	02	20					
TORA	3501	3501					
TODA	4485	4485					
ASDA	3501	3501					
LDA	3501	3501					




AERODROME CHART

EFF 7 AUG 25

AERODROME CHART

AWOS – 128.6				TFC – 123.2		ATF			
DECL DIST	17	35							
TORA	3935	3935							
TODA	4919	4919							
ASDA	3935	3935							
LDA	3935	3935							



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 26 DEC 24

CYVL

AERODROME CHART

		APRT RADIO – 122.1				RADIO Edmonton – 123.27		
						MF		
DECL DIST	16	34						
TORA	5006	5006						
TODA	5990	5990						
ASDA	5006	5006						
LDA	5006	5006						




AERODROME CHART

EFF 23 FEB 23

CYZS

AERODROME CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 2 OCT 25

CYDA

AERODROME CHART




AERODROME CHART

EFF 2 DEC 21

CYWJ

AERODROME CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

CDK2

EFF 16 MAY 24

AERODROME CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 16 MAY 24

CYOA

AERODROME CHART



FORT GOOD HOPE, NT
CYGH

CYGH

128 39.5 128 39 128 38.5 128 38

66 14.6 66 14.6

AS 20 070°

ELEV 246

Up 0.73 % first 2853' down 0.99% last 1581'

CYGH
N66 14.44
W128 38.86

4434 x 99 gravel

← 250° AS 25

ELEV 252

66 14.3 66 14.3

128 39.5 128 39 128 38.5 128 38

TAKE-OFF MINIMA

Rwys 07; 25: *

SCALE IN FEET

1000 500 0 1000

VAR 22° E 2017
ANNUAL RATE OF CHANGE 30' W


* DEPARTURE PROCEDURE
Rwy 07 - 1/2
Note: Trees to 312 ASL aprx 200' past departure end of rwy, 150' LEFT and 400' RIGHT of rwy centreline.
Rwy 25 - 1/2
Note: Trees to 285 ASL aprx 200' past departure end of rwy, 400' LEFT and RIGHT of rwy centreline.

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

CYGH

CYGH-AD

AERODROME CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 16 MAY 24

CYJF

AERODROME CHART




AERODROME CHART

EFF 26 DEC 24

CZFM

AERODROME CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 12 AUG 21

CYJP

AERODROME CHART



VAR 17° E
2014

ANNUAL RATE
OF CHANGE 23' W

ELEV 525

AS

126°

(P1)

CYFR
N61 10.85
W113 41.38

4001 x .98

gavel

Up 0.05%

AS

306°

(P1)

ELEV 527

Threshold 31 displaced 655'

* DEPARTURE PROCEDURE

Rwy 13 - ½ - Trees to 594 ASL aprx 0.1 NM past departure end of rwy. Church to 605 ASL aprx 0.5 NM past departure end of rwy, 400' RIGHT of rwy centreline.

Rwy 31 - ½ - Trees to 597 ASL aprx 0.2 NM past departure end of rwy, 350' LEFT and RIGHT of rwy centreline.

TAKE-OFF MINIMA

Rwys 13, 31: *

SCALE IN FEET


1000 500 0 1000

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

CYFR

AERODROME CHART




AERODROME CHART

EFF 12 JUN 25

CYFS

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 10 AUG 23

CYSM

AERODROME CHART

● AWOS – 122.55				● UNICOM – 123.35 (AU)		ATF	
DECL DIST	06	24					
TORA	5311	5311					
TODA	6295	6295					
ASDA	5505	5508					
LDA	5311	5311					




AERODROME CHART

EFF 16 MAY 24

CGK2


AERODROME CHART

				● APRT RADIO – 122.1 ● TFC – 122.1			
DECL DIST	14	32			MF		
TORA	3000	3000					
TODA	3197	3197					
ASDA	3000	3000					
LDA	3000	3000					



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART



AERODROME CHART

EFF 26 DEC 24

AERODROME CHART




AERODROME CHART

EFF 3 NOV 22

CYHK

AERODROME CHART



AERODROME CHART

EFF 17 APR 25

CYHY

IGLOOLIK, NU
CYGT

		APRT RADIO - 122.1 TFC - 122.1		MF	
DECL DIST	15	33			
TORA	4095	4095			
TODA	5079	4423			
ASDA	4095	4095			
LDA	4095	4095			

* DEPARTURE PROCEDURE
Rwy 33 - ½
Note: Road to 194 ASL aprx 350' past departure end of rwy, 150' LEFT and 250' RIGHT of rwy centreline.

TAKE-OFF MINIMA
 Rwy 15: ½
 Rwy 33: ★

SCALE IN FEET
 1000 500 0 1000

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


CYGT

CYGT-AD

CYEV-AD

INUUVIK (MIKE ZUBKO), NT
CYEV

AERODROME CHART



AERODROME CHART

EFF 20 FEB 25

CYEV

CYEV-AD


AERODROME CHART (AI)

ADDITIONAL INFORMATION

- Pre-taxi clearance is available for up to 1 hr prior to departure. Pilots will receive clearance validation or an amended clearance when ready to taxi. Pilots must ensure that they have received clearance validation prior to take off.
- Expect ALL IFR departures to be assigned a SID that corresponds to the requested departure runway. Pilots are to be familiar with both the ALREX and ITRUS SIDs in case of a short notice change in the operational runway.
- Transient operators should familiarize themselves with receiving aerodrome advisory services as opposed to an aerodrome control service. Aerodrome advisory services (AAS) are primarily intended for the arrival and departure phases of a flight to an aerodrome within a Mandatory Frequency (MF) area, and for transit through an MF area, served by a Flight service station (FSS). AAS is provided on the MF. Mandatory reports by aircraft on the MF are critical for the FSS to be able to provide effective air traffic information. Additional details regarding AAS and MF are available within the TC AIM.

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

CYFB




RUNWAY LEVEL OF SERVICE

A horizontal number line labeled "SCALE IN FEET". The line has tick marks at 2000, 1000, 0, and 2000. The 0 mark is in the center, with 1000 to its left and 2000 to its right. There are also tick marks between 2000 and 1000 on both sides, representing 1500 and 500 respectively.

CYFB

AERODROME CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 15 JUN 23

CET9

AERODROME CHART




AERODROME CHART

EFF 20 FEB 25

CYLC

AERODROME CHART




AERODROME CHART

EFF 10 AUG 23

CYTE

AERODROME CHART

				APRT RADIO – 122.1 TFC – 122.1		MF			
DECL DIST	05	23							
TORA	5000	5000							
TODA	5295	5459							
ASDA	5000	5000							
LDA	5000	5000							



AERODROME CHART


EFF 29 DEC 22

CYBB

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

				APRT RADIO – 122.1		CTR Edmonton – 124.25 RADIO Edmonton – 123.15	
						MF	
DECL DIST	12	30					
TORA	5502	5502					
TODA	6486	6486					
ASDA	5502	5502					
LDA	5502	5502					




AERODROME CHART

CYCO

EFF 30 NOV 23

AERODROME CHART

				APRT RADIO – 122.1 TFC – 122.1		MF	
DECL DIST	08	26					
TORA	3003	3003					
TODA	3200	3200					
ASDA	3003	3003					
LDA	3003	3003					




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 7 AUG 25

CYLK

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 20 APR 23

CMR2

MAYO, YT
CYMA

		APRT RADIO - 122.1				RADIO Whitehorse - 122.37			
DECL DISTS		07	25				MF		
TORA	4843	4843							
TODA	5040	5040							
ASDA	4843	4843							
LDA	4843	4843							

ANNUAL RATE OF CHANGE 25' W

VAR 20° E 2018

135 53 135 52 135 51

63 37.2 63 37.2

63 36.8 63 36.8

Down 0.34% →

071° →

ELEV 1653

B (Private)

4843 x 100 gravel

← 251°

25

ELEV 1636

CYMA N63 37.00 W135 52.14

DEPARTURE CLIMB RATE VV (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
370 FT/NM	560	740	870	990	1110	1240	1550	1850

* DEPARTURE PROCEDURE

Rwy 07 - 1/2 - Requires a minimum climb gradient of **370 ft/NM** to **5900**.
Climb hdg **071°** to **5200** BPOC.
Note: Trees to 1696 ASL aprx 200' past departure end of rwy, 130' LEFT and 150' RIGHT of rwy centreline.

or

SPEC VIS - Climb in visual conditions to cross the aprt at or above **4900** BPOC.

Rwy 25 - SPEC VIS - Climb in visual conditions to cross the aprt at or above **4900** BPOC.

135 53 135 52 135 51

TAKE-OFF MINIMA

Rwys 07; 25: *

SCALE IN FEET

1000 0 1000 2000


CYMA

CYMA-AD

NAHANNI BUTTE, NT
CBD6

AERODROME CHART

				TFC – 123.2		ATF	
DECL DIST	16	34					
TORA	2554	2554					
TODA	2554	2554					
ASDA	2554	2554					
LDA	2554	2554					



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART


CBD6

CBD6-AD

CYUT-AD

NAUJAAT, NU
CYUT

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 20 APR 23

CYUT

CYUT-AD

AERODROME CHART



126 49

126 47

65 17.4

65 16.8

65 16.3

126 49

126 47

ELEV 237

(P2)

40

01

097°

5998 x 150

CYVQ

N65 16.88

W126 47.91

C

B

A

FSS

277°

ELEV 235

28

(P2)

40

ANNUAL RATE OF CHANGE 28' W

VAR 20° E 2019

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
280 FT/NM	420	560	660	750	840	940	1170	1400
330 FT/NM	500	660	770	880	990	1100	1380	1650

* DEPARTURE PROCEDURE

Rwy 10 - ½ - Requires a minimum climb gradient of 330 ft/NM to 4500. Climb hdg 097° to 3500 BPOC.

or

SPEC VIS - Climb in visual conditions to cross the apt at or above 3300 BPOC.

Rwy 28 - ½ - Requires a minimum climb gradient of 280 ft/NM to 4000. Climb hdg 277° to 3000 BPOC.

Note: Trees to 262 ASL aprx 0.2 NM past departure end of rwy, 250' LEFT and RIGHT of rwy centreline.

or

SPEC VIS - Climb in visual conditions to cross the apt at or above 3300 BPOC.

TAKE-OFF MINIMA

Rwys 10; 28: *

SCALE IN FEET

1000 0 1000 2000


Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 14 JUL 22

CYVQ

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 26 DEC 24

CYOC

AERODROME CHART

LWIS – 125.1				APRT RADIO – 122.1 TFC – 122.1		MF	
DECL	DISTS	06	24				
TORA		2920	2920				
TODA		3301	3904				
ASDA		2920	2920				
LDA		2920	2920				



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART


EFF 10 AUG 23

CYXP

CYPC-AD

PAULATUK (NORA ALIQATCHIALUK RUBEN), NT
CYPC

				APRT RADIO - 122.1 TFC - 122.1		MF			
DECL	DISTS	02	20						
TORA		4003	4003						
TODA		4200	4200						
ASDA		4003	4003						
LDA		4003	4003						



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART
EFF 7 OCT 21

CYPC

CYPC-AD

AERODROME CHART

MET – 128.3				APRT RADIO – 122.1 TFC – 122.1		RADIO Quebec – 123.27	
						MF	
DECL	DISTS	02	20				
TORA		4006	4006				
TODA		4990	4006				
ASDA		4006	4006				
LDA		4006	4006				

* DEPARTURE PROCEDURE

Rwy 02 - ½ - Climb between
hdg **285° T** CCW to **202° T**.


Rwy 20 - ½ - Requires a minimum climb
gradient of **350 ft/NM** to **3700**. No turn below **3700**.

Note: Hill to 258' abeam the departure end
of rwy, 150' LEFT of rwy centreline.

or
SPEC VIS - Climb in visual conditions to cross aprt at or
above **3700** BPOC.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
350 FT/NM	530	700	820	940	1050	1170	1460	1750




AERODROME CHART

EFF 20 FEB 25

CYIO

AERODROME CHART

AUTO- 122.55				APRT RADIO Broughton - 122.1			
				TFC - 122.1		MF	
DECL DIST	03	21					
TORA	3803	3803					
TODA	4787	4787					
ASDA	3803	3803					
LDA	3803	3803					




AERODROME CHART

EFF 29 DEC 22

CYVM

AERODROME CHART




AERODROME CHART

EFF 7 AUG 25

CYRT

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART


EFF 5 OCT 23

CYRB

CYSY-AD


SACHS HARBOUR (DAVID NASOGALUAK JR. SAARYUAQ), NT

CYSY



AERODROME CHART

				TFC – 123.2		CTR Edmonton – 135.4	
DECL DIST	04	22					
TORA	3501	3501					
TODA	3501	3501					
ASDA	3501	3501					
LDA	3501	3501					




AERODROME CHART

CEU9

AERODROME CHART

				APRT RADIO – 122.1 TFC – 122.1		MF			
DECL DIST	09	27							
TORA	3807	3807							
TODA	4791	4791							
ASDA	3807	3807							
LDA	3807	3807							




AERODROME CHART

EFF 15 JUN 23

CYSK

AERODROME CHART

AWOS – 128.7		APRT RADIO – 122.2 TFC – 122.2				RADIO Edmonton – 123.27			
		MF							
DECL DIST	12	30							
TORA	5410	5410							
TODA	5610	6394							
ASDA	5410	5410							
LDA	5410	5218							




AERODROME CHART

EFF 7 AUG 25

CYUX

AERODROME CHART




AERODROME CHART

EFF 26 DEC 24

CYYH

AERODROME CHART



AERODROME CHART


EFF 16 MAY 24

CYZW

CYUB-AD

TUKTOYAKTUK/JAMES GRUBEN, NT
CYUB

		APRT RADIO – 122.1 TFC – 122.1				CTR Edmonton – 132.4			
						MF			
DECL DIST	11	29							
TORA	4600	4600							
TODA	4800	4800							
ASDA	4600	4600							
LDA	4600	4600							




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

CZFN-AD

TULITA, NT
CZFN

AERODROME CHART

				● APRT RADIO – 122.1 ● TFC – 122.1		MF	
DECL DIST	07	25					
TORA	3935	3935					
TODA	4135	4135					
ASDA	3935	3935					
LDA	3935	3935					



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART


CZFN

EFF 2 DEC 21

CZFN-AD

AERODROME CHART

				APRT RADIO – 122.1 TFC – 122.1		RADIO Edmonton – 123.47	
				MF			
DECL	DISTS	06	24				
TORA		4300	4300				
TODA		5284	5284				
ASDA		4300	4300				
LDA		4300	4300				




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 30 NOV 23

CYHI

AERODROME CHART




AERODROME CHART

EFF 7 OCT 21

CYQH

AERODROME CHART

AWOS – 128.7				TFC – 123.2		ATF			
DECL DIST	13	31							
TORA	2999	2999							
TODA	3196	3196							
ASDA	2999	2999							
LDA	2999	2999							



AERODROME CHART

CYWE


EFF 10 AUG 23

CYXN-AD

WHALE COVE, NU
CYXN

AERODROME CHART

				APRT RADIO – 122.1 TFC – 122.1		MF			
DECL	DISTS	15	33						
TORA		3937	3937						
TODA		3937	3937						
ASDA		3937	3937						
LDA		3937	3937						



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 7 AUG 25

CYXN

CYXN-AD

AERODROME CHART



AERODROME CHART

CEM3

EFF 30 NOV 23

WHITEHORSE/ERIK NIELSEN INTL, YT
CYXY

ATIS - 125.25		GND - 121.9		TWR - 118.3 236.6 RADIO - 118.3		CTR Edmonton - 134.15	
DECL DISTS		02	20	14R	32L	14L	32R
TORA	1239	nu	9500	9500	6597	6597	
TODA	1239	nu	10484	10484	9877	6597	
ASDA	1239	nu	9500	9500	6597	6597	
LDA	nu	1239	9500	9500	6597	6597	

*** DEPARTURE PROCEDURE**
Rwys 14L, 14R, 32L, 32R - Refer to SID.
 or
 SPEC VIS - Climb in visual conditions to cross the apt at or above **6300** BPOC.

SCALE IN FEET
 1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 2 OCT 25

CYXY

CYXY-AD

AERODROME CHART



AERODROME CHART

EFF 20 FEB 25

CYWY

YELLOWKNIFE, NT
CYZF

ATIS - 128.4		GND - 121.9		TWR - 118.5 340.8 RADIO - 118.5		CTR Edmonton - 135.8 RADIO Edmonton - 123.37 5680	
DECL DISTS	10	28	16	34			
TORA	5001	5001	7503	7503			
TODA	5985	5985	8487	8487			
ASDA	5001	5001	7503	7503			
LDA	5001	5001	7503	7503			

***DEPARTURE PROCEDURE**

Rwy 10 - ½
Note: Trees to 712 ASL apx 0.3 NM past departure end of rwy, 220' LEFT of rwy centreline.

Rwy 16 - ½
Note: Trees to 682 ASL apx 0.2 NM past departure end of rwy, 150' RIGHT of rwy centreline.

Rwy 28 - ½
Note: Trees to 709 ASL apx 0.24 NM past departure end of rwy, 470' LEFT of rwy centreline.
Tower to 817 ASL apx 0.9 NM past departure end of rwy, 1400' RIGHT of rwy centreline.

RUNWAY LEVEL OF SERVICE

RVO	LVO
RWY 34: RVR 1200 RWY 16: (¼ sm)	NOT AUTHORIZED


TAKE-OFF MINIMA	SCALE IN FEET
Rwy 34: ½ Rwys 10; 16; 28: ★	

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

CYZF

CYZF-AD


AERODROME CHART



CAJ4-AD

ANAHIM LAKE, BC
CAJ4

AERODROME CHART




AERODROME CHART

EFF 14 JUL 22

CAJ4

CAJ4-AD

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART


EFF 10 SEP 20

CBBB

CAMPBELL RIVER, BC
CYBL

AERODROME CHART

● ATIS – 128.55				● RADIO – 122.0		TML Comox – 123.7 227.6	
				● TFC – 122.0		RADIO Pacific – 123.55	
						MF*	
DECL DISTS	12	30					
TORA	6499	6499					
TODA	7483	7483					
ASDA	6499	6499					
LDA	6499	6499					



RUNWAY LEVEL OF SERVICE		
RVO	LVO	
RWY 12: RVR 1200 Day only RWY 30: (1/4sm) Day only	NOT AUTHORIZED	
TAKE-OFF MINIMA		
Rwys 12; 30: *	SCALE IN FEET 1000 0 1000	

AERODROME CHART


EFF 26 DEC 24

CYBL

CYBL-AD

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART




AERODROME CHART

EFF 11 JUL 24

AERODROME CHART

LWIS – 122.55				TFC – 123.2		CTR – Edmonton 132.6	
						ATF	
DECL DIST	05	23					
TORA	4481	4481					
TODA	4481	4481					
ASDA	4481	4481					
LDA	4481	4481					



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART


EFF 25 APR 19

CYCQ

COMOX, BC
CYQQ

AERODROME CHART (DND)

ATIS – 118.6 282.2		CLNC DEL – 127.0 227.6		TWR – 126.2 358.1		DEP – 123.7 227.6	
		GND – 119.75 250.3					
DECL DIST	12	30	18	36			
TORA	10001	10001	4998	4998			
TODA	10001	10001	4998	4998			
ASDA	10001	10001	4998	4998			
LDA	10001	10001	4998	4998			



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART (DND)

EFF 2 OCT 25

CYQQ

CYQQQ-AD

AERODROME CHART




AERODROME CHART

EFF 12 JUN 25

CYXC

AERODROME CHART

LWIS – 129.17						UNICOM – 122.8		CTR Vancouver – 133.6	
						ATF			
DECL DIST	15	33							
TORA	3944	3944							
TODA	3944	3944							
ASDA	3944	3944							
LDA	3944	3944							



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 17 APR 25

CAJ3

AERODROME CHART

AWOS – 128.55				● RADIO Yellowknife – 122.2		● RADIO Yellowknife – 122.2	
				● TFC – 122.2		MF	
DECL DIST	07	25					
TORA	5001	5001					
TODA	5985	5785					
ASDA	5001	5001					
LDA	5001	5001					




AERODROME CHART

EFF 11 JUL 24

AERODROME CHART

AUTO – 122.97				TFC – 123.2		CTR Vancouver – 133.6	
						ATF	
DECL DIST	16	34					
TORA	6005	6005					
TODA	6005	6005					
ASDA	6005	6005					
LDA	6005	5184					




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 20 FEB 25

CYCZ

AERODROME CHART



122 37

122 36

122 35

↑

VAR 18° E

2020

ANNUAL RATE
OF CHANGE 17° W

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
290 FT/NM	440	580	680	780	870	970	1210	1450

ELEV 1247

P2

219°

AO*

ELEV 1279

EAST APRON

II

B

26

ELEV 1227

264°

084°

Down 0.64%

3575 x 77

ELEV 1250

80'

6402 x 150

1293

039°

AN

ELEV 1253

CYYE

N58 50.23

W122 36.08

★ DEPARTURE PROCEDURE

Rwy 04 - ½

Note: Trees to 1337 ASL aprx 0.2 NM past departure end of rwy, 100' LEFT of rwy centreline.

Rwy 22 - ½ - Requires a minimum climb gradient of 290 ft/NM to 2200.

Climb hdg 219° to 2400 BPOC.

Note: Trees to 1339 ASL aprx 0.3 NM past departure end of rwy, 800' LEFT and 1000' RIGHT of rwy centreline.

or

SPEC VIS - Climb in visual conditions to cross the aprt at or above 2400 BPOC.

TAKE-OFF MINIMA

Rwys 04; 22: ★

SCALE IN FEET

1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 7 AUG 25

CYYE

AERODROME CHART

● ATIS – 128.5		● CLNC DEL – 121.9		RADIO – 118.5		CTR Edmonton – 132.6 285.4 RADIO Edmonton – 123.55	
				MF			
DECL DIST	03	21	12	30			
TORA	6698	6698	6909	6909			
TODA	7508	7518	7734	7893			
ASDA	6698	6698	6909	6909			
LDA	6698	6502	6909	6909			




RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 30: RVR 1200 RWY 12: (1/4sm)	NOT AUTHORIZED
TAKE-OFF MINIMA	
All Rwys: 1/2	

AERODROME CHART

EFF 25 JAN 24

AERODROME CHART


				TFC – 122.8		MF		CTR Vancouver – 132.35 RADIO Pacific – 122.37	
DECL DIST	14	32							
TORA	4528	4528							
TODA	4528	4528							
ASDA	4528	4528							
LDA	4528	4528							



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

AUTO – 122.55				TFC – 123.2		CTR Vancouver – 134.2 RADIO Pacific – 125.85	
						ATF	
DECL DIST	07	25					
TORA	4311	4311					
TODA	4700	4790					
ASDA	4311	4311					
LDA	4311	4311					



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 10 SEP 20

CZGF


CYKA

		● CLNC DEL – 121.9			RADIO – 125.7		CTR Vancouver – 132.35	
					MF			
DECL DIST	09	27	05	23				
TORA	8000	8000	1875	1875				
TODA	8984	8984	1875	1875				
ASDA	8000	8000	1875	2552				
LDA	8000	8000	1875	1626				



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

PARKING AREAS



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

PARKING AREAS

EFF 5 SEP 24

CYKA


PARKING AREAS

Aircraft Parking Position


Position	Coordinates	Position	Coordinates
1	504218.39N 1202625.48W	4A	504216.53N 1202630.20W
2	504217.50N 1202627.71W	5	504215.62N 1202633.07W
3	504216.91N 1202629.39W	6	504215.03N 1202634.55W
4	504216.14N 1202631.59W		

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART



PARKING AREAS (APRON I)




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

PARKING AREAS (APRON I)

CYLW

EFF 11 JUL 24

PARKING AREAS (APRON III)




PARKING AREAS (APRON III)

EFF 21 MAR 24

CYLW

AERODROME CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 2 OCT 25

TAXI CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

TAXI CHART

EFF 2 OCT 25


CYNJ

CYZY-AD

MACKENZIE, BC
CYZY

AERODROME CHART

AWOS – 127.7				TFC – 123.5		RADIO Pacific – 123.47	
						MF	
DECL DIST	17	35					
TORA	5033	5033					
TODA	6017	5033					
ASDA	5233	5233					
LDA	5033	5033					



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 30 JAN 20


CYZY

CYZY-AD

AERODROME CHART



AERODROME CHART



123 53

123 52.5

123 52

49 03.8

49 03.4

49 03

123 53

123 52.5

123 52

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
400 FT/NM	600	800	940	1070	1200	1340	1670	2000

★ DEPARTURE PROCEDURE

Rwy 16 - Refer to SID.

or

SPEC VIS - Climb visual over apt to **2000**. Continue climb INBD track **342°** to "YCD" NDB. Then shuttle climb INBD track **191°** (max **200** kt, LEFT turns) to **MEA** BPOC.

Rwy 34 - ½ - Requires a minimum climb gradient of **400** ft/NM to **1600**. Climb INBD track **342°** to "YCD" NDB. Then shuttle climb INBD track **191°** (max **200** kt, LEFT turns) to **MEA** BPOC.

Note: Trees to 156 ASL aprx 200' past departure end of rwy, 300' LEFT of rwy centreline. Pole to 149 ASL aprx 0.1 NM past departure end of rwy, 650' RIGHT of rwy centreline. Trees to 208 ASL aprx 0.3 NM past departure end of rwy.

or

SPEC VIS - Climb in visual conditions to cross the apt at or above **2000**. Continue climb INBD track **342°** to "YCD" NDB. Then shuttle climb INBD track **191°** (max **200** kt, LEFT turns) to **MEA** BPOC.

AW

91

ELEV 75

164°

Threshold 16 displaced 197'.

Taxiway G and Apron II day use only, rstd to 5,000 lbs

CYCD N49 03.27 W123 52.21

6602 x 150

FSS

Grass Tie Down Area

AS

34

344°

ELEV 92

Threshold 34 displaced 1002'.

P2 - Rwy 34 - 3.5° & offset 8° right OCL 3 NM.

ANNUAL RATE OF CHANGE 9' W

Var 17° E 2015

RUNWAY LEVEL OF SERVICE

RVO

LVO

RWY 34: (¼ sm)

NOT AUTHORIZED

TAKE-OFF MINIMA

Rwys 16; 34: ★

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART


EFF 26 DEC 24

CYCD

CDH5-HP

NANAIMO/NANAIMO HARBOUR HELIPORT, BC
CDH5

HELIPORT CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

CYYF-AD

PENTICTON, BC
CYYF

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

CYYF

EFF 2 OCT 25


CYYF-AD

CYPK

[illegible]

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART




AERODROME CHART

AERODROME CHART

				RADIO Hardy – 122.2			CTR Vancouver – 132.2 266.3	
						MF*		
DECL DIST	08	26	11	29	16	34		
TORA	4000	4000	4999	4999	3984	3984		
TODA	4902	4000	5983	5819	3984	4476		
ASDA	4000	4000	4999	4999	3984	3984		
LDA	4000	4000	4999	4999	3984	2493		



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 29: (¼ sm)	NOT AUTHORIZED
TAKE-OFF MINIMA	
Rwys 08, 34: NOT ASSESSED Rwys 11, 16, 26, 29: *	




AERODROME CHART

EFF 16 MAY 24

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART



AERODROME CHART

EFF 12 JUN 25

CYPW

CYXS

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
320 FT/NM	480	640	750	860	960	1070	1340	1600
370 FT/NM	560	740	870	990	1110	1240	1550	1850
410 FT/NM	620	820	960	1100	1230	1370	1710	2050

*** DEPARTURE PROCEDURE**

Rwy 06 - 1/2 - Requires a minimum climb gradient of **370 ft/NM to 4900**. Climb INBD **R-249** to "YXS" VOR. Then shuttle INBD **R-249** to MEA BPOC.

Note: Road to 2254 ASL aprx 0.1 NM past departure end of rwy, LEFT and RIGHT of rwy centreline.

Rwy 15 - 1/2 - Requires a minimum climb gradient of **410 ft/NM to 5400**.

Note: Trees to 2332 ASL aprx 0.4 NM past departure end of rwy, 90° LEFT of rwy centreline.

Rwy 33 - 1/2 - Requires a minimum climb gradient of **320 ft/NM to 4900**.

Note: Trees to 2376 ASL aprx 0.5 NM past departure end of rwy, 90° LEFT of rwy centreline.

or

Rwy 06, 15, 24, 33 - SPEC VIS - Climb visual over apt to **4100** BPOC.

Rwy 01-19 restricted to 12,500 lbs for take-off and landing, day only.

Threshold 19 displaced 373'

Threshold 24 displaced 401'

Threshold 01 displaced 984'

Threshold 33 displaced 500'

AN 153° Down 0.3%

Up 0.87%

11,450 x 150

333°

VAR 18° E 2014

ANNUAL RATE OF CHANGE 15' W

ELEV 2231

ELEV 2229

ELEV 2266

ELEV 2234

ELEV 2217

ELEV 2195

AS

TWR

CYXS N53 53.04 W122 40.65

3769 x 75

5624 x 150

013°

243°

063°

90°

122 42

122 41

122 40

53 53.5

53 53

53 53

53 52.5

122 42

122 41

122 40

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 15: RVR 1200 RWY 33: (1/4sm)	NOT AUTHORIZED
TAKE-OFF MINIMA	
Rwys 01, 19: Not assessed Rwys 15, 33, 06, 24: ★	SCALE IN FEET

CYXS

CYXS-AD

AERODROME CHART


AWOS – 128.57				TFC – 122.5		CTR Vancouver – 133.67	
				MF*			
DECL DISTS	13	31					
TORA	6000	6000					
TODA	6853	6984					
ASDA	6000	6000					
LDA	6000	6000					



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 13: RVR 1200 RWY 31: (1/4sm)	NOT AUTHORIZED
TAKE-OFF MINIMA	SCALE IN FEET 1000 0 1000
Rwys 13, 31: *	

AERODROME CHART

				TFC – 123.2		CTR Vancouver – 135.0 351.3	
						ATF	
DECL DIST	04	22					
TORA	3932	3932					
TODA	4916	4732					
ASDA	3932	3932					
LDA	3932	3932					




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 31 OCT 24

CYDC


				TFC – 122.8		TML Comox – 123.7 227.6	
				MF			
DECL DIST	11	29					
TORA	3564	3564					
TODA	3564	3564					
ASDA	3564	3564					
LDA	3079	3313					



QUESNEL, BC
CYQZ

AERODROME CHART

AWOS – 124.4						RADIO Williams Lake – 122.2 TFC – 122.2		CTR Vancouver – 134.0 381.4	
DECL DIST	13	31					MF		
TORA	5501	5501							
TODA	6485	6041							
ASDA	5501	5501							
LDA	5501	5501							




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

CYZP-AD

SANDSPIT, BC
CYZP

AERODROME CHART

AWOS – 128.75				RADIO Terrace – 122.3 296.2		CTR Vancouver – 133.67 227.2	
						MF	
DECL DIST	13	31					
TORA	5112	5112					
TODA	5112	5112					
ASDA	5112	5112					
LDA	5112	5112					



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART


EFF 20 FEB 25

CYZP

CYZP-AD

AERODROME CHART

AWOS – 128.65				RADIO – 122.3		CTR Vancouver – 132.52 RADIO Pacific – 123.37	
				TFC – 122.3		MF	
DECL	DISTS	15	33				
TORA		7547	7547				
TODA		8302	8167				
ASDA		7547	7547				
LDA		7287	7283				




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 2 OCT 25

CYYD

HELIPORT CHART




HELIPORT CHART

EFF 7 OCT 21

CSR6

AERODROME CHART

LWIS – 122.55				TFC – 123.2		CTR Vancouver – 134.0 381.4	
DECL DIST	15	33				ATF	
TORA	5292	5292					
TODA	5292	5292					
ASDA	5292	5292					
LDA	4877	5292					



AERODROME CHART


EFF 7 AUG 25

CZML

CYSW-AD

SPARWOOD/ELK VALLEY, BC
CYSW

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

CYSW

EFF 5 OCT 23

CYSW-AD


AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

				● RADIO Hardy – 123.25		CTR Vancouver – 132.9	
				● TFC – 123.25		RADIO Pacific – 125.85	
				MF			
DECL	DISTS	07	25	11	29	16	34
TORA		5000	5000	5000	5000	5000	5000
TODA		5000	5000	5000	5000	5000	5000
ASDA		5000	5000	5000	5000	5000	5000
LDA		4265	4642	4500	5000	4792	4113




AERODROME CHART

EFF 31 OCT 24

CYAZ

AERODROME CHART




AERODROME CHART

CAD4

EFF 11 JUL 24

CYVR

DECL DISTS	08R	26L	08L	26R	13	31		
TORA	11500	11493	9941	9941	7300	7300		
TODA	12484	17239	11417	14911	8284	8284		
ASDA	11500	11493	9941	9941	7300	7300		
LDA	10804	10804	9941	9941	7300	7300		



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

TAXI CHART

Notes		
AGN (ICAO Code)	MAX WINGSPAN	AVAILABLE TAXIWAYS
AGN VI (Code F) & Smaller	Max Wingspan: 79.9m/262.1'	D, D5, D7, D9, DT, H (north of Rwy 08R/26L), J (north of parking position W2), JA, K (west of R), L (west of Rwy 13/31), L4, L6, M ^{NOTE 1} , M5, M6, M7, M9, M10, R, V.
AGN V (Code E) & Smaller	Max Wingspan: 65.0m/213.3'	A (west of Rwy 13/31)* & btwn E and Rwy 13/31, A4*, A6*, D, D1*, D3, D5, D7, D9, DT, DU*, DV, E (north of Rwy 08R/26L)*, E (south of Rwy 08R/26L), H (north of Rwy 08R/26L), H4*, J, JA, JB, JC, K, L, L2*, L4, L6, M, M1*, M2*, M3*, M4, M5, M6, M7, M8, M9, M10, N7, P, Q, R, T, V. *Not avbl for A340-600, A350-900/-1000, B777-300/-300ER, B787-10 only due acft wheelbase.
AGN IV (Code D) & Smaller	Max Wingspan: 52.0m/170.6'	A, A4, A5, A6, AR, C (north of F), D, D1, D3, D5, D7, D9, DR, DS, DT, DU, DV, DY, E, F (west of C), G, H, H2, H4, J, JA, JB, JC, K, L, L2, L4, L6, M, M1, M2, M3, M4, M5, M6, M7, M8, M9, M10, N7,P,Q, R, S, T, V.

Note 1: When acft with wingspan greater than 65.0m/213.3' (A380/B747-8) is on the taxilane btwn Gate 66 & Gate 72, Twy M btwn Twy J and Twy T is avbl to acft with wingspan 52.0m/170.6' (A310/B767) & smaller only.

Rwy 08L Arrivals
Use of reverse thrust is to be avoided or reduced when conditions permit. M1, M3, M5 (rapid exit): Design speed in wet conditions is 50 kt (93 km/h). Reverse turns NOT AUTHORIZED without clearance.

Rwy 08R Arrivals
Acft exiting onto D1, turn north on E, do not stop in Rwy area (See HOT SPOT 4). D1, D3 (rapid exit): Design speed in wet conditions is 50 kt (93 km/h). Reverse turns NOT AUTHORIZED without clearance.

Rwy 13 Departures
Not avbl for acft with wingspan greater than 65.0m/213.3' (A380/B747-8/AN124). Not auth for A340-600, A350-900/-1000, B777-300/-300ER, B787-10.

Rwy 26R Arrivals
Use of reverse thrust is to be avoided or reduced when conditions permit. M2, M4, M6 (rapid exit): Design speed in wet conditions is 50 kt (93 km/h). Reverse turns NOT AUTHORIZED without clearance.

Rwy 26L Arrivals
Turns onto Rwy 31 NOT AUTHORIZED without clearance. Acft exiting onto Rwy 13/31: RIGHT turns onto D avbl to acft with wingspan 52.0m/170.6' (A310/B767) & smaller only. Acft exiting onto H, hold short of D, do not stop in Rwy area (See HOT SPOT 4). Reverse turns NOT AUTHORIZED without clearance.

Rwy 31 Arrivals
Not avbl for acft with wingspan greater than 65.0m/213.3' (A380/B747-8/AN124). Not auth for A340-600, A350-900/-1000, B777-300/-300ER, B787-10.

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

TAXI CHART

Notes**Taxiway Limitations**

All Twys: Discretionary oversteer is required at every intersection for all acft types.

A: Compass Rose: Not avbl SS-SR. Avbl to acft with wingspan 24.1m/79' (SF34) & smaller only.

A2: Avbl to acft with MTOW 50,000lbs (DHC-8 300/Lear 60) & less.

C (south of F): Avbl to acft with wingspan 36.0m/118.1' (A321/B737) & smaller only. Follow me required below RVR 1200, ctc Aprt Ops.

D: CAUTION: Acft cannot safely taxi via Twy D east or west past acft at the Twy D5 or Twy D7 runway holding positions.

D2: Avbl to acft with MTOW 100,000lbs (CRJ-900) & less.

DW: Avbl to acft with wingspan 41.1m/134.8' (B757) & smaller only.

E: Entry & exit at Apron VI avbl to acft with wingspan 60.4m/198.2' (A330-300/B787-9) & smaller only.

F (east of C): Avbl to acft with wingspan 24.9m/81.7' (CRJ-900) & smaller only. Follow me required below RVR 1200, ctc Aprt Ops.

J (southbound): A340, B747 not auth south of Twy K due jet blast (avbl for acft under tow).

L: Entry & exit at Apron VI avbl to acft with wingspan 36.0m/118.1' (A321/B737) & smaller only.

Q: Follow me required below RVR 1200, ctc Aprt Ops.

Turn Restrictions

A (westbound): RIGHT turns onto E avbl to acft with wingspan 24.1m/79.0' & smaller only.

D (eastbound): LEFT turns onto H avbl to acft with wingspan 36.0m/118.1' (A321/B737) & smaller only.

D (westbound): No LEFT turns onto H. No LEFT turns onto D7.

D7: No RIGHT turns onto D.

E (southbound): LEFT turns onto A avbl to acft with wingspan 24.1m/79.0' & smaller only.

H (southbound): No RIGHT turns onto A, L, or H4. RIGHT turns onto D avbl to acft with wingspan 36.0m/118.1' (A321/B737) & smaller only. No LEFT turns onto D1.

H (northbound): No LEFT turns onto V. No RIGHT turns onto D. RIGHT turns onto L avbl to acft with wingspan 36.0m/118.1' (A321/B737) & smaller only.

J (southbound): All acft use min thrust when turning due jet blast.

J (northbound): LEFT turns onto K avbl to acft with wingspan 41.1m/134.8' (B757) & smaller only, due jet blast (avbl for acft under tow).

L: No RIGHT turns onto V.

L4 (northbound): Only acft with a max wingspan of 52.0m/170.6' (e.g. A310/B767) can hold short of L while exiting/crossing Rwy 08R/26L due to acft tail height.

M4: LEFT and RIGHT turns onto M not avbl for A340-600, A350-900/-1000, B777-300/-300ER, B787-10 only, due acft wheelbase.

P: RIGHT turns onto M avbl to acft with wingspan 52.0m/170.6' (A310/B767) & smaller only, due jet blast (avbl for acft under tow).

V: (northbound) No RIGHT turns onto H.

V: (southbound) No LEFT turns onto L.

TAXI CHART

EFF 17 APR 25

CYVR

TAXI CHART

Notes**Uncontrolled Taxiways**

C (south of F), F, J (btwn K & L), Q, DR, DS, DT, DU, DV & DW.

Uncontrolled Vehicle Crossings

DS, DT, DU, DV, DY, F, H (north of H4), J, JA, JB, JC, K, N7, P, Q, R, S, T, V.

APU Shutdown Procedure

Acft Auxiliary Power Unit (APU) use shall be limited to 15 min or less in total between on-block time and departure of acft from stands supplied with Ground Power Unit (GPU) and/or preconditioned air, for environmental reasons, if the outside air temperature is between 0 degrees and 20 degrees Celsius.

Acft shall not need to comply with the above limitations on stands not equipped with serviceable GPU and/or preconditioned air or if there are overriding health & safety considerations.

Apron Notes

Apron I, II, III, IV, V, VI, VIII: PPR Airport Ops is required. PPR for all engine airstarts or crossbleed starts. Advise ATC if ground crew not present at gate.

Apron I: Avbl to acft with wingspan 24.9m/81.7' (CRJ-900) & smaller only. Hover taxi not auth, heli must ground taxi or be towed.

Apron II: Avbl to acft with wingspan 52.0m/170.6' (A310/B767) & smaller only. Hover taxi not auth, heli must ground taxi or be towed.

Apron III: Avbl to acft with wingspan 36.0m/118.1' (A321/B737) & smaller only. Jets tow in & out. Hover taxi not auth, heli must ground taxi or be towed.

Apron IV: Avbl to acft with wingspan 41.1m/134.8' (B757) & smaller only. Taxilane east of DW avbl to acft with wingspan 32.1m/105.3' (CV-580) & smaller only. Btwn DW & FedEx not auth for taxi below RVR 1200, follow me required, ctc Aprt Ops.

Apron VI (Horseshoe): Taxilanes avbl to acft with wingspan 36.0m/118.1' (A321/B737) & smaller only.

Apron VI (South): Taxilane btwn G & parking position S1 avbl to acft with wingspan 52.0m/170.6' (A310/B767) & smaller only.

Apron VI (South): Taxilane east of parking position S1 avbl to acft with wingspan 60.4m/198.2' (A330-300/B787-9) & smaller only.

Apron VI (North): Travelling eastbound, turns onto P avbl to acft with wingspan 52.0m/170.6' (A310/B767) & smaller only, due jet blast (avbl for acft under tow).

Apron VI (North): When acft with wingspan greater than 65.0m/213.3' (A380/B747-8) is on M btwn J & T, the taxilane between Gate 66 & T is avbl to acft with wingspan 52.0m/170.6' (A310/B767) & smaller only.

Apron VI (East): Bypass taxilane (amber inset lighting) avbl to acft with wingspan 36.0m/118.1' (A321/B737) & smaller only.

Apron VI (East): Simultaneous use of dual taxilanes avbl to acft with wingspan 36.0m/118.1' (A321/B737) & smaller only.

Apron VI (East): Pushbacks from parking positions E1-E3 to west taxilane. Pushbacks from parking positions E10-E19 to south taxilane.

Apron VIII: Avbl to acft with wingspan 52.0m/170.6' (A310/B767) & smaller only.

Btwn Purolator & FedEx Aprons: Avbl to acft with wingspan 17.4m/57.1' (Metro III) & smaller only.

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

TAXI CHART

EFF 7 AUG 25

CYVR

TAXI CHART

Notes


Hot Spots

- HS 1: Twy D9 commences beyond the rwy hold line for Rwy 08R/26L on Twy D and Twy DY.
Acft cannot safely taxi via Twy D east or west past acft at the Twy D5 or Twy D7 hold lines.
- HS 2: Twy L6 hold line for Rwy 08R is displaced 166m (545 ft) from rwy edge.
- HS 3: Taxiing to Rwy 08R/26L, acft fail to hold short and incur on Rwy 13/31 on Twy A. Taxiing across Rwy 08R/26L, acft fail to hold short and incur on Rwy 13/31 on Twy E.
- HS 4: Acft taxiing H, southbound, hold line is located 30m (100 ft) back from the standard rwy hold position. Acft exiting onto D1, turn north on E. Do not stop in rwy area.
- HS 5: Twy N7 hold line for Rwy 26R is displaced at intersection of Twy N7 and Apron IX 214m (702 ft) from rwy edge.

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

TAXI CHART

ATIS – 124.6	CLNC DEL – 121.4 GND – 121.7 (S) 127.15 (N) 275.8	TWR – 118.7 (S) 119.55 (N) 226.5
--------------	--	----------------------------------



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

TAXI CHART

EFF 20 FEB 25

CODED TAXI ROUTES

Read Back: “Code Route (code) and Assigned Runway”

Monitor tower frequency approaching the hold line of the assigned runway,
unless otherwise instructed by ATC.

Rwy 08R/26L – TWR 118.7 Rwy 08L/26R – TWR 119.55

Code	Taxi Route
Echo	Rwy 08R – E, D, H, hold short L. Rwy 08L – E, D, H, hold short V, contact ground 127.15 (expect taxi via H, M, M10). Rwy 26R – E, D, H, hold short V, contact ground 127.15 (expect taxi via V, M, M9). Rwy 26L – E, D.
Golf	Rwy 08R – G, H, hold short L. Rwy 08L – G, H, hold short V, contact ground 127.15 (expect taxi via H, M, M10). Rwy 26R – G, H, hold short V, contact ground 127.15 (expect taxi via V, M, M9). Rwy 26L – G, H, D.
Juliet-Alfa*	Rwy 08R – JA, J, K, V, hold short H, contact ground 121.7 (expect taxi via V, L, L6). Rwy 08L – JA, J, M, M10. Rwy 26R – JA, J, M, M9. Rwy 26L – JA, J, K, V, hold short H, contact ground 121.7 (expect taxi via H, D).
Juliet-Bravo*	Rwy 08R – JB, J, K, V, hold short H, contact ground 121.7 (expect taxi via V, L, L6). Rwy 08L – JB, J, M, M10. Rwy 26R – JB, J, M, M9. Rwy 26L – JB, J, K, V, hold short H, contact ground 121.7 (expect taxi via H, D).
Juliet-Charlie*	Rwy 08R – JC, K, V, hold short H, contact ground 121.7 (expect taxi via V, L, L6). Rwy 08L – JC, J, M, M10. Rwy 26R – JC, J, M, M9. Rwy 26L – JC, K, V, hold short H, contact ground 121.7 (expect taxi via H, D).
Lima	Rwy 08L – L, H, hold short V, contact ground 127.15 (expect taxi via H, M, M10). Rwy 26R – L, H, hold short V, contact ground 127.15 (expect taxi via V, M, M9). Rwy 26L – L, J, H, D.
Papa*	Rwy 08R – P, M, V, hold short H, contact ground 121.7 (expect taxi via V, L, L6). Rwy 08L – P, M, M10. Rwy 26R – P, M, M9 (avbl to acft with wingspan 52.0m (170.6') & smaller only). Rwy 26L – P, M, V, hold short H, contact ground 121.7 (expect taxi via H, D).
Sierra	Rwy 08R – S, M, V, hold short H, contact ground 121.7 (expect taxi via V, L, L6). Rwy 08L – P, M, M10. Rwy 26R – P, M, M9 (avbl to acft with wingspan 52.0m (170.6') & smaller only). Rwy 26L – S, M, V, hold short H, contact ground 121.7 (expect taxi H, D).
Tango*	Rwy 08R – T, M, V, hold short H, contact ground 121.7 (expect taxi via V, L, L6). Rwy 08L – T, M, M10. Rwy 26R – T, M, M9 Rwy 26L – T, M, V, hold short H, contact ground 121.7 (expect taxi via H, D).

*A340-600, A350-900/-1000, B777-300/-300ER, B787-10 Taxi Routes.

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

LOW VISIBILITY PROCEDURES

Low Visibility Procedures (RVR less than 1200 to 600 ft)**Application**

These procedures apply to ground movements of aircraft arriving and departing under low visibility conditions. Arrivals and departures below RVR 600 are not authorized. When weather conditions indicate visibility below RVR 1200 is imminent, procedures will be implemented restricting aircraft and vehicle operations on the movement area. The following message will be added to the ATIS broadcast: "Low visibility procedures in effect for <name of applicable runway>".

General**Taxi Routes**

Low Visibility Taxi Routes are equipped with green inset centerline lighting. Some taxiway/taxiway intersections have been identified with three inset yellow centerline lights. Midfield crossings of 08R/26L are not permitted during low visibility operations.

Airport Surface Detection Equipment (ASDE)

Ground radar is used to monitor the position of aircraft operating on the manoeuvring area. In the event of an ASDE failure, ATC may suspend, restrict or terminate low visibility operations.

Departures

The primary runways for departure are 08R/26L. Yellow flashing runway guard lights (wig-wags) and stop bars are installed abeam each hold line. Intersection take-offs are not permitted.

Sequencing of Aircraft Ground Movements for Take-off

Do not request start, push back or call for taxi clearance until the reported RVR is greater than:

Aircraft/Pilot Take-off Minima	Minimum RVR for Start
1200 RVR	1000 RVR
600 RVR	600 RVR

SMGCS Rwy 08L/26R and 08R/26L

Runway/taxiway intersections are equipped with yellow flashing runway guard lights and stop bars consisting of red inset lights and red elevated lights located at the taxi hold position.

At runway entry points, M10, M8, M7, M9, N7, L4, L6, D, D5, D7, DY, A5 and A, when the red stop bar lights are illuminated, green lead-on lights beyond the stop bar are extinguished. When ATC issues a clearance to proceed onto the runway, the red stop bar lights will be extinguished and the green lead-on lights beyond the stop bar will be illuminated. The stop bar is reset automatically as the aircraft moves onto the runway.

"AT NO TIME SHALL A PILOT CROSS AN ILLUMINATED RED STOP BAR"

Arrivals


The primary runways for arrival are 08L/26R.

Plan to exit on the centerline lighted rapid exit taxiways and proceed beyond the alternating green and yellow centerline lights to the taxi intersection lights to ensure the aircraft is clear of the runway and the ILS sensitive area.

LOW VISIBILITY TAXI CHART

LAND RWY 08L/08R, DEPART RWY 08L/08R (RVR LESS THAN 1200 TO 600 FT)

VANCOUVER INTL, BC
CYVR




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

LAND RWY 08L/08R, DEPART RWY 08L/08R (RVR LESS THAN 1200 TO 600 FT)

LOW VISIBILITY TAXI CHART

LAND RWY 26L/26R, DEPART RWY 26L/26R (RVR LESS THAN 1200 TO 600 FT)

ATIS – 124.6	CLNC DEL – 121.4 GND – 121.7 (S) 127.15 (N) 275.8	TWR – 118.7 (S) 119.55 (N) 226.5
--------------	--	----------------------------------



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

LAND RWY 26L/26R, DEPART RWY 26L/26R (RVR LESS THAN 1200 TO 600 FT)

LOW VISIBILITY TAXI CHART

CYVR
EFF 12 JUN 25

DE-ICING GENERAL

Overview

West Pads is the Central De-Icing Facility (CDF) and handles de-icing for all aircraft excluding South Terminal aircraft capable of utilizing the Ground Run-Up Enclosure (GRE) which is the South De-Icing Facility.

West Pads (CDF)

1. Thirty (30) min prior to pushback or taxi, advise "VANCOUVER DE-ICE" on 129.95 and advise, "ACFT DE-ICING REQUIRED".
2. When requesting pushback, ctc Ground Control on assigned frequency and advise, "ACFT DE-ICING REQUIRED". Ground Control will issue taxi instructions to the West Pads (CDF).
3. Aircraft queuing into CDF is on W12 via Twy V or on Twy R via Twy M/Twy K. When instructed by Ground Control, ctc "PAD CONTROL" 131.975.
4. Follow "PAD CONTROL" instructions to de-icing bay, stop with nose gear positioned on the yellow STOP BAR with brakes set.
5. Once aircraft is in final stop position, brakes are set and aircraft configured for de-icing, ctc "ICEMAN" on 130.700 and advise, "BRAKES SET, ACFT CONFIGURED, READY TO DE-ICE". At this time, pass along any specific fluid and/or treatment requirements.
6. After de-icing is completed and the aircraft has been inspected, "ICEMAN" will provide post-treatment information.
7. When advised by "ICEMAN", ctc "PAD CONTROL" on 131.975 for exit instructions.
8. When advised by "PAD CONTROL", ctc Ground Control on assigned frequency for taxi instructions.

UNDER NO CIRCUMSTANCES MAY THE AIRCRAFT BE MOVED BEFORE PAD CONTROL ADVISES THAT THE AIRCRAFT IS CLEARED TO TAXI OUT OF THE BAY.

West Pads (CDF) De-Icing Bay Capacity:

W1 & W3: Maximum wingspan 36.0m (118.1'), AMBER inset lighting;

W2: Maximum wingspan 65.0m (213.3'), GREEN inset lighting;

W4: Maximum wingspan 36.0m (118.1'), AMBER inset lighting;

W5: Maximum wingspan 65.0m (213.3'), GREEN inset lighting;

W6: Maximum wingspan 24.9m (81.7'), AMBER inset lighting;

W7 & W9: Maximum wingspan 36.0m (118.1'), AMBER inset lighting;

W8: Maximum wingspan 65.0m (213.3'), GREEN inset lighting;

W11 & W13: Maximum wingspan 36.0m (118.1'), AMBER inset lighting;

W12: Maximum wingspan 79.9m (262.1'), GREEN inset lighting;

W15: Maximum wingspan 65.0m (213.3'), GREEN inset lighting;

W17 & W19: Maximum wingspan 36.0m (118.1'), AMBER inset lighting;

W18: Maximum wingspan 79.9m (262.1'), GREEN inset lighting.

DE-ICING GENERAL

Ground Run-up Enclosure (GRE)

Operators must receive an orientation for the GRE facility prior to use.

Crews may contact the “VANCOUVER DE-ICE” or call Aeromag Operations at (604) 278-1901 to schedule de-icing up to 120 minutes prior to departure. Information required: aircraft type, flight number/call sign, and the type(s) of fluids required. Parking position 2A, on Apron I, is the only staging position for the facility. Aircraft waiting to use the GRE must remain on their aprons until 2A becomes available.

“ICEMAN” will advise if engines should be running during de-icing.

Entry Procedure

- 1. Before contacting Ground Control for taxi, contact “ICEMAN” 130.925 for position in de-icing queue.
- 2. When “ICEMAN” approves access to either the staging position (2A) or GRE, contact Ground Control on assigned frequency for taxi.
- 3. Proceed as instructed by “ICEMAN”. CAUTION: DO NOT enter GRE until instructed by “ICEMAN”.
- 4. Advise “ICEMAN” 130.925 when stopped in the GRE.

De-Icing Procedure

- 5. Contact “ICEMAN” 130.925 to confirm brakes set, aircraft configured, engines idle, and provide fluid requirements.
- 6. After de-icing is complete and the aircraft has been inspected, “ICEMAN” will provide posttreatment information.

Exit Procedure

- 7. When ready to taxi contact “ICEMAN” 130.925 for instructions.
- 8. When advised by “ICEMAN”, ctc Ground Control on assigned frequency for taxi instructions.

GRE De-Icing Capacity:

The largest aircraft that can access the GRE via taxilane on Apron II are:

Propellers (power in/out): Maximum wingspan: 28.9m (94.8') (DH8-Q400 and smaller)

Jets (power in/out): Maximum wingspan: 21.6m (70.9') (Dassault Falcon 900 with winglets and smaller)

Jets (tow in, power out)*: Maximum wingspan: 28.9m (94.8') (Global Express)


***Note:** Tow in may be unavailable when snow cannot be fully cleared from the GRE.

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

CENTRAL DE-ICING FACILITY


ATIS – 124.6

DE-ICE – 129.95
GND – 121.7 (S) 127.15 (N)
PAD CTL – 131.97
ICEMAN – 130.7



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

SOUTH DE-ICING FACILITY (GRE)




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

SOUTH DE-ICING FACILITY (GRE)

EFF 16 MAY 24

CYVR

PARKING AREAS




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

PARKING AREAS


EFF 11 JUL 24

START BOXES



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

PARKING AREAS (COMMON USE CARGO)




PARKING AREAS (COMMON USE CARGO)

EFF 31 OCT 24

CYVR

PARKING AREAS (SOUTH TERMINAL)



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


PARKING AREAS (SOUTH TERMINAL)

EFF 12 JUN 25

VANCOUVER/BOUNDARY BAY, BC
CZBB

AERODROME CHART

● ATIS – 125.5		● GND – 124.3		● TWR – 127.6 118.1		DEP Vancouver – 132.3 (S) 363.8	
				● TFC – 118.1		● MF*	
DECL DIST	07	25	13	31			
TORA	6015	6015	5605	5605			
TODA	6015	6999	5605	5933			
ASDA	6015	6015	5605	5605			
LDA	6015	5009	4949	5605			



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 20 FEB 25

CZBB

CZBB-AD

VANCOUVER/HARBOUR (PUBLIC), BC
CBC7

CBC7

123 06.43

123 06.31

49 17.25

49 17.25

VAR 17° E
2014

ANNUAL RATE
OF CHANGE 12' W

ELEV 2

CBC7
N49 17.21
W123 06.37

TAKE-OFF MINIMA

HRP: ★

SCALE IN FEET

100 0 100 200

123 06.43

123 06.31

49 17.17

49 17.17


Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

CBC7

CBC7-HP

AERODROME CHART

AWOS – 122.55		TFC – 122.8					CTR Vancouver – 133.8	
		ATF						
DECL	DISTS	03	21	07	25	16	34	
TORA		4496	4496	5019	5019	3331	3331	
TODA		4496	4496	5019	5019	3331	3331	
ASDA		4496	4496	5019	5019	3331	3331	
LDA		4496	4496	5019	4796	3331	3331	




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 23 FEB 23

CAU4

AERODROME CHART



AERODROME CHART


CYVK

EFF 5 SEP 24

CBF7-HP

VICTORIA HARBOUR (CAMEL POINT), BC
CBF7


HELIPORT CHART



VICTORIA INTL, BC
CYYJ

AERODROME CHART

Ⓢ ATIS – 118.8 Ⓢ LWIS – 118.8		Ⓢ CLNC DEL – 126.4 Ⓢ GND – 121.9 361.4		Ⓢ TWR – 119.7 239.6 Ⓢ RADIO Kamloops – 119.7		DEP – 125.95 MF*	
DECL DIST	03	21	09	27	14	32	
TORA	4141	3622	6998	6998	5001	4574	
TODA	4141	3622	7982	7982	5001	4574	
ASDA	5027	5027	6998	6998	5001	5001	
LDA	3622	4141	6998	6998	4574	5001	



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 7 AUG 25

CYYJ

CYYJ-AD

TAXI CHART

Notes

Widebody Aircraft

Rwy 09 Departures: Twy B, Rwy 03/21, Twy G, Twy E.
Rwy 09 Arrivals: Twy E westbound, Twy S, Twy A.
Rwy 27 Departures: Twy A, Twy S, Twy E eastbound.
Rwy 27 Arrivals: Twy E, Twy G, Rwy 03/21, Twy B.

Taxiways

Taxiway C restricted to 50,000 lbs.
Taxiway M restricted to 12,500 lbs.

Aprons

Apron II restricted to 50,000 lbs.
Apron IV restricted to scheduled commercial traffic only. Acft engine runs abv idle power prohibited, PPR fr OPR for idle power engine runs. Exceptions require prior approval of airport operator.

Rwy 03-21 Operations

Aircraft restricted to max 65,000 lbs for take-off and landing.
No weight restriction for taxiing aircraft rwy 03/21 south of rwy 14/32.

Rwy 27 Arrivals

Aircraft exiting on rwy 14, HOLD SHORT rwy 03, see Hot Spot 3.


Rwy 09 Arrivals

Aircraft exiting on rwy 21, HOLD SHORT rwy 14, see Hot Spot 3.

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

TAXI CHART

● ATIS – 118.8	● CLNC DEL – 126.4	● TWR – 119.7 239.6
● LWIS – 118.8	● GND – 121.9 361.4	● RADIO Kamloops – 119.7
MF*		



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

TAXI CHART

EFF 7 AUG 25

CYYJ

DE-ICING OPERATIONS

DE-ICING PROCEDURES

GENERAL

1. De-icing at gates is not permitted without authorization from airport operator.
2. North de-icing pad access is controlled by DE-ICE CONTROL. ALL Aircraft must have an approved assignment time prior to pushback or taxi.
3. Assignment times will be provided to de-icing providers only and are provided at 20-minute intervals. De-icing provider contact information and times are detailed in the Services section.
4. ATC does not have oversight of de-icing assignments; all inquiries must be directed to de-icing providers or Snow Desk when open (250-953-7595). If the Snow Desk is not open, all inquiries should be directed to de-icing providers or Airport Operations, Manager, Integrated Operations Centre.

SCHEDULED COMMERCIAL AIRCRAFT


1. De-icing assignments will be communicated to commercial aircraft via de-icing providers and individual company processes.
2. **NO de-icing will occur until an assignment has been issued.**

NON-SCHEDULED AIRCRAFT

1. Aircraft requiring an assignment shall contact a de-icing provider, who will request the assignment.
2. De-ice control will issue the assignment between scheduled commercial movements and notify the de-icing provider. The de-icing provider will provide the assignment to the aircraft.
3. If the non-scheduled aircraft misses their assignment, a new assignment must be obtained.
4. **NO de-icing will occur until an assignment has been issued.**

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

PARKING AREAS




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

PARKING AREAS

EFF 5 OCT 23

AERODROME CHART

				RADIO – 122.3		CTR Vancouver – 134.0 381.4	
						MF	
DECL DIST	12	30					
TORA	6966	6966					
TODA	7668	7767					
ASDA	6966	6966					
LDA	6966	6966					




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 12 JUN 25

CYWL

AERODROME CHART




AERODROME CHART

EFF 7 OCT 21

CYWM


AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

				UNICOM – 122.8 (AU)		ATF	
DECL DIST	18	36					
TORA	2995	2995					
TODA	3979	3979					
ASDA	2995	2995					
LDA	2995	2995					



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 11 JUL 24

CZTA

AERODROME CHART

AUTO – 122.97				TFC – 123.2		ATF		TML Cold Lake – 124.5	
DECL DIST	08	26							
TORA	4434	4434							
TODA	4434	4434							
ASDA	4434	4434							
LDA	4434	3921							



★ DEPARTURE PROCEDURE

Rwy 08 - ½

Note: Trees to 1974 ASL abeam departure end of rwy, 400' LEFT and RIGHT of rwy centreline. Road to 1853 ASL at departure end of rwy.

Rwy 26 - ½

Note: Hangars to 1883 ASL abeam departure end of rwy, 500' RIGHT of rwy centreline. Trees to 1858 ASL 0.1 NM past departure end of rwy, 10' LEFT of rwy centreline, and to 1931 ASL 0.3 NM past departure end of rwy, 400' RIGHT of rwy centreline.

TAKE-OFF MINIMA


Rwys 08, 26: ★

SCALE IN FEET

1000 0 1000

AERODROME CHART

AERODROME CHART




AERODROME CHART

EFF 2 OCT 25

CYBR

AERODROME CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

CYBT

EFF 20 FEB 25

AERODROME CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

CYBP

AERODROME CHART

AWOS – 128.6		● RADIO Regina – 118.65 ● TFC – 118.65				RADIO Edmonton – 123.27			
		MF							
DECL DIST	06	24	12	30					
TORA	2297	2297	5006	5006					
TODA	2297	2297	5990	5990					
ASDA	2297	2297	5006	5006					
LDA	2297	2297	5006	5006					




AERODROME CHART

EFF 17 APR 25

CYVT


AERODROME CHART

● ATIS – 127.9 ● AWOS – 127.9		● GND – 121.8		● TWR – 118.2 120.7 ● TFC – 118.2		● MF*		DEP – 124.52 255.1 RADIO Edmonton – 123.37	
DECL DIST	08	26	17	35					
TORA	3423	3423	5000	5000					
TODA	3863	4423	5840	5720					
ASDA	3423	3423	5000	5000					
LDA	3423	3423	5000	5000					



* See DEPARTURE PROCEDURE page

RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 35: RVR 1200 Day only RWY 17: (1/2sm) Day only	NOT AUTHORIZED
TAKE-OFF MINIMA	
All Rwy: *	



AERODROME CHART

CYBW

EFF 7 AUG 25

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

REDUCED VISIBILITY PROCEDURES

Visibility Procedures (RVR less than 2600 to 1200 ft)

Reduced Visibility Taxi Routes

Taxi routes will be coordinated by ATC. All taxiways and runways are available except for Rwy 08/26, taxiway D north of taxiway C, and taxiway C east of taxiway E. Uncontrolled taxiways may be used at the discretion of the pilot. Vehicles responding to an emergency are not required to follow the routes.

Departures

Rwy 17/35 will be used for departures.

Sequencing of Ground Movements for Take-off

Pilots must follow instructions on Sequencing of Ground Movements for Take-off as described in CAP GEN Operating Minima.

Surface Movement Guidance Control System

All taxiway intersections on Rwy 17/35 are equipped with rwy guard lights.

Arrivals

Taxi routes will be coordinated by ATC.

Airport Services and Equipment Available under Reduced Visibility Operations

All taxiway intersections on Rwy 17/35 are equipped with rwy guard lights.

Runway Level of Service


Runway	Certification
17	¼ sm Day only
35	RVR 1200 Day only

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

REDUCED VISIBILITY TAXI CHART
(RVR LESS THAN 2600 TO 1200 FT)

CALGARY/SPRINGBANK, AB
CYBW


● ATIS – 127.9 ● AWOS – 127.9	● GND – 121.8	● TWR – 118.2 120.7 ● TFC – 118.2	● MF*
----------------------------------	---------------	--------------------------------------	-------



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

ATIS – 128.22		CLNC DEL – 120.82 ● APRON – 121.3 (I) GND – 121.9 (W) 125.35 (E) 275.8		TWR – 118.4 (W) 118.7 (E) 236.6		DEP – 124.52 (W) 119.8 (E) 255.1	
DECL DIST	11	29	17R	17L	35L	35R	
TORA	8000	8000	12675	14000	12675	14000	
TODA	8719	8719	13659	14984	13659	14984	
ASDA	8000	8000	12675	14000	12675	14000	
LDA	8000	8000	12675	14000	12675	14000	



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 11, 17R, 17L, 29, 35L, 35R: RVR 1200	RWY 17L, 35R: RVR 600
TAKE-OFF MINIMA	
All Rwys: *	

AERODROME CHART

EFF 2 OCT 25

CYYC

AERODROME CHART (HIGH INTENSITY RUNWAY OPERATIONS – HIRO)

CYYC

LDA for High Intensity Runway Operations				
From threshold rwy:	To exit point	LDA in ft	Preferred exit for med/heavy jet transport	Preferred exit for prop/ turboprop transport
11	A C G F1 F/U	3373 5000 5165 6000 8000	F/U	F1
17L	D1 D3 D5 S Q B	4154 6549 8261 11,979 13,475 13,795	D3 D5	D3
17R	A1 C2 C1 A3 C3 C/A	3976 5840 6415 7489 8516 12,675	C1 A3 C3	C1 A3
29	C A J2 W/J	3200 4853 6606 8000	J2 J	J2
35L	C3 A3 C1 C2 A1 C4 C6 A/C	4154 5181 6255 6830 8684 9369 10,984 12,675	C2 C4	C2
35R	D2 D4 D6 Z V D	4156 6462 8265 10,205 13,475 13,795	D4 D6	D2 D4

Pilots may plan their arrivals using the above table of threshold-to-exit-point distances. The distances are measured from the landing threshold to the point of the intersection of the runway centreline and the extended exit taxiway centreline.

During HIRO operations, the Control Tower may nominate the rwy exit. Compliance with ATC nomination of rwy exit is at the pilot’s discretion and should be acknowledged.

REMARK: For detailed information on High Intensity Runway Operations, pilots may refer to AIP RAC 4.4.10

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

CYYC

AERODROME CHART (REDUCED TAKE OFF RUNS)

Reduced Take-Off Runs

When authorized by ATC, intersection departures are available as follows:

RUNWAY	INTERSECTION	RUNWAY REMAINING
17L	V	13680
	Z	10450
35R	Q	13680
	S	12200

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

TAXI CHART

Notes

Widebody Aircraft

***A380/*B747-8/*AN124 Available Taxiways:** B, BC, D, E, EA, J (east of JV), JS, JQ, JR, S, V, Q, Z, Apron IX and Apron IX De-Ice Pad.

*Twy H and C (north of J) restricted from simultaneous use by aircraft larger than B767/A300.

A340-600/777-300: Discretionary oversteer required at all intersections.

Taxiways

P, GB, GD: Uncontrolled.

W, N & M: Restricted to aircraft with wingspan of 170' or less.

AB, P, GB, JT, L west of A, WB, YD & YE: Restricted to aircraft with wingspan of 118' or less.

C: Right turn on YB restricted to aircraft with wingspan of 118' or less.

F: Left turn on G restricted to aircraft with wingspan of 118' or less.

F: Left turn on F1 restricted to aircraft with wingspan of 79' or less.

F1: Right turn on F restricted to aircraft with wingspan of 79' or less.

G: Right turn on F restricted to aircraft with wingspan of 118' or less.

GB & GD: Restricted to one-way westbound.

J eastbound: Right turn on J2 restricted to aircraft with wingspan of 79' or less.

J2: Left turn on J restricted to aircraft with wingspan of 79' or less.

Y: Right turn on YB restricted to aircraft with wingspan of 118' or less.

YB: Left turn on C restricted to aircraft with wingspan of 118' or less. Left turn on Y restricted to aircraft with wingspan of 118' or less.


Hot Spots

HS 1 – Crossing Rwy 29, aircraft mistake Twy G and Twy C.

HS 2 - Aircraft taxiing for departure Rwy 17L via Twy J, B, D or Twy E, B, D often miss the turn onto Twy B and instead turn onto Twy D, conflicting with aircraft on Twy D3.

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

TAXI CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

TAXI CHART

EFF 2 OCT 25

CYYC

LOW/REDUCED VISIBILITY PROCEDURES

**Low Visibility Procedures (RVR less than 1200 to 600 ft) and
Reduced Visibility Procedures (RVR less than 2600 to 1200 ft)****Low/Reduced Visibility Taxi Routes**

Anticipated taxi routes will be identified, and should portions thereof be unavailable, alternate routes will be identified.

In the event that an aircraft must taxi across the airfield for departure, the RVR values along the taxi route must be used to determine visibility limitations.

Once an aircraft has commenced taxi for takeoff, or taxi after landing, and the visibility falls below the published level of service on the given taxiway, the aircraft may continue to taxi.

Aircraft requiring imminent departure are permitted to tow during RVO but must obtain taxi routing clearances and follow all applicable airside traffic directives guidelines. Tow operations below 1200 RVR are not authorized on manoeuvring areas.

Engine run ups will not be allowed.

Departures

Departures during LVO will be on rwy 17L/35R. During RVO, rwy 17R/35L will be the preferential runway. The departure runway will be identified.

Runways 17L/35R and 17R/35L are equipped with high intensity edge lights and threshold/end lights. Rwy 17L/35R is equipped with centreline lights.

Departure taxi routes will be the most direct route to the threshold. Intersection departures are not permitted. If the primary route is unavailable, Calgary Tower may recommend a secondary route.

Exceptions for departures:

- Taxi to Rwy 11 may be approved from Apron VII and IX when RVR 11 is 1200 or greater
- Taxi to Rwy 11 may be approved from Apron I, East Deice and West Deice when RVR 11 AND 17R are 1200 or greater
- Taxi to Rwy 17R may be approved from Apron I, IX, East Deice and West Deice when RVR 17R is 1200 or greater
- Taxi to Rwy 17R may be approved from Apron VII when RVR 11 AND 17R are 1200 or greater.
- Taxi to Rwy 35L may be approved from Aprons III, IV, V, VI and VIII when RVR 35L is 1200 or greater
- Taxi to Rwy 29 may be approved from Aprons I, IX and West Deice when RVR 17R and RVR 29 are 1200 or greater.

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

LOW/REDUCED VISIBILITY PROCEDURES

CYYC

LOW/REDUCED VISIBILITY PROCEDURES

Sequencing of Ground Movements for Take-off

Pilots must follow instructions on Sequencing of Ground Movements for Take-off as described in CAP GEN Operating Minima.

Surface Movement Ground Control System

All taxi hold positions on taxiways leading to Runway 17L/35R are equipped with stop bars.

Prior to manoeuvring on aprons, aircraft are recommended to contact Apron Advisory Service.

AT NO TIME SHALL A PILOT CROSS AN ILLUMINATED RED STOP BAR

Arrivals

Arrivals during LVO will be on rwy 17L/35R. During RVO, rwy 17L/35R will be the preferential runway. ATC will designate the arrival runway.

Calgary Tower will direct arrival taxi routes in order to ensure the aircraft exits the runway at the first available exit, and will provide instruction from the runway to the Apron.

Airport Services And Equipment Available Under Low Or Reduced Visibility Operations

Airport Surface Movement & Ground Control System (A-SMGCS)

Upon request “follow-me” service can be provided to aircraft. Requests should be made with as much notice as possible.

Runway Level of Service	
Rwy	Certification
11	RVR 1200
29	RVR 1200
17L	RVR 600
35R	RVR 600
17R	RVR 1200
35L	RVR 1200


Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

LOW VISIBILITY TAXI CHART

LAND RWY 17L, DEPART RWY 17L (RVR LESS THAN 1200 TO 600 FT)

CALGARY/YYC CALGARY INTL, AB

CYYC



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

LAND RWY 17L, DEPART RWY 17L (RVR LESS THAN 1200 TO 600 FT)


LOW VISIBILITY TAXI CHART

LOW VISIBILITY TAXI CHART

LAND RWY 35R, DEPART RWY 35R (RVR LESS THAN 1200 TO 600 FT)

CALGARY/YYC CALGARY INTL, AB

CYYC



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

LAND RWY 35R, DEPART RWY 35R (RVR LESS THAN 1200 TO 600 FT)

LOW VISIBILITY TAXI CHART

DE-ICING OPERATIONS

De-icing Procedures

1. Contact CALGARY DE-ICE on 129.5 thirty (30) min prior to push-back with aircraft type and estimated push-back time.
2. Contact CALGARY DE-ICE on 129.5 five (5) min prior to push-back to confirm treatment type and DE-ICE pad assignment.
3. Follow normal pushback procedures and advise Apron Advisory EAST or WEST DE-ICE pad has been assigned.
4. East Pad - Enter from Twy J at Twy JQ. When instructed by GROUND CONTROL, contact PAD CONTROL on 129.12 prior to entering pad.
5. West Pad - Enter from Twy J at Twy JV. When instructed by GROUND CONTROL, contact PAD CONTROL on 122.35 prior to entering pad.
6. Follow PAD CONTROL instructions, signboards and guidance lines to the assigned staging position or de-icing bay and confirm "BRAKES SET" when in position with nosewheel on stop bar.

AUTOMATIC MODE (Active signboard guidance)

As the aircraft enters the de-icing bay, proximity capturing devices will recognize the aircraft. The signboards will actively guide the aircraft to the stop bar position and the signboard will advise SET PARK BRAKE.

MANUAL MODE (Automatic mode not operational)

Follow the instructions from PAD CONTROL and stop on the designated stop bar. Nosewheel should be placed as close to the stop bar marking as possible.

CAUTION: The wingtip to tail clearance for aircraft taxiing in the EAST pad from JQ behind staged aircraft is only assured when the staged aircraft nosewheel is on the stop bar.

7. If assigned a staging bay, monitor PAD CONTROL until further instructed.
8. When directed by PAD CONTROL, contact ICEMAN (East 123.35, West 122.72) and confirm "BRAKES SET, AIRCRAFT CONFIGURED FOR DE-ICE."
9. When de-ice is complete, do not move aircraft. When directed by ICEMAN, contact PAD CONTROL on assigned frequency.
10. Advise PAD CONTROL when ready to taxi. PAD CONTROL will assign appropriate GROUND CONTROL frequency to obtain taxi clearance.
11. Queuing is not permitted on Twy J, staging positions are provided on both EAST and WEST pads, reference DE-ICE Facility diagram.

CAUTION:

During the de-icing process, thrust setting must not exceed ground idle and/or propellers must remain feathered at all times.

Engine run-ups will only be approved by PAD CONTROL or ICEMAN when operations permit and when it is safe to do so. Engine fan blade ice shedding run-ups are prohibited on the de-ice pads.

DE-ICING OPERATIONS

ATIS – 128.22

DE-ICE – 129.5
GND – 121.9 (W) 125.35 (E) 275.8
PAD CTL – 122.35 (W) 129.12 (E)
ICEMAN – 122.72 (W) 123.35 (E)

VAR 15° E
2013
ANNUAL RATE
OF CHANGE 12° W

WEST DE-ICE

De-icing pad aircraft entry

De-icing pad aircraft exit to Taxi Golf.

S1, S2 & S3 are staging for narrow-body aircraft only.
S4 is for staging wide-body or narrow-body as directed by ICEMAN WEST DE-ICE

CALGARY DEICE (Initial contact)	129.5
PAD CONTROL WEST DE-ICE	122.35
ICEMAN WEST DE-ICE	122.725

EAST DE-ICE

De-icing pad aircraft entry.

Apron taxi lane up to Bay 5 will accommodate aircraft with wingspans of 213' (65m) and smaller.

Apron taxi lane Bay 6 to Bay 9 will accommodate aircraft with wingspans of 118' (36m) and smaller.

Aircraft in staging positions must place nosewheel on stopbar to ensure clearance to taxi lane.

MAX SPAN 36M

Aircraft must contact E GND prior to exiting EAST DE-ICE for access onto Twy Bravo.

Delimitation Area Marking


De-icing pad aircraft exit to Twy Bravo.

CALGARY DEICE (Initial contact)	129.5
PAD CONTROL EAST DE-ICE	129.125
ICEMAN EAST DE-ICE	123.35

DE-ICING OPERATIONS

PARKING AREAS

CLNC DEL – 120.82
 ● APRON – 121.3 (I)
 GND – 121.9 (W) 125.35 (E) 275.8



Apron 1 Exit Routing Procedure and Restrictions (see chart below)


Routing	
	Apron I Advisory (121.3 - limited hours) will normally direct departing a/c to a taxi position fix dependent upon active runways.
	Twy JT restricted to aircraft with wingspan of 118' or less.
	Twy GB is restricted to one-way westbound and to aircraft with wingspan of 118' or less.
	Twy GD restricted to one-way westbound

Multilateration: Acft transponders must be kept on at all times when manoeuvring on runways, taxiways and all aprons.

PARKING AREAS

CYYC

AERODROME CHART



AERODROME CHART


CEQ3

CYYQ-AD

CHURCHILL, MB
CYYQ

AERODROME CHART

				RADIO – 126.9		CTR Winnipeg – 134.6 RADIO Edmonton – 123.27	
						MF	
DECL DIST	15	33	07	25			
TORA	9195	9195	4000	4000			
TODA	10179	10179	4700	4984			
ASDA	9195	9195	4000	4000			
LDA	9195	9195	4000	4000			



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART


EFF 7 AUG 25

CYYQ-AD

CYYQ

AERODROME CHART

AUTO – 122.97				UNICOM – 123.3 (AU)		ATF	
DECL DIST	17	35					
TORA	5240	5240					
TODA	5869	5869					
ASDA	5240	5240					
LDA	5240	5240					



AERODROME CHART


EFF 15 JUN 23

CJW7

COLD LAKE REGIONAL, AB
CEN5

AERODROME CHART

ATIS Cold Lake – 118.25					TFC – 122.8		ATF		TML Cold Lake – 124.5	
DECL DIST	08	26								
TORA	3005	3005								
TODA	3005	3005								
ASDA	3005	3005								
LDA	3005	3005								



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 30 NOV 23


CEN5

CEN5-AD

CYOD-AD

COLD LAKE/GROUP CAPTAIN R.W. MCNAIR, AB
CYOD

AERODROME CHART (DND)




AERODROME CHART (DND)

CYOD


EFF 26 DEC 24

CYOD-AD


AERODROME CHART



AUTO – 123.17		UNICOM – 122.8 (AU)				CTR Edmonton – 133.72			
DECL DIST		09	27						
TORA		5251	5251						
TODA		6235	6235						
ASDA		5251	5251						
LDA		5251	5251						



AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART


CFG3

EFF 11 JUL 24

CYCR-AD

CROSS LAKE (CHARLIE SINCLAIR MEMORIAL), MB
CYCR

					UNICOM – 122.8 (AU)		CTR Winnipeg – 135.1	
		ATF						
DECL DIST	05	23						
TORA	3993	3993						
TODA	4977	4977						
ASDA	3993	3993						
LDA	3993	3993						



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART


EFF 2 OCT 25

CYCR

CYCR-AD

AERODROME CHART

AUTO – 122.97				TFC – 123.2		CTR Winnipeg – 135.62	
						ATF	
DECL DIST	10	28					
TORA	2944	2944					
TODA	2944	2944					
ASDA	2944	2944					
LDA	2944	2944					



AERODROME CHART


EFF 11 JUL 24

CJT4

CYDN-AD

DAUPHIN (LT. COL W.G.(BILLY) BARKER, VC), MB
CYDN

AWOS - 128.6		● RADIO Brandon - 122.3				RADIO Edmonton - 123.37	
		● TFC - 122.3				MF	
DECL DIST	08	26	14	32	02	20	
TORA	2703	2703	5002	5002	2110	2110	
TODA	3687	3523	5986	5986	2110	2110	
ASDA	2703	2703	5002	5002	2110	2110	
LDA	2703	2703	5002	5002	2110	2110	



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

CYDN

EFF 2 OCT 25

CYDN-AD

AERODROME CHART



AERODROME CHART

EFF 11 JUL 24

CJJ4

DONNELLY, AB
CFM4

CFM4

W117 06.0 W117 05.3

N55 42.8 N55 42.8

VAR 17° E 2014

ANNUAL RATE OF CHANGE 17° W

CFM4
N55 42.56
W117 05.63

253°

07 25

ELEV 1936 ELEV 1949

3182 x 75

Threshold 25 displaced 202'

073° → Up 0.44% →

*** DEPARTURE PROCEDURE**
Rwy 07 - 1/2
Note: Trees to 1999 ASL aprx 0.2 NM past departure end of rwy, 260' RIGHT of rwy centreline.
Rwy 25 - 1/2
Note: Power poles to 1960 ASL aprx 0.1 NM past departure end of rwy, 250' LEFT and 680' RIGHT of rwy centreline.

N55 42.3 N55 42.3

W117 06.0 W117 05.3

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

Rwy 07 - 1/2

Note: Trees to 1999 ASL aprx 0.2 NM past departure end of rwy, 260' RIGHT of rwy centreline.

Rwy 25 - 1/2

Note: Power poles to 1960 ASL aprx 0.1 NM past departure end of rwy, 250' LEFT and 680' RIGHT of rwy centreline.

Rwys 07, 25: *


CFM4

CFM4-AD

CFV9-HP

DRAYTON VALLEY (HOSP & CARE CENTRE), AB
CFV9

HELIPORT CHART




HELIPORT CHART

EFF 11 JUL 24


CFV9

CFV9-HP

AERODROME CHART




AUTO – 122.17		UNICOM – 122.8		CTR Edmonton – 124.45 132.85	
DECL DIST	17	35			ATF
TORA	3505	3505			
TODA	3505	3505			
ASDA	3505	3505			
LDA	3505	3505			



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

EDMONTON INTL, AB
CYEG

CYEG

113 37 113 36 113 35 113 34 113 33

53 20 53 19 53 18 53 17.2

2363

VAR 15° E 2013
ANNUAL RATE OF CHANGE 14' W

Heli Training Area "B"

ELEV 2337

200°

B1 B2 B3 B4

Taxiways "K", "R", "S", "T", "U", "W" & "V" uncontrolled

CYEG
N53 18.59
W113 34.77

TWR 2486

ELEV 2322

ELEV 2323

120°

10,995

10,200

300°

ELEV 2372

Down 0.48%

*** DEPARTURE PROCEDURE**
Rwy 30 - ½
Note: Trees to 2426 ASL aprx 0.5 NM past departure end of rwy. 1200' LEFT of rwy centreline.

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

RUNWAY LEVEL OF SERVICE	
RVO RWY 02, 12, 30: RVR 1200 RWY 20: (1/4sm)	LVO NOT AUTHORIZED
TAKE-OFF MINIMA	SCALE IN FEET 2000 0 2000 4000 6000
Rwy 02: 12: 20: ½ Rwy 30: ★	

CYEG

CYEG-AD

REDUCED VISIBILITY PROCEDURES

Reduced Visibility Procedures (RVR less than 2600 to 1200 ft)

If any portion of the airport drops below $\frac{1}{2}$ SM or 2600 RVR but is at or above $\frac{1}{4}$ SM or 1200 RVR, the airport is considered to be operating in RVOP with no restrictions to aircraft or vehicles.

If any portion of the airport drops below $\frac{1}{4}$ SM or 1200 RVR, provided the runway of intended use is at or above $\frac{1}{4}$ SM or 1200 RVR, the following procedures shall be implemented:

- Any runway that is below $\frac{1}{4}$ SM or 1200 RVR will not be used for arrivals or departures.
- Restrictions apply to vehicles and aircraft on the manoeuvring area. Only one aircraft, helicopter or vehicle will be given permission to operate on the manoeuvring area at any given time (except as permitted below under Vehicle Exceptions).
- Towing of aircraft on the manoeuvring area is not permitted.

Departures

An aircraft may be taxied for departure if the runway of intended use is at or above $\frac{1}{4}$ SM or 1200 RVR provided no other aircraft or vehicle is on the manoeuvring area.

If the visibility drops below $\frac{1}{4}$ SM or 1200 RVR after taxi clearance was issued, the aircraft may continue to taxi.

An aircraft may depart during RVOP operations provided the RVR serving the departure runway is at or above $\frac{1}{4}$ SM or 1200 RVR.

Arrivals

An aircraft may land and taxi if the runway of intended use is at or above $\frac{1}{4}$ SM or 1200 RVR provided no other aircraft or vehicle is on the manoeuvring area.

Arrivals will be in accordance with applicable approach minima or approach ban considerations. After landing, the aircraft may taxi provided no other aircraft or vehicle is on the manoeuvring area.

If the visibility for the runway of intended use drops below $\frac{1}{4}$ SM or 1200 RVR after an arriving aircraft crosses the final approach fix (FAF), the aircraft may land and taxi in.

Vehicle Exceptions

A group of vehicles may be considered one movement provided they are traveling together and use a single call sign.

Vehicles are permitted to operate on an inactive runway. Once vehicles are established and restricted to remain on the inactive runway, RVOP may resume on the remaining manoeuvring area.

Emergency vehicles responding to emergency situations are exempt.

REDUCED VISIBILITY PROCEDURES

CYEG


DE-ICING OPERATIONS

De-icing Procedures

1. When de-icing is required, ctc EDMONTON DE-ICE on 122.850 30 min prior or as soon as possible with de-icing requirements. AEROMAG will assign the expected de-icing pad or holding area according to de-icing flow.
2. Prior to pushback and for taxi clearance ctc GROUND CONTROL on 121.700 with de-icing pad assignment.
3. On the Main Apron, hold short of the assigned de-icing pad and ctc AEROMAG PAD CONTROL on 122.775.
4. Follow AEROMAG PAD CONTROL instructions and guidance lines to the assigned de-icing bay or staging bay and confirm "BRAKES SET" when in position. Monitor GROUND CONTROL on 121.700 at all times.
5. When directed by AEROMAG PAD CONTROL, ctc ICEMAN on 130.125 (136.535 backup frequency) and confirm "BRAKES SET, AIRCRAFT CONFIGURED and ENGINES IDLE FOR DE-ICE."
6. When de-ice is complete, do not move aircraft. When directed by ICEMAN, ctc AEROMAG PAD CONTROL on 122.775 to obtain taxi instructions.
7. Follow AEROMAG PAD CONTROL instructions to exit de-icing. Hold short of Twy ALPHA and ctc GROUND on 121.700 to obtain clearance. Holding short of Twy ALPHA is only relevant to DF1 and DF2. DF3 aircraft exit onto Apron I.

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

PARKING AREAS (APRON 1)



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

PARKING AREAS (APRON 1)


EFF 10 SEP 20

CYEP-AD

EDMONTON/EDMONTON PARKLAND EXECUTIVE AIRPORT, AB


CYEP

				TFC - 122.7		TML Edmonton - 119.5	
				MF			
DECL DIST	08	26					
TORA	4330	4930					
TODA	4330	4930					
ASDA	5217	5217					
LDA	4732	4181					



AERODROME CHART

AWOS – 122.35				TFC – 123.5		TML – 119.5	
						ATF	
DECL DISTS	08	26					
TORA	4560	4560					
TODA	4796	4826					
ASDA	4560	4560					
LDA	4166	4313					




AERODROME CHART

EFF 16 MAY 24

CFB6

HELIPORT CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

EDMONTON/VILLENEUVE, AB
CZVL

● ATIS - 128.35 ● AWOS - 128.35	● GND - 120.8	● TWR - 118.8	TML - 119.5
		● TFC - 118.8	● ATF*

DECL DIST	08	26	16	34				
TORA	5001	5001	3496	3496				
TODA	5001	5001	3696	3696				
ASDA	5001	5001	3496	3496				
LDA	5001	5001	3496	3496				

*** DEPARTURE PROCEDURE**

Rwy 08 - ½ - Climb between hdg **043°** CCW to **289°** or between hdg **107°** CW to **207°** to remain clear of CYA202, CYA209 or CYA218 when active.
Note: Trees to 2238 ASL aprx 500' past departure end of rwy, 450' LEFT of rwy centreline.

Rwy 16 - ½ - Cimb between hdg **208°** CCW to **099°** to remain clear of CYA202, CYA209 or CYA218 when active.
Note: Trees to 2293 ASL aprx 0.2 NM past departure end of rwy, 400' RIGHT of rwy centreline.

Rwy 26 - ½ - Climb between hdg **188°** CCW to **099°** or between hdg **294°** CW to **045°** to remain clear of CYA202, CYA209 or CYA218 when active.
Note: Trees to 2274 ASL abeam departure end of rwy, 500' LEFT of rwy centreline.

Rwy 34 - ½ - Cimb between hdg **291°** CW to **045°** to remain clear of CYA202, CYA209 or CYA218 when active.
Note: Trees to 2274 ASL aprx 200' past departure end of rwy, 500' LEFT of rwy centreline.

TAKE-OFF MINIMA

All Rwys: *

SCALE IN FEET
 1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART


EFF 3 NOV 22

CZVL


CZVL-AD

AERODROME CHART

AWOS – 128.75				TFC – 123.2		RADIO Edmonton – 126.7	
DECL DIST	07	25			ATF		
TORA	5997	5997					
TODA	6197	6197					
ASDA	5997	5997					
LDA	5403	5513					



AERODROME CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 15 JUN 23

CEJ6

AERODROME CHART




AERODROME CHART

EFF 2 DEC 21

CYEN

AERODROME CHART

AUTO – 122.97		UNICOM – 122.8				CTR Edmonton – 135.27		
						ATF		
DECL DIST	04	22						
TORA	3506	3506						
TODA	3506	3506						
ASDA	3506	3506						
LDA	3506	3506						




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

CEB5

EFF 5 OCT 23

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 24 MAR 22

CYFO

AERODROME CHART

AUTO – 122.17				TFC – 123.2		ATF	
DECL DIST	10	28					
TORA	3805	3805					
TODA	4789	4297					
ASDA	3805	3805					
LDA	3805	3805					



AERODROME CHART

CZFD

FORT CHIPEWYAN, AB
CYPY

AWOS – 128.0		TFC – 123.2		RADIO Edmonton – 123.47	
DECL DISTS	04	22			
TORA	5000	5000			
TODA	5000	5000			
ASDA	5000	5000			
LDA	5000	5000			

VAR 15° E 2013
ANNUAL RATE OF CHANGE 19° W

58 46.2
58 45.9

111 07.5
111 07
111 06.5

5000 x 150

CYPY
N58 46.03
W111 07.03

037°
ELEV 704

Up 1.24%

217°
ELEV 757

Up 0.63 % first 472'

***DEPARTURE PROCEDURE**
Rwy 04 - ½
Note: Trees to 781 ASL aprx 0.2 NM past departure end of rwy, 150' RIGHT of rwy centreline.

Rwy 22 - ½ - NO LEFT turn below 1400.
Note: Trees to 820 ASL aprx 0.2 NM past departure end of rwy, 400' LEFT of rwy centreline.

TAKE-OFF MINIMA

Rwy 04: 22: *

SCALE IN FEET


1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

CYPY

AERODROME CHART

AUTO – 122.97		CLNC DEL Edmonton – 134.02				CTR Edmonton – 134.02			
		UNICOM – 123.3 (AU) TFC – 123.5				ATF*			
DECL DIST	13	31							
TORA	7549	7549							
TODA	8533	8533							
ASDA	7549	7549							
LDA	7549	7549							




AERODROME CHART

EFF 29 DEC 22

CAL4

AERODROME CHART

AUTO – 129.65		CLNC DEL Edmonton – 134.02				CTR Edmonton – 134.02			
		UNICOM – 122.8 (AU) TFC – 123.5				ATF*			
DECL DIST	17	35							
TORA	6890	6890							
TODA	7874	7874							
ASDA	6890	6890							
LDA	6890	6890							




AERODROME CHART

EFF 17 JUN 21

CYFI

AERODROME CHART




AERODROME CHART

EFF 11 JUL 24

CYNR

AERODROME CHART



DE-ICING OPERATIONS


De-Ice Bay Procedure

Fort McMurray International operates a central de-icing facility which is located on the main/south ramp (Apron I) on the south side of the airport. All bays are capable of both engine on and engine off de-icing operations concurrently. All de-icing is to be accomplished at this facility.

- 1. De-icing is accomplished by each of the ground handling companies that operate at the Fort McMurray International Airport.
- 2. Coordinate any special treatment with your Ground Handler prior to taxi to the CDF.
- 3. Entry point to the CDF, if transitioning from the North, is via taxi-way J to Apron I – use west entrance.
- 4. If required to hold – the designated holding area is to your immediate right upon entering Apron I.
- 5. CDF flow is from west to east.
- 6. Contact YMM Ground on 121.9 (or Yellowknife Radio on 118.1 during the hours of 2245-0615 local) for runway and taxi instructions.
- 7. Exit is via taxi-way H.


Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

DE-ICING OPERATIONS




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AUTO – 120.22				TFC – 123.2		CTR Edmonton – 135.1	
DECL DIST		08	26			ATF	
TORA		4000	4000				
TODA		4000	4000				
ASDA		4000	4000				
LDA		4000	4000				



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 24 MAR 22

CYGX

AERODROME CHART

AUTO- 122.97				UNICOM - 122.15		CTR Winnipeg - 118.0	
DECL DIST	15	33					
TORA	6800	6800					
TODA	7784	7784					
ASDA	7007	7281					
LDA	6800	6800					



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 12 JUN 25

CYGM

AERODROME CHART

				UNICOM – 122.8 (AU)		ATF	
DECL DIST	14	32					
TORA	3810	3810					
TODA	3810	4210					
ASDA	3810	3810					
LDA	3810	3810					




AERODROME CHART

EFF 21 MAY 20

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 20 FEB 25

CZGI

AERODROME CHART

ATIS – 128.6		CLNC DEL – 121.9		RADIO – 118.1		CTR Edmonton – 134.5 RADIO Edmonton – 123.47	
						MF	
DECL DIST	07	25	12	30			
TORA	6200	6200	8502	8502			
TODA	7184	7184	9368	9402			
ASDA	6200	6200	8502	8502			
LDA	6200	6200	8102	8502			



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

RVO		LVO	
RWY 30: (1/4 sm)		NOT AUTHORIZED	
TAKE-OFF MINIMA			
Rwys 07: 12: 25: 1/2			
Rwy 30: *			


AERODROME CHART

CYQU

EFF 29 DEC 22

AERODROME CHART

AUTO – 129.17		UNICOM – 122.8				ATF			
DECL DIST	13	31							
TORA	3119	3119							
TODA	3119	3119							
ASDA	3119	3119							
LDA	3119	3119							




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 16 MAY 24


CJV8

AERODROME CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART




AERODROME CHART

AERODROME CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART




AERODROME CHART



AERODROME CHART


CZHP

						CTR Edmonton – 132.75		
		Foothills TFC – 123.0				MF		
DECL DIST	07	25	15	33				
TORA	4160	4160	2726	2726				
TODA	4160	4160	2726	2726				
ASDA	4160	4160	2726	2726				
LDA	3473	3685	2726	2726				




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AUTO – 122.55		UNICOM – 123.35 (AU)				RADIO Edmonton – 123.55			
		ATF							
DECL DIST	02	20							
TORA	4510	4510							
TODA	4510	4510							
ASDA	4510	4510							
LDA	4305	4203							



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART




AERODROME CHART

EFF 7 AUG 25

CYHB

AERODROME CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 16 MAY 24

AERODROME CHART

AUTO – 122.07				TFC – 123.2		ATF	
DECL DIST	15	33					
TORA	3908	3908					
TODA	3908	3908					
ASDA	3908	3908					
LDA	3908	3908					



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 11 JUL 24

CJF3

ILFORD, MB
CZBD

CZBD

95 37.5 95 36.7

VAR 1° E 2013
ANNUAL RATE OF CHANGE 8' W

56 03.2 56 03.2

60 089° → 2989 x 75 ← 269° 27

ELEV 635 crushed rock ELEV 642

CZBD
N56 03.10
W95 37.08

★

DEPARTURE PROCEDURE

★ **Rwy 09** - ½ - Climb between hdg **062°** CW to **018°** to remain clear of blasting area aprx 22NM NE to **5500**.
Note: Trees to 699 ASL within 0.2NM of departure end of rwy.

Rwy 27 - ½ - Climb between hdg **018°** CCW to **062°** to remain clear of blasting area aprx 22NM NE to **5500**.
Note: Trees to 676 ASL within 0.3NM of departure end of rwy.

56 02.9 56 02.9

95 37.5 95 36.7

TAKE-OFF MINIMA

Rwys 09, 27: ★

SCALE IN FEET


500 0 500

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

CZBD

CZBD-AD

AERODROME CHART



VAR 0°

2014

↑

ANNUAL RATE OF CHANGE 7° W

APRON II

A

53 51.6

ELEV 769

122°

30

4000 x 100

B

APRON I

C

crushed rock

CYIV

N53 51.43

W94 39.22

869

302°

ELEV 768

30

* DEPARTURE PROCEDURE

Rwy 12 - ½ - Requires a minimum climb gradient of 260 ft/NM to 1100.

Note: Trees to 797 ASL within 0.2 NM past departure end of rwy, 200' RIGHT of rwy centerline.

or

SPEC VIS - Climb in visual conditions to cross the aprt at or above 1300 BPOC.

Rwy 30 - ½

Note: Trees to 846 ASL within 0.6 NM past departure end of rwy, 200' RIGHT of rwy centerline.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
260 FT/NM	390	520	610	700	780	870	1090	1300

TAKE-OFF MINIMA

Rwys 12; 30: *

SCALE IN FEET

1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 2 OCT 25

CYIV


AERODROME CHART



AERODROME CHART

AERODROME CHART

AUTO – 122.55		UNICOM – 122.8				CTR Winnipeg – 133.15		
						ATF		
DECL DIST	12	30						
TORA	3800	3800						
TODA	3800	3800						
ASDA	3955	3956						
LDA	3800	3800						




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 14 JUL 22

CZEE

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 23 FEB 23


CYKJ

CEK6-AD

KILLAM-SEDGEWICK/FLAGSTAFF REGIONAL, AB

CEK6

AERODROME CHART




AERODROME CHART

CEK6

EFF 16 JUL 20

CEK6-AD


AERODROME CHART



KIPLING, SK
CKD5

AERODROME CHART

				TFC – 123.2		ATF	
DECL DIST	10	28					
TORA	3001	3001					
TODA	3001	3001					
ASDA	3001	3001					
LDA	3001	3001					



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 7 AUG 25

CKD5

CKD5-AD

AERODROME CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

LA RONGE (BARBER FIELD), SK
CYVC

CYVC

					RADIO – 122.2		CTR Winnipeg – 126.4 RADIO Edmonton – 123.55	
DECL DIST	18	36	11	29		MF		
TORA	5002	5002	2396	2396				
TODA	5986	5986	2986	2986				
ASDA	5002	5002	2396	2396				
LDA	5002	5002	2396	2396				




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

CZWH-AD

LAC BROCHET, MB
CZWH

AERODROME CHART



AERODROME CHART

CZWH


EFF 20 FEB 25

CZWH-AD

LAC DU BONNET, MB
CYAX

AERODROME CHART

				TFC – 122.8		ATF	
DECL DIST	18	36					
TORA	3609	3609					
TODA	3609	3609					
ASDA	3609	3609					
LDA	3609	3609					



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART


EFF 16 MAY 24

CYAX

CYAX-AD

AERODROME CHART

AUTO – 122.12				TFC – 123.2		RADIO Edmonton – 123.47	
						ATF	
DECL DIST	11	29					
TORA	5704	5704					
TODA	5704	5704					
ASDA	5704	5704					
LDA	5704	5704					




AERODROME CHART

EFF 17 APR 25

CYLB

AERODROME CHART

ATIS Red Deer – 124.0		UNICOM – 123.3				CTR Edmonton – 132.85		
						ATF		
DECL DIST	17	35						
TORA	3004	3004						
TODA	3004	3004						
ASDA	3004	3004						
LDA	3004	3004						




AERODROME CHART

CEG3

AERODROME CHART

● ATIS – 124.4 ● AWOS – 124.4				● RADIO – 121.0 ● TFC – 121.0		CTR Edmonton – 132.75 265.2 RADIO Edmonton – 123.47	
DECL	DISTS	06	24	13	31		
TORA		6500	6500	5500	5500		
TODA		7484	7484	6484	6484		
ASDA		6500	6500	5500	5500		
LDA		6500	6500	5500	5500		



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART


EFF 15 JUN 23

CYQL

LITTLE GRAND RAPIDS, MB
CZGR

AERODROME CHART

				UNICOM – 122.8 (AU)			
DECL DIST	18	36			ATF		
TORA	2798	2798					
TODA	2798	2823					
ASDA	2798	2798					
LDA	2798	2798					



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART


EFF 17 JUN 21

CZGR

CZGR-AD

AERODROME CHART

● AWOS – 128.55				● RADIO Lloyd – 122.2		CTR Edmonton – 133.45 340.7 RADIO Edmonton – 123.55	
				● TFC – 122.2		MF	
DECL DIST	08	26	13	31			
TORA	5577	5577	1202	1202			
TODA	5577	5577	1202	1202			
ASDA	5577	5577	1202	1202			
LDA	5577	5577	1202	1202			




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 10 AUG 23

CYLL

AERODROME CHART



AERODROME CHART

EFF 24 MAR 22


CJR2

CYYL-AD

LYNN LAKE, MB
CYYL

AERODROME CHART

AWOS – 128.0				UNICOM – 122.3 TFC – 122.3		CTR Winnipeg – 135.05 RADIO Edmonton – 123.47	
DECL DIST	17	35					
TORA	5004	5004					
TODA	5988	5988					
ASDA	5004	5004					
LDA	5004	5004					



AERODROME CHART

EFF 12 JUN 25

CYYL-AD


CYYL

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

MAIDSTONE, SK
CJH3

AERODROME CHART

● AUTO Lloydminster – 128.55				TFC – 123.2		RADIO Edmonton – 123.37	
DECL	DISTS	12	30			ATF	
TORA	3610	3610					
TODA	3610	3807					
ASDA	3610	3610					
LDA	3610	3610					




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

CJH3

CJH3-AD

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 5 OCT 23

CFX4

AERODROME CHART

		UNICOM – 122.8				RADIO Edmonton – 123.37		
						ATF		
DECL DIST	06	24	17	35				
TORA	3078	3078	1936	1936				
TODA	3078	3078	1936	1936				
ASDA	3078	3078	1936	1936				
LDA	3078	3078	1936	1936				



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART


EFF 20 FEB 25

CJQ4

CKQ8-AD

MCARTHUR RIVER, SK
CKQ8

AUTO – 122.27				UNICOM – 123.3 (AU)		ATF	
DECL DIST	18	36					
TORA	5278	5278					
TODA	5653	5558					
ASDA	5278	5278					
LDA	5278	5278					




AERODROME CHART

CKQ8

EFF 23 FEB 23

CKQ8-AD

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 17 JUN 21

CYLJ

AERODROME CHART

● ATIS – 124.87 ● AWOS – 124.87				● RADIO – 122.2 ● TFC – 122.2		● RADIO – 122.2 ● RADIO Edmonton – 123.37	
						MF	
DECL	DISTS	03	21	09	27		
TORA		5003	5003	2850	2850		
TODA		5987	5987	3834	3834		
ASDA		5003	5003	2850	2850		
LDA		5003	5003	2850	2850		




AERODROME CHART

EFF 8 SEP 22

CYXH

AERODROME CHART



AERODROME CHART

EFF 16 MAY 24

CJZ3


CYMJ-AD

MOOSE JAW/AIR VICE MARSHAL C.M. MCEWEN, SK

CYMJ

AERODROME CHART (DND)

● ATIS – 131.3 257.8		● CLNC DEL – 135.3 234.4		● TWR – 126.2 295.6		● DEP – 119.0 227.6	
		● GND – 121.8 275.8					
DECL DIST	11L	29R	11R	29L	03	21	
TORA	8320	8320	7280	7280	3460	3460	
TODA	8320	8320	7280	7280	3460	3460	
ASDA	8520	8520	7480	7480	3720	3680	
LDA	8320	8320	7280	7280	3460	3460	



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART (DND)

CYMJ

EFF 8 SEP 22

CYMJ-AD

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 31 OCT 24

CJB5-AD

MOOSOMIN/MARSHALL MCLEOD FIELD, SK
CJB5

		UNICOM – 122.8				CTR Winnipeg – 132.25			
		ATF							
DECL DIST	13	31							
TORA	5000	5000							
TODA	5000	5000							
ASDA	5000	5000							
LDA	5000	5000							




AERODROME CHART
EFF 31 OCT 24

CJB5

CJB5-AD

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 30 JAN 20

CJV5

AERODROME CHART

AWOS – 128.75						UNICOM – 122.8		CTR Winnipeg – 133.9		
								ATF		
DECL DIST	03	21	12	30						
TORA	2933	2933	2900	2900						
TODA	2933	2933	2900	2900						
ASDA	2933	2933	2900	2900						
LDA	2933	2933	2900	2900						



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 23 FEB 23

CYBU

AERODROME CHART

AWOS – 128.12				TFC – 122.1		RADIO Edmonton – 123.37	
						MF	
DECL DIST	12	30					
TORA	5000	5000					
TODA	5984	5984					
ASDA	5000	5000					
LDA	5000	5000					




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 25 JAN 24

AERODROME CHART

AWOS – 127.7				● RADIO Kenora – 122.1		DEP Winnipeg – 135.1	
				● TFC – 122.1		RADIO Edmonton – 123.37	
						MF	
DECL DIST	06	24					
TORA	3903	3903					
TODA	4887	4887					
ASDA	3903	3903					
LDA	3903	3903					




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 17 APR 25

CYNE

AERODROME CHART



AERODROME CHART

OXFORD HOUSE, MB
CYOH

CYOH

95 17.1 95 16.5

VAR 1° E
2015
ANNUAL RATE
OF CHANGE 3' W

54 56.2 54 56.2

23 ELEV 663
(P₁)

228°

Down 0.97%

crushed rock

3829 x 82

CYOH
N54 55.98
W95 16.73

049°

05 ELEV 645

54 55.7 54 55.7

95 17.1 95 16.5

*** DEPARTURE PROCEDURE**

Rwy 05 -½
Note: Trees to 714 ASL aprx 0.1NM past departure end of rwy.

Rwy 23 -½
Note: Trees to 721 ASL aprx 0.1NM past departure end of rwy.
Procedure not auth when blasting area 4.1 NM SW of apt active.

TAKE-OFF MINIMA

Rwys 05; 23: *

SCALE IN FEET

1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

CYOH

CYOH-AD

AERODROME CHART

AUTO – 121.87		UNICOM – 122.8				CTR Edmonton – 124.45			
						ATF			
DECL DIST	14	32							
TORA	3018	3018							
TODA	3018	3018							
ASDA	3018	3018							
LDA	3018	3018							



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 12 JUN 25

CED3

AERODROME CHART

AWOS – 128.1		CLNC DEL – 135.27		TFC – 122.0		CTR Edmonton – 135.27 RADIO Edmonton – 123.27	
DECL DISTS		04	22			MF	
TORA		5000	5000				
TODA		5984	5984				
ASDA		5000	5000				
LDA		5000	5000				




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 17 APR 25

CYPE

AERODROME CHART




AERODROME CHART

EFF 10 SEP 20

CZMN

AERODROME CHART

AWOS – 127.65				CTR Edmonton – 132.75 265.2	
		TFC – 123.2		ATF	
DECL DIST	08	26			
TORA	6597	6597			
TODA	6597	6597			
ASDA	6597	6597			
LDA	6000	6448			



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 25 JAN 24

CZPC

AERODROME CHART

AWOS – 122.55				68 Points North UNICOM – 123.3 (AU)		ATF	
DECL DIST	16	34					
TORA	5848	5848					
TODA	6832	6832					
ASDA	6048	6048					
LDA	5848	5848					




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 26 DEC 24

AERODROME CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 14 JUL 22

CEH3

AERODROME CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 17 APR 25

CZNG

AERODROME CHART




AERODROME CHART

EFF 2 OCT 25

CYPG

AERODROME CHART




AERODROME CHART

EFF 2 OCT 25

CYPA


AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

		UNICOM – 122.8 (AU)				CTR Winnipeg – 135.05			
						ATF			
DECL DIST	15	33							
TORA	2998	2998							
TODA	3982	3982							
ASDA	2998	2998							
LDA	2998	2998							



AERODROME CHART

CZFG


EFF 30 JAN 20

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

RAINBOW LAKE, AB
CYOP

AERODROME CHART

				 UNICOM – 122.8 (AU)			
DECL DIST	09	27				ATF	
TORA	5002	5002					
TODA	5002	5002					
ASDA	5002	5002					
LDA	5002	5002					



AERODROME CHART


EFF 20 FEB 25

CYOP

CYOP-AD

AERODROME CHART

● ATIS – 124.0 ● AWOS – 124.0		● GND – 121.9		● TWR – 118.5 ● TFC – 118.5		CTR Edmonton – 132.85 RADIO Edmonton – 123.47	
DECL	DISTS	12	30	17	35		
TORA		3454	3254	7500	7500		
TODA		3454	3254	8484	8484		
ASDA		3454	3454	7500	7500		
LDA		3254	3454	7500	7500		



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 17 APR 25

CYQF

AERODROME CHART

		TFC – 123.2				CTR Edmonton – 135.27		
						ATF		
DECL DIST	13	31						
TORA	3542	3542						
TODA	3542	3542						
ASDA	3542	3542						
LDA	3542	3542						



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

CEH5

EFF 12 AUG 21

AERODROME CHART

AUTO – 122.07				UNICOM – 122.8 (AU)		ATF	
DECL DIST	09	27					
TORA	3552	3552					
TODA	5328	5328					
ASDA	3552	3552					
LDA	3552	3552					




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 12 JUN 25

CYRS

AERODROME CHART



VAR 10° E
2011

ANNUAL RATE
OF CHANGE 10° W

HOT SPOTS:
HS1: Departing aircraft mistake Rwy 26 and
Rwy 31 and depart incorrect runway. Taxiing
on Twy K aircraft fail to hold short and incur on
Rwy 26 and Rwy 31.

RVO for Rwy 13/31
During ATC hours of ops, when vis is
below ¼ SM and RVR is 1200 or above,
one in/one out ops will be provided.

RESTRICTIONS
Apron I rstd to sked commercial t/c only. Exceptions require
prior appr of aprt opr.
Apron II posn 1 rstd to commercial t/c only. Exceptions require
prior appr of aprt opr.
Apron III single row prkg only.
Apron IV rstd to acft under 5,000 lbs.
Btwn Apron V and Apron III rstd to acft less than 24m (78')
Hi power run-up other than engine-clearing after de-icing PPR etc OPR.

* DEPARTURE PROCEDURE
Rwy 13 - ½
Note: Trees to 1967 ASL aprx 0.4 NM
past departure end of rwy, 500' LEFT
of rwy centreline.

104 40.5

104 39.5

50 26.5

50 26

50 25.5

104 40.5

104 39.5

1238°

260°

308°

1895

1894

1895

2005

2033

1976

6200 x 150

7901 x 150

AO

P2

P2

P2

AN

104 40.5

104 39.5

50 26.5

50 26

50 25.5

104 40.5

104 39.5

1238°

260°

308°

1895

1894

1895

2005

2033

1976

6200 x 150

7901 x 150

AO

P2

P2

P2

AN

RUNWAY LEVEL OF SERVICE

RVO

LVO

RWY 13: RVR 1200
RWY 31: (½sm)

NOT AUTHORIZED

TAKE-OFF MINIMA

RWys 08, 26, 31: ½
Rwy 13: *

SCALE IN FEET

1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

CYQR

EFF 11 JUL 24

CYQR-AD

PARKING AREAS




PARKING AREAS

EFF 24 MAR 22

AERODROME CHART

AUTO – 131.97				TFC – 122.8		CTR Edmonton – 134.3	
						MF	
DECL DIST	13	31					
TORA	5513	5513					
TODA	6303	6213					
ASDA	5513	5513					
LDA	5513	5513					




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

CYRM

AERODROME CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 24 MAR 22

CJX4

AERODROME CHART



AERODROME CHART


EFF 11 JUL 24

CJW5

CYXE-AD

SASKATOON/JOHN G. DIEFENBAKER INTL, SK
CYXE

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 5 SEP 24

CYXE

CYXE-AD

REDUCED VISIBILITY PROCEDURES

CYXE

Reduced Visibility Procedures (RVR less than 2600 to 1200 ft)

If any portion of the airport drops below $\frac{1}{2}$ SM or 2600 RVR but is at or above $\frac{1}{4}$ SM or 1200 RVR, the airport is considered to be operating in RVOP with no restrictions to aircraft or vehicles.

If any portion of the airport drops below $\frac{1}{4}$ SM or 1200 RVR, provided the runway of intended use is at or above $\frac{1}{4}$ SM or 1200 RVR, the following procedures shall be implemented:

- Any runway that is below $\frac{1}{4}$ SM or 1200 RVR will not be used for arrivals or departures.
- Restrictions apply to vehicles and aircraft on the manoeuvring area. Only one aircraft, helicopter or vehicle will be given permission to operate on the manoeuvring area at any given time (except as permitted below under Vehicle Exceptions).
- Towing of aircraft on the manoeuvring area is not permitted.

Departures

An aircraft may be taxied for departure if the runway of intended use is at or above $\frac{1}{4}$ SM or 1200 RVR provided no other aircraft or vehicle is on the manoeuvring area.

If the visibility drops below $\frac{1}{4}$ SM or 1200 RVR after taxi clearance was issued, the aircraft may continue to taxi.

An aircraft may depart during RVOP operations provided the RVR serving the departure runway is at or above $\frac{1}{4}$ SM or 1200 RVR.

Arrivals

An aircraft may land and taxi if the runway of intended use is at or above $\frac{1}{4}$ SM or 1200 RVR provided no other aircraft or vehicle is on the manoeuvring area.

Arrivals will be in accordance with applicable approach minima or approach ban considerations. After landing, the aircraft may taxi provided no other aircraft or vehicle is on the manoeuvring area.

If the visibility for the runway of intended use drops below $\frac{1}{4}$ SM or 1200 RVR after an arriving aircraft crosses the final approach fix (FAF), the aircraft may land and taxi in.

Vehicle Exceptions

A group of vehicles may be considered one movement provided they are traveling together and use a single call sign.


Vehicles are permitted to operate on an inactive runway. Once vehicles are established and restricted to remain on the inactive runway, RVOP may resume on the remaining manoeuvring area.

Emergency vehicles responding to emergency situations are exempt.

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

				UNICOM – 122.8 (AU)		ATF			
DECL DIST	01	19							
TORA	4006	4006							
TODA	4990	4990							
ASDA	4006	4006							
LDA	4006	4006							



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART


EFF 20 FEB 25

CZTM

SHAUNAVON, SK
CJC5

AERODROME CHART

LWIS – 122.55					UNICOM – 122.8		CTR Winnipeg – 132.8	
DECL DIST	12	30	02	20		ATF		
TORA	2969	2969	1844	1844				
TODA	2969	2969	1844	1844				
ASDA	2969	2969	1844	1844				
LDA	2969	2969	1844	1844				



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 14 JUL 22


CJC5

CJC5-AD

AERODROME CHART



AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 17 APR 25

CZSN

AERODROME CHART




AERODROME CHART

EFF 25 JAN 24

CFS5

AERODROME CHART


					UNICOM – 122.8		TML Cold Lake – 124.5	
		ATF						
DECL DIST	08	26						
TORA	3498	3498						
TODA	3498	3498						
ASDA	3498	3498						
LDA	3498	3498						



AERODROME CHART

AERODROME CHART

AWOS Island Lake – 128.1				RADIO Thunder Bay – 122.2			
						MF	
DECL DIST	04	22					
TORA	3393	3393					
TODA	4377	4377					
ASDA	3393	3393					
LDA	3393	3393					




AERODROME CHART

EFF 20 FEB 25

CYST

AERODROME CHART

		UNICOM – 122.7				TML Winnipeg – 119.9		
						ATF		
DECL DIST	07	25	18	36				
TORA	1834	1834	3112	3112				
TODA	1834	1834	3112	3112				
ASDA	1834	1834	3112	3112				
LDA	1834	1834	3112	3112				



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART


EFF 23 FEB 23

CKK7

CEJ3-AD

STETTLE, AB
CEJ3

AERODROME CHART



AERODROME CHART


EFF 5 OCT 23

CEJ3

CEJ3-AD

AERODROME CHART

AWOS – 128.75				● RADIO Regina – 122.1		RADIO Edmonton – 122.37	
				● TFC – 122.1		MF	
DECL DIST	06	24					
TORA	5052	5052					
TODA	6036	5551					
ASDA	5052	5052					
LDA	5052	5052					




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

CYSF

AERODROME CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 15 JUN 23

AERODROME CHART

					CTR Winnipeg – 132.52			
TFC – 122.8					ATF			
DECL DIST	02	20	08	26				
TORA	3935	3935	1957	1957				
TODA	3935	3935	1957	1957				
ASDA	3935	3935	1957	1957				
LDA	3935	3935	1957	1957				




AERODROME CHART

EFF 12 JUN 25

CYYN-AD

SWIFT CURRENT, SK
CYYN

AERODROME CHART



AERODROME CHART


EFF 17 APR 25

CYYN-AD

CYYN

AERODROME CHART

		UNICOM – 122.8				CTR Edmonton – 132.75 265.2		
						ATF		
DECL DIST	05	23	13	31				
TORA	3005	3005	1930	1930				
TODA	3005	3005	1930	1930				
ASDA	3005	3005	1930	1930				
LDA	3005	3005	1930	1930				



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 7 AUG 25

CED5

AERODROME CHART

AWOS – 128.62					UNICOM – 122.8 (AU)		RADIO Edmonton – 126.7 DRCO	
		ATF						
DECL DIST	07	25						
TORA	3202	3202						
TODA	4186	3227						
ASDA	3202	3202						
LDA	3202	3202						



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 12 JUN 25

CYBQ

AERODROME CHART

MET – 124.7		RADIO Saskatoon – 122.2		RADIO Edmonton – 123.55	
		TFC – 122.2		MF	
DECL DISTS	13	31			
TORA	5901	5901			
TODA	6885	6669			
ASDA	5901	5901			
LDA	5901	5901			




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

CYQD

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART


EFF 20 FEB 25

CJR3

CZLQ-AD

THICKET PORTAGE, MB
CZLQ

				UNICOM – 122.8 (AU)		ATF	
DECL DIST	12	30					
TORA	2211	2211					
TODA	3195	3195					
ASDA	2211	2211					
LDA	2211	2211					



AERODROME CHART
EFF 16 JUL 20

CZLQ


CZLQ-AD

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

THOMPSON, MB
CYTH

AERODROME CHART

ATIS – 127.65					RADIO – 122.5		CTR Winnipeg – 133.15 RADIO Edmonton – 123.55	
					MF*			
DECL DISTS	06	24	15	33				
TORA	5800	5800	5079	5079				
TODA	6784	6784	5279	5279				
ASDA	5800	5800	5079	5079				
LDA	5800	5800	5079	5079				



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 26 DEC 24

CYTH

CYTH-AD


AERODROME CHART



AERODROME CHART

CEN3

AERODROME CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 23 FEB 23

AERODROME CHART



AERODROME CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 15 JUN 23

CEL5

AERODROME CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 20 APR 23

CEV3

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 17 APR 25

CYVG


CYVD-AD

VIRDEN/R.J. (BOB) ANDREW FIELD REGIONAL, MB

CYVD

AERODROME CHART

AUTO – 122.17				TFC – 123.0		CTR Winnipeg – 132.25	
				ATF			
DECL DIST	08	26					
TORA	6001	6001					
TODA	6001	6001					
ASDA	6001	6001					
LDA	6001	6001					



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

CYVD

EFF 12 JUN 25

CYVD-AD

AERODROME CHART




AERODROME CHART

EFF 15 JUN 23

CYWV

AERODROME CHART

				UNICOM – 122.8		CTR Edmonton – 134.7	
				ATF			
DECL DIST	10	28					
TORA	3397	3397					
TODA	3397	3397					
ASDA	3397	3397					
LDA	3200	3397					




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 20 FEB 25


CES4

				UNICOM – 123.5		TML Edmonton – 119.5	
						ATF	
DECL DIST	12	30					
TORA	3888	3888					
TODA	3888	4305					
ASDA	3888	3888					
LDA	3888	3518					



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 14 JUL 22

CJE3

WHITECOURT, AB
CYZU

AERODROME CHART

				● RADIO - 122.3		CTR Edmonton - 132.05 RADIO Edmonton - 123.27	
				● TFC - 122.3		MF	
DECL DIST	11	29					
TORA	5797	5797					
TODA	5797	5797					
ASDA	5797	5797					
LDA	5797	5797					

*** DEPARTURE PROCEDURES**
Rwy 11 - ½ - NO RIGHT turn below **4300**.
Note: Trees to 2621 ASL aprx 0.1 NM past departure end of rwy, 710° LEFT and 630° RIGHT of rwy centreline.

Rwy 29 - ½ - Climb hdg 290° to 3300 BPOC.
Note: Trees to 2608 ASL aprx 0.1 NM past departure end of rwy, 730° LEFT and 590° RIGHT of rwy centreline.

TAKE-OFF MINIMA

Rwys 11; 29: *

SCALE IN FEET

1000 0 1000 2000

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 11 JUL 24

CYZU

CYZU-AD

LOW VISIBILITY PROCEDURES

Low Visibility Procedures (RVR less than 1200 to 600 ft)

Expect Delays

When low visibility procedures are in effect, ATC will restrict operations to one aircraft on the maneuvering area at a time (1 departure or 1 arrival at a time).

Departures

Only departures on Runway 36 or 18 shall be permitted. Intersection departures will not be permitted.

Although Winnipeg Tower does not control aircraft push backs or taxiing on aprons, pilots are recommended to contact Winnipeg Tower before maneuvering on Apron I.

Contact ATC for a start / taxi time.

Sequencing of Ground Movements for Take-off

Do not request start, push back or call for taxi clearance until the reported RVR is a minimum of:

Aircraft/Pilot Take-Off Minima	Minimum RVR for Start
1200 RVR	1000 RVR
600 RVR	600 RVR

“AT NO TIME SHALL A PILOT CROSS AN ILLUMINATED RED STOP BAR”

Arrivals

When Low Visibility Procedures are in effect the arrival RWY is 36 in accordance with applicable approach minima or approach ban considerations.

Winnipeg Tower will restrict operations to one aircraft on the maneuvering area at a time (1 departure or 1 arrival at a time). Approximately 6 movements per hour.

Airport Services and Equipment Available Under Low Visibility Operations


Airport Surface Detection Equipment (ASDE).

Runway Certification

Rwy	Certification
36	RVR 600
13	RVR 1200
31	RVR 1200
18	¼ SM (Based on reported visibility)


Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

CENTRAL DE-ICING FACILITY



CENTRAL DE-ICING FACILITY


PARKING AREAS (APRON I)



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

PARKING AREAS (APRON I)

PARKING AREAS (APRON V)




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

PARKING AREAS (APRON V)

EFF 30 NOV 23

CYWG

PARKING AREAS (APRON VII)



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

PARKING AREAS (APRON VII)

EFF 31 OCT 24

PARKING AREAS

Aircraft Parking Positions (APRON I, APRON V and APRON VII)

Position	Coordinates	Position	Coordinates
2	495424.27N 0971317.65W	35	495427.73N 0971309.19W
3	495424.57N 0971319.76W	41	495416.13N 0971347.23W
4	495424.75N 0971321.91W	42	495414.80N 0971347.92W
4A	495424.48N 0971322.45W	43	495413.46N 0971348.61W
5	495424.96N 0971324.06W	54	495349.26N 0971320.58W
6	495424.65N 0971326.94W	55	495349.28N 0971317.01W
7	495424.92N 0971329.94W	56	495349.13N 0971313.21W
8	495424.76N 0971332.10W	57	495348.99N 0971309.41W
9	495424.49N 0971334.23W	58	495348.84N 0971305.60W
10	495424.13N 0971336.33W	59	495345.54N 0971321.83W
11	495423.71N 0971338.39W	61	495414.82N 0971340.50W
12	495423.15N 0971340.41W	62	495413.00N 0971341.45W
15	495421.91N 0971341.59W	63	495410.63N 0971342.68W
16	495420.51N 0971341.0W	64	495408.97N 0971344.38W
17	495419.14N 0971340.74W	64A	495409.39N 0971343.72W
18	495419.09N 0971338.53W	71	495404.16N 0971348.39W
19	495419.48N 0971336.44W	71A	495403.31N 0971346.43W
20	495419.85N 0971334.38W	72	495402.97N 0971345.97W
21	495420.20N 0971332.28W	73	495401.10N 0971343.40W
30	495423.42N 0971313.54W	73A	495400.08N 0971341.75W
31	495423.89N 0971315.57W	74	495359.61N 0971341.50W
32	495429.06N 0971314.87W	75	495357.83N 0971338.80W
33	495428.67N 0971312.94W	75A	495357.56N 0971338.20W
34	495428.23N 0971311.05W	76	495356.25N 0971337.06W


Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

PARKING AREAS

CYWG

AERODROME CHART

● ATIS – 125.8		● GND – 121.8		● TWR – 118.5		TML Winnipeg – 119.9	
				● TFC – 118.5		● ATF*	
DECL DIST	04	22	13	31	18	36	
TORA	2852	2852	3002	3002	3000	3000	
TODA	3836	3836	3986	3986	3984	3984	
ASDA	2852	2852	3002	3002	3000	3000	
LDA	2852	2852	3002	3002	3000	3000	



AERODROME CHART

EFF 17 APR 25


CYAV

CZWL-AD

WOLLASTON LAKE, SK
CZWL

AERODROME CHART

AUTO – 122.07				TFC – 123.3		RADIO Edmonton – 123.55 DRCO	
						ATF	
DECL	DISTS	17	35				
TORA		3793	3793				
TODA		4777	4777				
ASDA		3793	3793				
LDA		3793	3793				



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART


EFF 17 APR 25

CZWL

CZWL-AD

AERODROME CHART

		UNICOM – 122.8 (AU)				CTR Winnipeg – 133.15			
						ATF			
DECL DIST	10	28							
TORA	3397	3397							
TODA	4381	4381							
ASDA	3397	3397							
LDA	3397	3397							



AERODROME CHART

EFF 11 JUL 24

CZAC

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

YORKTON REGIONAL, SK
CYQV

AWOS - 128.72				RADIO Regina - 119.65 296.6 TFC - 119.65 296.6		CTR Winnipeg - 132.52 RADIO Edmonton - 123.47	
DECL DIST	04	22	13	31			
TORA	4800	4800	2984	2984			
TODA	5784	5784	3968	3968			
ASDA	4800	4800	2984	2984			
LDA	4800	4800	2984	2984			

Runway 13-31 restricted to acft less than 15,000 lbs.

ANNUAL RATE OF CHANGE 7° W

VAR 7° E 2018

ELEV 1597

AD

218°

ELEV 1609

4800 x 148

128°

CYQV
N51 15.88
W102 27.70

2984 x 98

asphalt/gravel

308°

ELEV 1611

AD

ELEV 1635

A

B

1715

* DEPARTURE PROCEDURE

Runway 22 - 1/2

Note: Building to 1666 ASL aprx 270' past departure end of rwy, 560' LEFT of rwy centreline. Trees to 1706 ASL aprx 0.3 NM past departure end of rwy, 530' LEFT of rwy centreline.

TAKE-OFF MINIMA

Runway 04: 1/2

Runway 22: *

Runways 13, 31: NOT ASSESSED

SCALE IN FEET

1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART


EFF 31 OCT 24

CYQV

CYQV-AD

AERODROME CHART

AWOS Big Trout Lake – 128.7				TFC – 123.2		ATF			
DECL DIST	12	30							
TORA	3609	3609							
TODA	3609	3609							
ASDA	3609	3609							
LDA	3609	3609							



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 25 JAN 24


CKB6

CYYW-AD

ARMSTRONG, ON
CYYW

AERODROME CHART

MET – 128.65				TFC – 122.8		ATF			
DECL DIST	12	30							
TORA	4006	4006							
TODA	4006	4006							
ASDA	4006	4006							
LDA	4006	4006							



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 24 MAR 22

CYYW

CYYW-AD

AERODROME CHART




AERODROME CHART

EFF 12 JUN 25

CNP3

AERODROME CHART

AWOS – 128.77				TFC – 122.8		ATF			
DECL DISTS	06	24							
TORA	3495	3495							
TODA	3695	3695							
ASDA	3495	3495							
LDA	3495	3495							




AERODROME CHART


EFF 12 JUN 25

CYAT

AERODROME CHART



AERODROME CHART




AERODROME CHART

EFF 17 APR 25

CYLS

AERODROME CHART

AWOS Big Trout Lake – 128.7				TFC – 123.2		ATF			
DECL DIST	07	25							
TORA	3503	3503							
TODA	3503	3503							
ASDA	3503	3503							
LDA	3503	3503							




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 30 JAN 20

CNE3


AWOS – 128.7				TFC – 123.2		RADIO London – 123.55	
						ATF	
DECL DISTS	14	32					
TORA	3906	3906					
TODA	4306	4306					
ASDA	3906	3906					
LDA	3906	3906					



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART


					 UNICOM – 123.3		TML Toronto – 119.3	
	08	26	15	33		ATF*		
TORA	2500	2500	3500	3500				
TODA	2500	2500	3500	3500				
ASDA	2500	2500	3500	3500				
LDA	2309	2500	3500	3500				




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

		UNICOM – 122.82					CTR Toronto – 119.7	
		ATF						
DECL	DISTS	05	23	11	29	17	35	
TORA		5036	5036	2626	2626	2626	2626	
TODA		5036	5636	3610	3610	3610	3526	
ASDA		5036	5036	2626	2626	2626	2626	
LDA		5036	5036	2626	2626	2626	2626	




AUTO Ogdensburg Intl – 118.52		UNICOM – 123.0				CTR Montreal – 134.67		
		ATF						
DECL DIST	04	22	16	34				
TORA	4505	4505	2203	2203				
TODA	4505	4505	2203	2203				
ASDA	4505	4505	2203	2203				
LDA	4505	4505	2203	2203				



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

AUTO – 122.55					UNICOM – 123.5		TML Toronto – 119.3	
DECL DISTS	09	27	14	32		ATF*		
TORA	2464	2464	3950	3950				
TODA	2464	2464	3950	3950				
ASDA	2464	2464	3950	3950				
LDA	2136	2210	3769	3541				



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

CAT LAKE, ON
CYAC

CYAC

ANNUAL RATE OF CHANGE 5' W
VAR 1° W
2003

ELEV 1339
108°
11
CYAC
N51 43.64
W91 49.47
3963 x 100
gravel
288°
29
ELEV 1336
AP

*** DEPARTURE PROCEDURE**
Rwy 11 - ½
Note: Trees to 1454 ASL aprx 0.2 NM past departure end of rwy.
Rwy 29 - ½
Note: Trees to 1467 ASL aprx 0.1 NM past departure end of rwy.

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

Note: Trees to 1467 ASL aprx 0.1 NM past departure end of rwy.

Rwys 11; 29: *


CYAC

CYAC-AD

CYCE-AD

CENTRALIA/JAMES T. FIELD MEMORIAL, ON
CYCE

AERODROME CHART



AERODROME CHART


EFF 8 SEP 22

CYCE

CYCE-AD

AERODROME CHART

				TFC- 122.8		ATF			
DECL DIST	05	23	10	28					
TORA	3006	3006	5003	5003					
TODA	3990	3990	5987	5987					
ASDA	3006	3006	5003	5003					
LDA	3006	3006	5003	5003					



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 11 JUL 24

CYLD

AERODROME CHART

AWOS – 122.97				UNICOM – 123.2		ARR Selfridge – 119.6 318.2 O/T CTR Cleveland – 132.25 298.87	
						ATF	
DECL DIST	06	24					
TORA	5502	5502					
TODA	5502	5502					
ASDA	5502	5502					
LDA	5002	5002					



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 16 MAY 24

CYCK

AERODROME CHART

AUTO – 122.55				TFC – 122.8		CTR Toronto – 128.3	
						ATF	
DECL DIST	13	31					
TORA	4484	4484					
TODA	4484	4484					
ASDA	4484	4484					
LDA	4484	4484					



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 2 OCT 25

CYCN

AERODROME CHART


AUTO – 122.17		UNICOM – 122.85				CTR Toronto – 124.02		
						ATF		
DECL DIST	01	19	13	31				
TORA	2548	2548	5000	5000				
TODA	2548	2548	5984	5000				
ASDA	2548	2548	5000	5000				
LDA	2548	2548	5000	5000				




AERODROME CHART

CNY3

AERODROME CHART



AERODROME CHART




AERODROME CHART

CYVZ

AERODROME CHART

AUTO – 122.17		UNICOM – 122.95				CTR Toronto – 128.3 133.72		
						ATF		
DECL DIST	10	28						
TORA	5002	5002						
TODA	5002	5002						
ASDA	5002	5002						
LDA	5002	5002						



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 15 JUN 23

CDT9

AERODROME CHART

AWOS – 128.7				RADIO Sioux Lookout – 122.1		CTR Winnipeg – 132.2	
						MF	
DECL DIST	12	30					
TORA	5993	5993					
TODA	6193	6977					
ASDA	5993	5993					
LDA	5993	5796					




AERODROME CHART

EFF 12 AUG 21


CYHD

AWOS – 128.6						TFC – 122.0		RADIO London – 123.37	
						MF			
DECL DISTS	08	26	16	34					
TORA	5998	5998	3019	3019					
TODA	6598	6898	3119	3119					
ASDA	5998	5998	3019	3019					
LDA	5998	5998	3019	3019					



AERODROME CHART

AUTO – 123.17		UNICOM – 122.77				CTR Toronto – 124.02		
						ATF		
DECL DIST	08	26	13	31				
TORA	3014	3014	3936	3936				
TODA	3014	3014	3936	3936				
ASDA	3014	3014	3936	3936				
LDA	3014	3014	3936	3936				




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 15 JUN 23

CNV8

AERODROME CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

CYEL

AERODROME CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 5 OCT 23


CYFA

AUTO Falls Intl – 120.0						UNICOM – 122.8		CTR Minneapolis – 120.9 RADIO London – 123.55		
		ATF								
DECL DIST	12	30								
TORA	4493	4493								
TODA	5477	5477								
ASDA	4493	4493								
LDA	4493	4493								



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 24 MAR 22

CYFH

CYER


AWOS – 124.55				TFC – 122.8		ATF	
DECL DISTS	15	33					
TORA	3519	3519					
TODA	3519	3519					
ASDA	3519	3519					
LDA	3519	3519					



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

						CTR Toronto – 135.5		
		TFC – 123.5				ATF		
DECL DIST	01	19	10	28				
TORA	2415	2415	2493	2493				
TODA	2415	2415	2493	2493				
ASDA	2415	2415	2493	2493				
LDA	2370	2415	2493	2493				




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

CPJ4-HP

GERALDTON (DISTRICT HOSPITAL), ON
CPJ4

HELIPORT CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


HELIPORT CHART

EFF 24 JUL 14

CPJ4


CPJ4-HP

AWOS – 128.1		UNICOM – 122.8				RADIO London – 123.47		
		ATF						
DECL DIST	08	26						
TORA	5007	5007						
TODA	5207	5207						
ASDA	5007	5007						
LDA	5007	5007						



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART




AERODROME CHART

EFF 23 FEB 23

CYGD

AERODROME CHART

AWOS – 128.72		UNICOM – 122.8				CTR Toronto – 135.4 RADIO London – 126.7		
		ATF						
DECL DISTS	11	29	05	23				
TORA	5500	5500	2615	2615				
TODA	6484	6484	2615	2615				
ASDA	5500	5550	2615	2615				
LDA	5500	5500	2615	2615				




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 12 JUN 25

CYZE

AERODROME CHART




AERODROME CHART

EFF 12 JUN 25

CYHM

TAXI CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

TAXI CHART

EFF 12 JUN 25

CYHM

LOW VISIBILITY PROCEDURES

Low Visibility Procedures (Less than RVR 1200 to RVR 600)

Application

These procedures apply to ground movements of aircraft departing under low visibility conditions. Departures below RVR 600 are not authorized. When weather conditions indicate visibility below RVR 1200 is imminent, procedures will be implemented restricting aircraft and vehicle operations on the movement area. The following message will be added to the ATIS broadcast.
“LOW VISIBILITY PROCEDURES IN EFFECT”

General

Low Visibility Taxi Routes

Taxi routes during low visibility operations are exclusive to the following routes:

- 1. Route 1 – Taxiway C
- 2. Route 2 – Taxiway B, rwy 06, taxiway C.
- 3. Taxiway surfaces are painted with enhanced yellow and black centreline markings. Aircraft restricted to one movement in or out at any time during low visibility operations. Alternate routing may be specified by ATC as required.

ATC may find it necessary to suspend, restrict, or terminate low visibility operations.

Departures

Sequencing of Aircraft Ground Movements for Take-off.

Do not request taxi clearance until the reported RVR is greater than:


Aircraft/Pilot Take-off Minima	Minimum RVR for Start
1200 RVR	1000 RVR
600 RVR	600 RVR

Arrivals

Taxi route will be specified by ATC.

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

PARKING AREAS



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

PARKING AREAS

EFF 12 JUN 25

PARKING AREAS

Aircraft Parking Position

Position	Coordinates	Position	Coordinates
1	430949.20N 0795529.86W	11	430954.72N 0795548.15W
2	430950.45N 0795529.28W	12	430955.28N 0795550.61W
2A	430950.15N 0795530.61W	13	430955.84N 0795553.09W
3	430950.94N 0795530.90W	14A	431001.46N 0795544.80W
4	430950.70N 0795532.63W	15	431001.64N 0795545.36W
5	430951.63N 0795534.37W	17	431000.94N 0795542.30W
6	430951.59N 0795536.52W	19	431000.24N 0795539.24W
7	430952.52N 0795538.26W	21	430959.55N 0795536.19W
8	430952.47N 0795540.41W	21A	430959.72N 0795536.95W
9	430954.03N 0795543.37W	23	430945.60N 0795523.68W
9A	430953.17N 0795543.75W	23A	430943.58N 0795524.51W
10	430954.15N 0795545.68W	24	430943.78N 0795524.45W
10A	430954.46N 0795548.34W	25	430941.97N 0795525.21W


Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

PARKING AREAS

CYHM

AERODROME CHART

		UNICOM – 122.8				CTR Toronto – 132.57		
						ATF		
DECL	DISTS	01	19	09	27			
TORA		4001	4001	2502	2502			
TODA		4001	4001	2502	2502			
ASDA		4001	4001	2502	2502			
LDA		4001	4001	2171	2382			




AERODROME CHART

EFF 25 JAN 24

CYHS

CYHF-AD

HEARST (RENE FONTAINE) MUNI, ON
CYHF



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

CYHF

EFF 25 JAN 24

CYHF-AD

HORNEPAYNE MUNI, ON
CYHN

CYHN

ANNUAL RATE OF CHANGE 1' W
VAR 8° W
2013

ELEV 1088

247° AS

3504 x 75

CYHN
N49 11.59
W84 45.56

Down 0.36%

067° AS

ELEV 1101

49 11.7

49 11.4

84 45.7

84 45.3

*** DEPARTURE PROCEDURE**
Rwy 07 - ½ - Requires a minimum climb gradient of **330 ft/NM** to **1300**.
Note: Trees to 1237 ASL aprx. 0.1 NM past departure end of rwy.
 or
 SPEC VIS - Climb in visual conditions to cross the aprt at or above **1900 BPOC**.

Rwy 25 - ½
Note: Trees to 1210 ASL aprx 0.1 NM past departure end of rwy,
 700' LEFT and 600' RIGHT of rwy centreline.

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
330 FT/NM	500	660	770	880	990	1100	1380	1650

TAKE-OFF MINIMA

Rwys 07, 25: *

SCALE IN FEET


1000 0 1000

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

CYHN

CYHN-AD

AERODROME CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

CNE4

AERODROME CHART

				TFC – 122.2		CTR Toronto – 132.7	
				MF			
DECL DIST	17	35					
TORA	5506	5506					
TODA	5966	6490					
ASDA	5506	5506					
LDA	5506	5506					




AERODROME CHART

EFF 5 OCT 23

AERODROME CHART

				TFC – 123.2		ATF			
DECL DIST	03	21							
TORA	3519	3519							
TODA	4503	4503							
ASDA	3519	4319							
LDA	3519	3519							




AERODROME CHART

EFF 10 AUG 23

AERODROME CHART

				TFC – 122.8		ATF			
DECL DIST	06	24							
TORA	3903	3903							
TODA	3903	3903							
ASDA	3903	3903							
LDA	3903	3903							




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 10 AUG 23

CZKE

AERODROME CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

CPV8

EFF 24 MAR 22

AERODROME CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 20 FEB 25

CYKM

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 24 MAR 22

CNM5

AERODROME CHART

● ATIS – 135.55				● RADIO – 122.5		CTR Montreal – 135.05 RADIO London – 123.55	
				● TFC – 122.5		● MF	
DECL DIST	01	19	07	25			
TORA	6001	6001	3909	3909			
TODA	7001	6985	4893	4893			
ASDA	6001	6001	3909	3909			
LDA	5622	5000	3909	3909			



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 17 APR 25

CYKX-AD

KIRKLAND LAKE, ON
CYKX

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 17 APR 25


CYKX

CYKX-AD

● ATIS – 125.1		● GND Waterloo – 121.8		● TWR Waterloo – 126.0 118.55		CTR Toronto – 128.27	
● MET – 125.1				● TFC – 126.0		● MF	
DECL DIST	08	26	14	32			
TORA	7003	7003	4103	4103			
TODA	7987	7659	5087	4634			
ASDA	7003	7003	4103	4103			
LDA	7003	7003	4103	4103			



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 08, 26: (1/4sm)	NOT AUTHORIZED
TAKE-OFF MINIMA	
All Rws: *	




CYLH-AD

LANSDOWNE HOUSE, ON
CYLH

AERODROME CHART

AWOS – 128.4				TFC – 122.8		RADIO London – 123.37 DRCO	
				ATF			
DECL DIST	08	26					
TORA	3484	3484					
TODA	4468	4468					
ASDA	3484	3484					
LDA	3484	3484					



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 17 APR 25

CYLH

CYLH-AD

AERODROME CHART




AERODROME CHART

CLM2

EFF 11 JUL 24

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

LONDON, ON
CYXU

• ATIS - 127.8
 • GND - 121.9
 • TWR - 119.4 125.65
 • RADIO Sudbury - 119.4
 • CTR Toronto - 135.3
 • MF*

DECL DIST	09	27	15	33				
TORA	6300	6300	8800	8800				
TODA	7284	7284	9784	9625				
ASDA	6300	6300	8800	8800				
LDA	6300	6300	8800	8800				

① Shell FBO
 ② ERS
 ③ World Fuels FBO
 ④ ATB
 ⑤ AIR CARGO FACILITY

LDA FOR LAND AND HOLD SHORT OPERATIONS (LAHSO)		
FROM	TO	LDA in ft
Thld Rwy 09	Short of Rwy 15-33	1584
Thld Rwy 27	Short of Rwy 15-33	3656
Thld Rwy 15	Short of Rwy 09-27	910
Thld Rwy 33	Short of Rwy 09-27	6859

* DEPARTURE PROCEDURE
 Refer to DEPARTURE PROCEDURE page.

RUNWAY LEVEL OF SERVICE
 RVO: Rwy 15: RVR 1200, Rwy 33: (1/4 sm)
 LVO: NOT AUTHORIZED

TAKE-OFF MINIMA
 All Rwys: *


SCALE IN FEET
 2000 0 2000

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

CYXU

CYXU-AD

PARKING AREAS (APRON V)




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

PARKING AREAS (APRON V)

EFF 20 FEB 25

AERODROME CHART

AUTO – 129.15					UNICOM – 122.8		CTR Winnipeg – 134.07	
		ATF						
DECL DIST	05	23						
TORA	3603	3603						
TODA	3603	3603						
ASDA	3603	3603						
LDA	3603	3603						



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART


EFF 12 JUN 25

CYMG

CYEM-AD

MANITOWANING/MANITOULIN EAST MUNI, ON
CYEM

		UNICOM – 122.8				CTR Toronto – 135.4		
		ATF						
DECL DIST	02	20						
TORA	3498	3498						
TODA	4482	4482						
ASDA	3728	3728						
LDA	3498	3498						



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 7 AUG 25


CYEM

CYEM-AD

CYSP

CTR Winnipeg – 134.07

DECL DIST	16	34	16	34				
TORA	3933	3933	3933	3933				
TODA	4300	4133	3933	3933				
ASDA	4300	3933	3933	3933				
LDA	3933	3735	3933	3735				




CYSP

CYSP-AD

CYOS-AD

MEAFORD/MAJOR-GENERAL RICHARD ROHMER, ON
CYOS

		UNICOM – 123.0 (AU)				CTR Toronto – 132.57			
		ATF							
DECL	DISTS	18	36						
TORA		3933	3933						
TODA		3933	4917						
ASDA		3933	3933						
LDA		3933	3933						



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

CYOS

EFF 17 APR 25

CYOS-AD


				UNICOM – 122.85 (AU)		CTR Toronto – 124.02	
						ATF	
DECL	DISTS	16	34				
TORA		3996	3996				
TODA		4196	4266				
ASDA		3996	3996				
LDA		3996	3996				



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

AWOS – 124.8		● RADIO Timmins – 122.5				CTR Toronto – 133.72		
		● TFC – 122.5				MF*		
DECL DIST	06	24	14	32				
TORA	4000	4000	3591	3591				
TODA	4984	4984	4575	4575				
ASDA	4000	4000	3591	3591				
LDA	4000	4000	3591	3591				



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 11 JUL 24

CYMO

AERODROME CHART

AWOS – 124.57				RADIO Timmins – 122.3		RADIO Timmins – 122.3	
						MF	
DECL DIST	18	36					
TORA	6000	6000					
TODA	6984	6700					
ASDA	6000	6000					
LDA	5200	6000					




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 17 APR 25

AERODROME CHART

AWOS – 124.45				TFC – 123.2		ATF			
DECL DIST	05	23							
TORA	3508	3508							
TODA	3508	3508							
ASDA	3508	3508							
LDA	3508	3508							



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 8 SEP 22

CZMD

NAKINA, ON
CYQN

CYQN




CYQN

CYQN-AD

AERODROME CHART

● ATIS – 124.9 ● AWOS – 124.9					● RADIO – 118.3 ● TFC – 118.3		CTR Toronto – 127.25	
					MF*			
DECL DISTS	08	26	13	31	18	36		
TORA	10004	10004	2000	2000	4492	4492		
TODA	10988	10988	2000	2000	5476	5476		
ASDA	10004	10004	2000	2000	4492	4492		
LDA	10004	10004	2000	2000	4492	4492		



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 08: RVR 1200 RWY 26: (¼sm)	NOT AUTHORIZED
TAKE-OFF MINIMA	
Rwys 08; 18; 36: ★ Rwy 26: ½ Rwys 13; 31: NOT ASSESSED	


AERODROME CHART

EFF 2 OCT 25

CYYB

AERODROME CHART

				TFC - 122.8		ATF			
DECL	DISTS	13	31						
TORA		3518	3518						
TODA		3518	3518						
ASDA		3518	3518						
LDA		3518	3518						



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 27 JAN 22

CKQ3

AERODROME CHART

AWOS – 128.12				TFC – 123.2		CTR – Winnipeg 135.47	
				ATF			
DECL DIST	09	27					
TORA	3514	3514					
TODA	3514	3514					
ASDA	3514	3514					
LDA	3514	3514					




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART


EFF 12 JUN 25

AERODROME CHART




CARTE D'AÉRODROME

ATIS – 132.95 (Fr) 121.15 (Ang)		CLNC DEL – 119.4 GND – 121.9			TWR – 118.8		DEP – 128.17 RADIO Québec – 123.15	
DIST DÉCLARÉES	04	22	07	25	14	32		
TORA	3300	3300	8000	8000	10005	10005		
TODA	3300	3300	8984	8984	10989	10989		
ASDA	3300	3300	8000	8000	10005	10005		
LDA	3050	3300	8000	8000	10005	10005		



TAXI CHART



TAXI CHART

EFF 7 AUG 25

CYOW

CYOW

ATIS – 132.95 (Fr) 121.15 (Ang)	CLNC DEL – 119.4 GND – 121.9	TWR – 118.8
---------------------------------	---------------------------------	-------------

Piste 04-22: 3300 x 75

Aviation générale

Piste 04-22 et twy M, P, Q et T
restreintes aux aéronefs d'un poids
inférieur à 60,000 lbs



POINTS CHAUDS

HS 1-Lorsqu'ils circulent sur l'aire de trafic, les aéronefs manquent les voies de circulation E et C.

déglacage

ATTENTION - Les rambarbes bordant le pont ont 28 pouces de haut. Pont réservé aux aéronefs de moins de 122,000 lbs


TOUR DE
CONTRÔLE

8000 x 197
asphalte rainurée

Aire de trafic non-contrôlée
Les aéronefs en circulation au sol doivent
demeurer dans les allées de circulation.
Les aéronefs au sol ne doivent pas circuler
dans l'espace entre l'aérogare et les
aéronefs refoulés.
Cédez le passage aux aéronefs en circulation
au départ des barrières 1 à 6.

Pour DÉGIVRAGE voir carte
OPÉRATIONS DE DÉGIVRAGE.

ÉCHELLE EN PIEDS



Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

CYOW

EFF 7 AOÛT 25

DE-ICING OPERATIONS

Gate De-icing – Originating Flights

- Gate de-icing is approved for environmental frost under the following conditions:
 - Active precipitation is not forecasted for the operational period.
 - Apron conditions are such as to allow the recovery of spent fluid (no snow, ice, sand, gravel, etc.).
 - The required fluid to de-ice is optimal for the presenting frost and up to the minimum 1 litre/square metre.
 - Winds are light to variable (8 knots).
- De-icing for originating flights will take place 60-90 minutes before scheduled departure time.
- Staff will conduct initial inspection of acft to determine the requirement for de-icing and will proceed with spray if reqd.
- Airlines must ensure acft are configured and ready for de-icing prior to the above time. De-icing will take place under the assumption that originating flights are configured.
- De-icing confirmation will be sent electronically or via fax to airline operations following de-icing. Flight crews requiring additional information may contact PAD CONTROL on 122.92.
- No holdover time is provided for on gate de-icing.
- The process of **“Pre-Spray”** (Lines 2-3) 60-90 mins before push is being reviewed due to frost regeneration (fall weather patterns with high humidity and close OAT/DP spread).
- Unless requested of de-ice crews, the PIC is responsible for **“Pre-flight take off inspections.”** Any treatments by de-ice crews for Pre-Sprays will be followed by an **“appropriate post de-ice inspection.”** The **“Pre-Spray”** treatments 60-90 mins before push do not include a **“pre-take off”** inspection.

Gate De-icing – Turn Flights

- All conditions of gate de-icing exist from above list.
- De-ice crews will not interact with turn aircraft unless requested – Contact PAD CONTROL on 122.92 to arrange. There will be no pre-emptive contact with the aircraft without request for service. Pre-take off De-ice check remains with the flight crew unless a live spray is completed at pushback.

Centralized De-icing Facility Operations

- Flow – North to South
 - Entry point is K or AA via Alpha. Acft must hold short of the CDF on the entry point and establish radio contact with PAD CONTROL on 122.92.
- Flow – South to North
 - Entry point is CC or BB via Alpha. Acft must hold short of the CDF on the entry point and establish radio contact with PAD CONTROL on 122.92.
- Follow taxi instructions via East Line to Bays 1, 2, 3 via West Line Bays 4, 5, 6.
- Aircraft will be staged on the East/West Line short of AA/BB when necessary.
- When exiting CC/K – Acft must maintain listening watch on the E/W staging lines on 122.92 until reaching Twy A.

NOTE: Aircraft intended on returning to terminal gates after de-icing must drip dry for 25 minutes on CDF.


DE-ICING OPERATIONS

De-icing Requirements

- 1. Wings and Stabs refers to the upper surfaces of the wings, upper/lower surface of the Horizontal Stabilizers and both sides (including rudder) of the Vertical Stabilizer.
- 2. Fuselage includes all components from the front cabin doors aft and Wings and Stabs.
- 3. Full Body includes the cockpit/radome plus Fuselage, Wings and Stabilizers.
- 4. Individual treatments like “inspections only”, “radome”, “winglets” can be done upon request.
- 5. Hard leading edges tactiles/underwing inspections and treatments may require engine shut down if inlet is in close proximity to surface requiring attention.

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

DE-ICING OPERATIONS



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

DE-ICING OPERATIONS	
1. Ctc PAD CONTROL on 122.925 30 min prior to dep if de-icing is rqrd. Notify of any special treatments prior to taxi to CDF. 2. Ctc Ottawa GND after pushback for taxi to CDF. 3. Hold short of the CDF on K, AA, BB or CC and ctc PAD CONTROL for further taxi. 4. Follow instructions and electronic sign boards to de-icing bays. 5. Stop on the 2nd (illuminated) yellow stop bar, immediately set brakes and advise PAD CONTROL. DO NOT MOVE ACFT. This will allow positioning of trucks while you configure your aircraft. 6. Once instructed switch to ICEMAN on 122.350, confirm brakes are set, confirm treatment and that acft is configured for treatment (engines at idle/props feathered/pacs off). If you can't reduce engines to idle ICEMAN must know, de-icing may not be possible with running engines. 7. After de-icing, configure acft for taxi, however, DO NOT MOVE ACFT. 8. Once instructed, ctc PAD CONTROL for taxi. 9. Follow instructions to designated exit point. Holding short of Twy A, ctc GND 121.9.	
TYPE 1 - All Clear Lift-Off E188	TYPE IV - UCAR ADF ENDURANCE EG106 100%
BAY RESTRICTIONS Bay 1, 3, 4, 6 - May be used by acft with wingspans 36m (118') or less. Bay 2 - May be used by acft with the wingspan 65m (213') or less. If CC used, the taxi must be on the East taxi line only to/from Bay 2. Bay 5 - May be used by acft with the wingspan 65m (213') or less. If CC used, taxi must be on the East taxi line only with crossover to/from Bay 5.	AD HOC FLIGHTS 1. Obtain a projected acceptance time for de-icing from PAD CONTROL on 122.925 or via phone 613-248-0228 . 2. Submit Authorization form via fax 613-248-0860 or via e-mail YOW_InlandOps@Inlandgroup.ca. 3. An estimate of litres required will be provided to flight crew. 4. Ad hoc aircraft not abiding by the above may be denied service at the CDF.

DE-ICING OPERATIONS

EFF 20 FEB 25

OPÉRATIONS DE DÉGIVRAGE

Dégivrage à la barrière – vols cédulés

1. Le dégivrage aux portes d'embarquement est approuvé pour le givre dans les conditions suivantes :
 - Les précipitations actives ne sont pas prévues pour la période opérationnelle.
 - Les conditions du tablier sont telles qu'elles permettent de récupérer le fluide usé (pas de neige, de glace, de sable, de gravier, etc.).
 - Le liquide de dégivrage requis est optimal pour le givre présent et ce, jusqu'à un minimum de 1 litre / mètre carré.
 - Les vents sont de légers à variables (8 nœuds).
2. Dégivrage pour les vols cédulés aura lieu 60 – 90 minutes avant l'heure de départ cédulé.
3. Technicien doit faire une inspection initiale de l'appareil pour déterminer les besoins en dégivrage et vont procéder au dégivrage si requis.
4. Les sociétés aériennes doivent s'assurer que l'appareil est configuré et prêt pour le dégivrage. Le dégivrage va avoir lieu en prenant compte que les vols cédulés sont configurés.
5. La confirmation de dégivrage sera envoyée électroniquement ou par fax à la société aérienne après le dégivrage. L'équipage requérant de l'information additionnelle peut contacter CTL DÉGIVRAGE sur 122.92.
6. Aucun temps d'efficacité n'est fourni pour le dégivrage à la barrière.
7. Le processus de « **Pré-application** » (lignes 2-3), 60-90 minutes avant le refoulement est en cours de révision en raison de la régénération du givre (conditions météorologiques automnal, incluant une forte humidité et une relation étroite entre la TAE / PR).
8. À moins que les équipes de dégivrage ne le demandent, le commandant de bord est responsable des « **inspections avant le décollage** ». Tout traitement effectué par les équipes de dégivrage pour les pré-applications sera suivi d'une « **inspection post-dégivrage appropriée** ». Les traitements de « **pré-application** » de 60 à 90 minutes avant le refoulement n'incluent pas une inspection de « **pré-décollage** ».

Dégivrage à la barrière – vols en transit

1. Toutes les conditions de dégivrage aux portes d'embarquement existent depuis la liste ci-dessus.
2. Les équipes de dégivrage n'interagiront pas avec le virage des avions à moins que cela ne soit demandé – Contactez PAD CONTROL sur 122.92 pour organiser la manoeuvre. Il n'y aura pas de contact préventif avec l'aéronef sans demande de service. La vérification de dégivrage avant le décollage demeure à l'équipage de l'aéronef à moins qu'une application directe soit complétée au refoulement.

Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

OPÉRATIONS DE DÉGIVRAGE

Opération au centre de dégivrage

1. Circulation – Nord vers Sud

- Point d'entrée est K ou AA via Apha. L'appareil doit se tenir à l'écart du CDF au point d'entrée et établir le contact radio avec CTL DÉGIVRAGE sur 122.92.

Circulation – Sud vers Nord

- Points d'entrée est CC ou BB via Alpha. L'appareil doit se tenir à l'écart du CDF au point d'entrée et établir le contact radio avec CTL DÉGIVRAGE sur 122.92.
2. Suivre les instructions pour le taxi via la ligne Est pour les baies 1,2,3 ou via la ligne Ouest pour les baie 4,5,6.
 3. L'appareil sera mis en attente sur la ligne Est/Ouest à l'écart de AA/BB lorsque nécessaire.
 4. À la sortie de CC / K – L'aéronef doit rester attentif aux lignes d'arrêt E / W et au 122.92 jusqu'à ce qu'il atteigne le Twy A.

Note : L'appareil qui doit retourner à la barrière doit rester au CDF pendant 25 minutes afin d'assécher l'appareil

Besoins en dégivrage

1. Ailes et Stabilisateurs se réfère aux surfaces supérieures des ailes, aux surfaces supérieures / inférieures des Stabilisateurs Horizontaux et des deux côtés (y compris le gouvernail) du Stabilisateur Vertical.
2. Le Fuselage comprend toutes les composantes, des portes de cabine avant vers l'arrière ainsi que les Ailes et Stabilisateurs.
3. L'appareil complet comprend la cabine de pilotage, le radôme ainsi que le Fuselage et les Ailes et Stabilisateurs.
4. Des traitements individuels tels que « inspections seulement », « radôme », « ailettes » peuvent être effectués sur demande.
5. Les inspections tactiles et les traitements sous les ailes peuvent nécessiter la fermeture d'un moteur si l'entrée est à proximité de la surface nécessitant une attention.

Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

OPÉRATIONS DE DÉGIVRAGE

ATIS – 132.95 (Fr) 121.15 (Ang) GND – 121.9 PAD CTL – 122.92 ICEMAN – 122.35			
LÉGENDE ZONE DE SÉCURITÉ DE VÉHICULE PANNEAU ÉLECTRONIQUE BARRES D'ARRÊT		BAIES DE DÉGIVRAGE 1 2 3 4 5 6 AA BB A A	
Linge E pour aéronefs d'envergure moins de 36m (118') E Ligne d'attente Est		E Lignes d'attente Est & Ouest W Ligne W pour aéronefs d'envergure moins de 36m (118') Note: Baie 2-référez à SB1 & SB3 Baie 5-référez à SB4 & SB6	
OPÉRATIONS DE DÉGIVRAGE 1. Ctc CTL DÉGIVRAGE 122.925 30 min avant le dép si dégivrage est requis. SVP aviser de tout traitement spécial avant de rouler à l'installation centrale de dégivrage. 2. Ctc Ottawa SOL, après refoulement pour circuler au CDF. 3. Rester à l'écart du CDF sur K, AA, BB ou CC et ctc CTL DÉGIVRAGE pour circuler. 4. Suivez les instructions et les panneaux électroniques pour procéder à la baie de dégivrage. 5. Arrêtez-vous sur la deuxième barre d'arrêt jaune (éclairée), actionnez immédiatement les freins et confirmez avec PAD CONTROL. NE PAS BOUGER L'AÉRONEF. Cela permettra de positionner les camions pendant que vous configurez votre avion. 6. Une fois qu'on vous le demande, passez à ICEMAN au 122.350. Confirmez que les freins sont serrés, le traitement désiré et que votre avion est configuré pour le traitement (Moteurs au ralenti / hélices mises en drapeau). Si vous ne pouvez pas réduire les moteurs au ralenti, avisez ICEMAN, il se peut que le dégivrage ne soit possible avec les moteurs en marche. 7. Après dégivrage, configurez l'appareil pour circuler, toutefois, NE PAS BOUGER L'APPAREIL. 8. Une fois avisé, ctc CTL DÉGIVRAGE pour circuler. 9. Suivre les instructions pour le point de sortie désigné. À l'écart de la voie de circulation A ctc SOL 121.9.			
TYPE 1 - All Clear Lift-Off E188		TYPE IV - UCAR ADF ENDURANCE EG106 100%	
RESTRICTIONS DES BAIES DE DÉGIVRAGE Baies 1, 3, 4, 6 - Peuvent être utilisées par les aéronefs d'envergure de 36m (118') ou moins Baie 2 - Peut être utilisé par un aéronef ayant une envergure de 65m (213pi) ou moins. Si CC est utilisée, le taxi doit être sur la ligne de taxi Est uniquement vers/de la baie 2. Baie 5 - Peut être utilisé par un aéronef ayant une envergure de 65m (213pi) ou moins. Si CC est utilisée, le taxi doit être sur la ligne de taxi Est uniquement vers/de la baie 5.		VOLS AD HOC 1. Obtenir une heure projetée pur le dégivrage en contactant CTL DÉGIVRAGE sur 122.925 ou par téléphone au 613-248-0228. 2. Soumettre le formulaire d'autorisation par fax au 613-248-0860 ou par courriel à YOW_inlandOps@Inlandgroup.ca. 3. Un estimé des litres de glycol requis sera transmis à l'équipage. 4. Un vol AD HOC ne se conformant pas à la procédure ci-haut mentionné, peut se voir refuser l'accès au centre de dégivrage.	


Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

OPÉRATIONS DE DÉGIVRAGE

CYOW

EFF 20 FÉV 25

PARKING AREAS (APRON I)




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

PARKING AREAS (APRON I)

EFF 7 AUG 25

CYOW

PARKING AREAS (APRON II)




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

PARKING AREAS (APRON II)

CYOW

EFF 20 FEB 25

AIRES DE STATIONNEMENT (AIRE DE TRAFIC I)




AIRES DE STATIONNEMENT (AIRE DE TRAFIC I)

CYOW

EFF 7 AOÛT 25

AIRES DE STATIONNEMENT (AIRE DE TRAFIC II)



Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

AIRES DE STATIONNEMENT (AIRE DE TRAFIC II)

EFF 20 FÉV 25

ATIS - 132.95 (Fr) 121.15 (Ang)

CLNC DEL - 119.4

GND - 121.9

POSITIONNEMENT - 122.4

AIRES DE STATIONNEMENT (AIRE DE TRAFIC II)

EFF 20 FÉV 25


ATIS - 132.95 (Fr) 121.15 (Ang)

CLNC DEL - 119.4

GND - 121.9

POSITIONNEMENT - 122.4

AERODROME CHART




AERODROME CHART

EFF 25 JAN 24

CNK4

AERODROME CHART

AWOS – 128.52				TFC – 122.8		RADIO London – 123.27	
						ATF	
DECL DIST	11	29					
TORA	3520	3520					
TODA	3520	3520					
ASDA	3520	3520					
LDA	3520	3520					




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 5 OCT 23

CYPO

AERODROME CHART




AERODROME CHART

CYPT

EFF 26 DEC 24

AERODROME CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART


EFF 25 JAN 24

AWOS – 126.92		UNICOM – 123.0				CTR Toronto – 134.25		
						MF		
DECL DIST	09	27	13	31				
TORA	7005	7005	2000	2000				
TODA	7300	7300	2000	2000				
ASDA	7005	7005	2000	2000				
LDA	7005	7005	2000	2000				



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART




AERODROME CHART

EFF 25 JAN 24

CYPL

AERODROME CHART




AERODROME CHART

EFF 24 MAR 22

CYPM

AERODROME CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 27 JAN 22

CPV7

HELIPORT CHART




HELIPORT CHART

EFF 16 JUL 20

CFA2

AERODROME CHART

				● RADIO Kenora – 122.3		CTR Winnipeg – 135.32	
				● TFC – 122.3		RADIO London – 123.55	
				MF			
DECL DIST	08	26					
TORA	5001	5001					
TODA	5985	5395					
ASDA	5001	5001					
LDA	5001	5001					



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

CYRL


EFF 21 MAR 24

CZRJ-AD

ROUND LAKE (WEAGAMOW LAKE), ON
CZRJ

AERODROME CHART

				TFC - 123.2		ATF			
DECL DIST	03	21							
TORA	3613	3613							
TODA	4597	4597							
ASDA	3613	3613							
LDA	3613	3613							




AERODROME CHART

EFF 20 APR 23

CZRJ

CZRJ-AD

AERODROME CHART




AERODROME CHART

EFF 20 FEB 25

CZPB

AERODROME CHART

AWOS – 124.82				TFC – 122.8		ATF			
DECL DIST	11	29							
TORA	3507	3507							
TODA	3507	3507							
ASDA	3507	3507							
LDA	3507	3507							



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 24 MAR 22

CZSJ

AERODROME CHART

AWOS – 119.12						CTR Toronto – 134.37	
		TFC – 123.0				ATF	
DECL DISTS	06	24	15	33			
TORA	2990	2990	5106	5106			
TODA	3482	3289	6090	5811			
ASDA	2990	2990	5106	5106			
LDA	2990	2990	5106	5106			




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 17 APR 25

CYZR

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART


EFF 31 OCT 24

CYAM

SIOUX LOOKOUT, ON
 CYXL

AERODROME CHART

ATIS – 124.75					RADIO – 122.0		CTR Winnipeg – 132.2 RADIO London – 126.0	
					MF			
DECL DISTS	16	34						
TORA	5300	5300						
TODA	6284	6000						
ASDA	5300	5300						
LDA	5002	5300						



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 16; 34: (¼sm)	NOT AUTHORIZED
TAKE-OFF MINIMA	
Rwys 16; 34: *	


AERODROME CHART

EFF 3 NOV 22

CYXL


CYXL-AD

AERODROME CHART



AERODROME CHART

● ATIS – 128.52				● RADIO – 123.25		CTR Toronto – 133.4 RADIO London – 123.47	
				● TFC – 123.25		● MF	
DECL	DISTS	01	19	06	24	11	29
TORA		2498	2498	5000	5000	1988	1988
TODA		2695	3348	5984	5197	2972	2185
ASDA		2498	2498	5000	5000	1988	1988
LDA		2498	2498	5000	5000	1988	1988



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 12 JUN 25

CYSN

AERODROME CHART

AUTO – 122.55		UNICOM – 122.7					CTR Toronto – 135.3	
							ATF	
DECL	DISTS	03	21	09	27	15	33	
TORA		2607	2607	5013	5013	2610	2610	
TODA		3591	3591	5997	5543	3594	3594	
ASDA		2607	2607	5013	5013	2610	2610	
LDA		2607	2607	5013	5013	2610	2610	




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 21 MAR 24

CYQS

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 25 JAN 24

CYSA

CNM3-HP
STURGEON FALLS (WEST NIPISSING GEN HOSPITAL), ON
CNM3

HELIPORT CHART




HELIPORT CHART

EFF 5 JAN 17

CNM3

CNM3-HP

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 10 AUG 23

CYSB

AERODROME CHART

				TFC – 123.2		ATF	
DECL DIST	17	35					
TORA	3509	3509					
TODA	4493	4009					
ASDA	3509	3509					
LDA	3509	3509					



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

THUNDER BAY, ON
CYQT

ATIS - 128.8

GND - 121.9

TWR - 118.1

RADIO - 118.1

CTR Winnipeg - 119.2

RADIO London - 122.37

DECL DIST

	07	25	12	30				
TORA	7318	7318	5297	5126				
TODA	7702	7468	5797	5126				
ASDA	7318	7318	5297	5126				
LDA	7318	7318	5297	5126				

*** DEPARTURE PROCEDURE**
Refer to DEPARTURE PROCEDURE page.

Taxiway "F" extends for 173' then changes to Apron VII.

CYQT
N48 22.32
W89 19.30

7318 x 148

5297 x 150

305°

ELEV 652

ELEV 653

ELEV 639

AD-AS

AN I

APRON I - Scheduled Commercial Air Carrier by stand assignment only from TBIAAI.

APRON II - Itinerant aircraft parking.
CAUTION: Heli-flood lights 30' AGL N side of Apron II.
Extv bird and wildlife activity in vic of A/D.
Railroad tracks SW of A/D in close proximity

Runway Level of Service

RVO	LVO
RWY 07: RVR 1200 RWY 12, 25, 30: (¼ sm)	NOT AUTHORIZED

TAKE-OFF MINIMA

Rwys 07; 12; 25; 30:*

SCALE IN FEET

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 7 AUG 25

CYQT

CYQT-AD

PARKING AREAS



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

PARKING AREAS

EFF 7 AUG 25

CYQT


PARKING AREAS

Aircraft Parking Position

Position	Coordinates	Position	Coordinates
1B	482217.78N 0891847.56W	3B	482222.20N 0891843.42W
1C	482218.44N 0891847.55W	4	482221.51N 0891841.70W
1D	482217.61N 0891848.07W	4A	482221.84N 0891841.74W
1E	482216.32N 0891848.11W	5	482222.93N 0891840.12W
1F	482217.16N 0891847.16W	6	482224.27N 0891840.57W
1G	482217.34N 0891848.57W	7	482224.68N 0891841.37W
2A	482219.47N 0891846.12W	8	482225.10N 0891842.18W
2B	482220.48N 0891845.78W	10	482219.40N 0891853.46W
3A	482221.25N 0891844.20W		

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART




AERODROME CHART

EFF 7 AUG 25

CYTB

AERODROME CHART

ATIS – 124.95					RADIO – 122.3		CTR Toronto – 128.3	
							MF	
DECL DIST	03	21	10	28				
TORA	6001	6001	4905	4905				
TODA	6601	6985	5889	5889				
ASDA	6001	6001	4905	4905				
LDA	6001	6001	4905	4905				



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 26 DEC 24

CYTS

AERODROME CHART

ATIS – 120.82 133.1		CLNC DEL – 121.3 APRON – 122.27 (N) 122.07 (S) 122.82 GND – 121.9 121.65 119.1 PAD CTL – 131.17 131.95				TWR – 118.35 118.7		DEP – 128.8 127.57		
DECL DIST	05	23	06L	24R	06R	24L	15L	33R	15R	33L
TORA	10775	10775	9697	9589	9000	8898	10886	11050	9088	9078
TODA	10895	11850	10484	10681	9984	10800	12034	12034	10072	10072
ASDA	10775	10775	9697	9589	9000	8898	10886	11050	9088	9078
LDA	10640	10089	9697	9392	9000	8898	10886	11050	8500	8490



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART (HIGH INTENSITY RUNWAY OPERATIONS – HIRO)

LDA for High Intensity Runway Operations				
From threshold rwy:	To exit point	LDA in ft	Preferred exit for med/heavy jet transport	Preferred exit for prop/turboprop transport
05	15R F P H3 15L B	5030 5630 6570 6670 8536 9278	H3	H3
06L	C1 C3	4790 6797	C3	C1
06R	D1 D3 D5	4424 5682 7483	D3 D5	D1
15L	B4 R S B1 B3	4050 5118 6154 6500 8250	B1 B3	B1
15R	F1	6276	F1	F1
23	H3 P F 15R H2 H4 J2	3427 3516 4449 5064 5176 6593 7577	H2 H4	H2
24L	D2 D4 D8	4061 5682 7883	D4 D8	D2
24R	C2 C4	5090 6984	C2 C4	C2
33L	F2 F4 H 05	4860 6060 6680 7424	F2 F4	F2
33R	B3 B1 S/B2 R B4 H 23	2805 4550 4895 5920 6994 9160 9900	B2 B4	B2

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART (REDUCED TAKE-OFF RUNS)

When authorized by ATC, intersection departures are available as follows:


RUNWAY	INTERSECTION	RUNWAY REMAINING
05	J2	8120
	H4	7129
	H6	10512
06L	D4	7763
	C4	7182
06R	D8	7883
	D4	5682
	Y	4401
15L	H	8996
	N	7766
	B4	6841
15R	H	7270
	F4	6633
23	H/J	10246
	B	9058
24L	D5	7381
	Y	4753
	W	6567
24R	D5	7973
	C3	6693
33L	F1	6854
33R	V	10669
	T	9219
	B3	8251

Departures from holding bay inner centerlines rwy 06L/D6, 24R/C5 and 05/H6
subtract 263' from declared distances.

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

ADVISORY CHART

ATIS - 120.82 133.1	CLNC DEL - 121.3 APRON - 122.27 (N) 122.07 (S) 122.82 GND - 121.9 121.65 119.1 PAD CTL - 131.17 131.95	TWR - 118.35 118.7
---------------------	---	--------------------



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

TAXI CHART

Notes

Twy "K" is uncontrolled and is restricted to aircraft with wingspans of 41.15m/135ft (B757W) or less and an Aircraft Load Rating of 9.0 or less. Other aircraft may be authorized with prior approval from operator (416) 776-3056.

Discretionary oversteering required for aircraft with wingspans 38m/124ft (B757) or greater:

- Rwy 06L onto "E", "D3" and "D5".
- Rwy 24R onto "D3", "E", "D4" and "D10/D8 southbound".

A340-500/600, A350-900/1000, B777-300, and A380 discretionary oversteering required at all intersections.

Specific aircraft operations plan in effect for aircraft with wingspans 65m/214ft up to 79.9m/262ft. Restrictions in place include;

- No holding short of Runway 06L/24R after exit from Runway 06R/24L.
- Aircraft (as defined above) operations on any parallel taxiway system, such as Alpha-Bravo, Charlie-Delta, or Delta-Victor (Alpha to Echo), restrict operations on adjacent taxiway to aircraft with wingspans less than 36m.
- Strict adherence to taxiway centre line is required all times.
- Discretionary oversteering is required at all intersections.
- No taxiing on apron taxi lane between AJ and AK (between gates C31-C34).
- No taxiing on apron taxi lane between AJ and AT (between gates B15-B18).
- No turns from twy E onto CDF Pads 1 through 6.
- When aircraft on taxilane 5S, strict adherence to centreline. Taxilane 5 between 5A and 5D closed. Taxilane 6 between 6A and 6C closed, remainder of taxilane 6 restricted to aircraft with wingspan less than 36m/118'. Simultaneous use of taxilane 7 & 8, max span 64.9m/213'.
- No taxiing on twy D between twy D4 and twy E.
- No taxiing on twy B between rwy 05/23 and twy J.
- When aircraft taxiing within Holding Bays rwys 06L/24R/05, adjacent parallel taxilane restricted to aircraft with wingspans less than 36m.
- Tow only authorized onto parking stands H1 and H10.

While taxiing on twy V (Pad 1) and twy T (Pad 5) through the CDF strict adherence to the centreline is required. When in contact with ATC use Centre Lane. When in contact with Pad Control or Iceman, use assigned Lane. Pad 1 (twy V) and Pad 5 (twy T) Centre Lane will accommodate aircraft with wingspans 79.9m/261ft and smaller. Aircraft with wingspans less than 36m may use North/South Lanes.

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

TAXI CHART

Hot Spots

Note: HS 4 to 8 - Short distance between parallel runways. Manage your taxi speed. Expect to hold short of parallel runway.

HS 1 – Taxiing northbound on rwy 33R aircraft fail to hold short of and incur on rwy 05/23.

HS 2 – Taxiing northbound on twy B aircraft miss turn onto twy H and incur on rwy 05/23.

HS 3 – Taxiing eastbound on twy H aircraft continue onto twy Q and incur on rwy 23.

HS 4 – Exiting rwy 24L onto twy D8 aircraft fail to hold short of and incur on rwy 06L/24R.

HS 5 – Exiting rwy 24L onto twy D4 aircraft fail to hold short of and incur on rwy 06L/24R.

Note: Angled rwy hold position in effect on twy D4 south of rwy 06L/24R.

HS 6 – Exiting rwy 06R onto twy D3 aircraft fail to hold short of and incur on rwy 06L/24R.

HS 7 – Exiting rwy 06R onto twy D5 aircraft fail to hold short of and incur on rwy 06L/24R.


Note: Angled rwy hold position in effect on twy D5 south of rwy 06L/24R.

HS 8 – Taxiing southbound on twy D7 aircraft fail to hold short of the 24L approach hold line and incur on rwy 06R/24L.

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

TAXI CHART

ATIS - 120.82 133.1	CLNC DEL - 121.3 APRON - 122.27 (N) 122.07 (S) 122.82 GND - 121.9 121.65 119.1 PAD CTL - 131.17 131.95	TWR - 118.35 118.7
---------------------	---	--------------------



LOW VISIBILITY PROCEDURES

Low Visibility Procedures (RVR less than 1200 to 600 ft)

Application

These procedures apply to ground movements of aircraft arriving and departing under low visibility conditions. Arrivals and departures below RVR 600 are not authorized. When weather conditions indicate visibility below RVR 1200 is imminent, procedures will be implemented restricting aircraft and vehicle operations on the movement area. The following message will be added to the ATIS broadcast:

“LOW VISIBILITY PROCEDURES IN EFFECT”

General

Low Visibility Taxi Routes

Typical taxi routes are shown on the Low Visibility Taxi Charts. Taxiway surfaces are painted with enhanced yellow and black centerline markings. In addition, taxiways A, C, F, H, J, N, T, P, R, S, V, E, D, B, T1, and T3 aprons are equipped with green centreline lights. Yellow in-set taxiway intersection lights that consist of three lights spaced 1.5 meters apart at 90 degrees to the direction of travel are located at taxiway/taxiway intersections and apron entry/exit points coincident with lighted locations signs. Aircraft may be directed to hold or report by any of these positions.

Airport Surface Detection Equipment (ASDE)

Ground radar is used to monitor the position of aircraft operating on the manoeuvring area. In the event of an ASDE failure, ATC may suspend, restrict or terminate low visibility operations.

Departures

When low visibility procedures are in effect the Departure runways are 05, 06L and 33R. Intersection take-offs from 06L are not authorized. Intersection take-offs on 33R from Victor Taxiway and on 05 from H6 may be assigned by ATC.

Sequencing of Aircraft Ground Movements for Take-off

Do not request start, push back or call for taxi clearance until the reported RVR is greater than:

Aircraft/Pilot Take-off Minima

1200 RVR
600 RVR

Minimum RVR for Start

1000 RVR
600 RVR

Stop Bar/Guard Light system

Each taxiway entrance onto runways 05, 06L and 33R is equipped with a stop bar consisting of red in-set lights and red elevated lights located at the taxi holding position. Yellow flashing runway guard lights (wig-wags) are installed at each end of the stop bar. When the red stop bar lights are illuminated, green lead on lights beyond the stop bar are extinguished. When ATC issues a clearance to proceed onto the runway, the red stop bar lights will be extinguished and the green lead on lights beyond the stop bar will be illuminated. The stop bar is reset automatically as the aircraft moves onto the runway.

“AT NO TIME SHALL A PILOT CROSS AN ILLUMINATED RED STOP BAR”

Arrivals


When low visibility procedures are in effect the Arrival runways are 05 and 06L. For 05, approved exits are Taxiways F (northbound), H3, B, H/J and Q. For 06L, approved exits are Taxiways C1, C3 and C7. Aircraft exiting either runway must proceed beyond the alternating green and yellow centreline lights to ensure the aircraft is clear of the runway and the ILS sensitive area.

LOW VISIBILITY TAXI CHART

LAND RWY 05, DEPART RWY 05 (RVR LESS THAN 1200 TO 600 FT)

TORONTO/LESTER B. PEARSON INTL, ON

CYYZ



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

LAND RWY 05, DEPART RWY 05 (RVR LESS THAN 1200 TO 600 FT)

LOW VISIBILITY TAXI CHART

CYYZ


EFF 16 MAY 24

LOW VISIBILITY TAXI CHART

LAND RWY 06L, DEPART RWY 06L (RVR LESS THAN 1200 TO 600 FT)

TORONTO/LESTER B. PEARSON INTL, ON

CYYZ



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

LAND RWY 06L, DEPART RWY 06L (RVR LESS THAN 1200 TO 600 FT)

LOW VISIBILITY TAXI CHART

CYYZ


EFF 16 MAY 24

LOW VISIBILITY TAXI CHART

LAND RWY 06L, DEPART RWY 33R (RVR LESS THAN 1200 TO 600 FT)

TORONTO/LESTER B. PEARSON INTL, ON

CYYZ



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

LAND RWY 06L, DEPART RWY 33R (RVR LESS THAN 1200 TO 600 FT)

LOW VISIBILITY TAXI CHART

CYYZ

EFF 16 MAY 24

DE-ICING OPERATIONS

CENTRAL DE-ICING FACILITY (CDF)

Overview

All de-icing ops are performed with acft engines oprg, unless otherwise advised by Pad Control or ICEMAN.

Pad 1 & 5

- Centre lane will accommodate all acft.
- Acft with wingspans less than 36m may use North/South lanes.

Pad 2, 3, 4 & 6

- Centre lanes will accommodate acft with wingspans 64.9m/213ft and smaller.
 - Acft with wingspans less than 36m may use North/South lanes.
1. Prior to departing Parking Position, ctc CLNC DEL/APRON/GND (as applicable) and advise, "ACFT DE-ICING REQUIRED".
 2. On twys T, V and E, hold short of ICE# and when directed by Ground Control monitor Pad Control on 131.17. Follow Pad Control taxi instructions to the entrance of the de-icing pad.
 3. When directed by Pad Control, ctc ICEMAN on the assigned freq. (129.62 or 131.37).
 4. Follow verbal instructions, guidance displays and lights (as applicable) into staging and/or de-icing bays.
 5. Once aircraft is in final stop position, brakes are set and aircraft configured for de-icing, ctc ICEMAN and advise, "BRAKES SET, ACFT CONFIGURED, READY TO DE-ICE". At this time, pass along any specific fluid and/or treatment requirements.
 6. After de-icing, do not move aircraft. Ctc Pad Control on 131.17 when instructed by ICEMAN to obtain taxi instruction.
 7. Follow Pad Control instruction designated exit points. When instructed by Pad Control ctc Ground Control on assigned freq.
 8. Specific aircraft operations plan in effect for aircraft with wingspans 65m/214ft up to 79.9m/262ft. Restrictions in place include:
 - For Central De-icing Facility (CDF) operations, no turns from twy E into any of the de-icing pads are permitted. The only taxi routes permitted for de-icing are via twy T into Pad 5 and via twy V into Pad 1.


Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

DE-ICING OPERATIONS

EFF 24 MAR 22

CYYZ

CENTRAL DE-ICING FACILITY



CENTRAL DE-ICING FACILITY

EFF 24 MAR 22

CYYZ

ENGINE FAN BLADE ICE SHEDDING PROCEDURES

The completion of aircraft engine run-up for engine fan blade ice shedding must be conducted on taxiways. Strict adherence to the centerline is mandatory during engine fan blade ice shedding. Proper coordination with air traffic control (ATC) (clearance delivery or ground) is required.


On initial contact with Clearance Delivery (121.3 MHz), flight crews shall advise:

- De-icing requirements
- Run-up requirement prior to take-off
- Duration of run-up (if required)

Should taxiway surface conditions make engine run-up unsafe, flight crews shall coordinate with ATC to have the run-up conducted at the takeoff position.

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


PARKING AREAS (TERMINAL 1)



PARKING AREAS (TERMINAL 1)

EFF 20 APR 23

PARKING AREAS (TERMINAL 1 EAST HOLD)



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

PARKING AREAS (TERMINAL 1 EAST HOLD)

EFF 5 SEP 24

CYYZ



CYYZ-APD-3

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

TAXILANE LIMITATIONS

Taxilane	Taxilane Segment	Acft Code/ Limitation	Max Wingspan	Comments
Pier A North	Between AG and Gate A1A	DH8-400	28.4m/93'	
1	Between AT & Stand B8	C	36m/118'	
	Between Stand B8 & Stand B7D	DH8-400	28.4m/93'	
1S	Between AT and Hangar	E	65m/213'	
2	Between AT and Hangar	D	51.9m/170'	
2	Between 2C & Stand B8	C	36m/118'	
1 / 2	1B/2B Radius	C	36m/118'	
3	Between AJ & 3B	E	65m/213'	
	Between 3B & 3C	C	36m/118'	Code E to Stand C29 & C27
4	Between AJ & 4B	E	65m/213'	
	Between 4B & 4C	C	36m/118'	Code E to Stand C29 & C27
3 / 4	3B/4B Radius	D	51.9m/170'	
	3C/4C Radius	C	36m/118'	
N/S	Between AT & AK	E	65m/213'	
5	Between AK & 5E	E	65m/213'	AK to 5D closed when Lane 5S in use.
	Between 5E & 5G	D	51.9m/170'	
5S	Between AK & Stand C35	F	79.9m/262'	A380 only. Strict Adherence to C/L. Closes Lane 5A-5D. Lane 6 between 6A and 6C closed, remainder of Lane 6 restricted to Code C or smaller.
5-6	Crossover	E	65m/213'	Closed when Lane 5S in use
6	Between AK & 6C	E	65m/213'	Code E allowed to Stand 124. AK to 6C closed when Lane 5S in use.
	Between 6C & 6D	C	36m/118'	Code E allowed to Stand 124. No code E push tail East onto Lane 6 from Stand 124.
	Between 6D & 6F	C	36m/118'	
	Between 6F & Stand 101	DH8-400	28.4m/93'	
5 / 6	5C/6C Radius	E	65m/213'	No B777 due to Jet Blast
	5G/6F Radius	C	36m/118'	
7	Between AL & 7D	F	79.9m/262'	Simultaneous use of lane 7 & 8, Max span 64.9m/213', Code E
	Between 7D & 7E	C	36m/118'	Code D allowed to stand 151
8	Between AL & 8D	F	79.9m/262'	Simultaneous use of lane 7 & 8, Max span 64.9m/213', Code E
	Between 8D & 8E	C	36m/118'	
7 / 8	7D/8D Radius	F	79.9m/262'	
	7E/8E Radius	C	36m/118'	
7S	Between 7C & 7S	E	65m/213'	
	Between 8C & 7S	E	65m/213'	
	Between 7S & 151	E	65m/213'	No 77W/773, Closes Taxilane 7 & 8 beyond 7C/8C.
	Between 7S & 161A	E	65m/213'	Closes Taxilane 7 & 8 beyond 7C/8C.
N/S	Between AK & AM	F	79.9m/262'	
9	Between DR & 9C	E	65m/213'	
	Between 9C & 9D	C	36m/118'	

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

TAXILANE LIMITATIONS

EFF 7 AUG 25


CYYZ

TAXILANE LIMITATIONS

Taxilane	Taxilane Segment	Acft Code/ Limitation	Max Wingspan	Comments
10	Between DR & 10D	C	36m/118'	
9 / 10	9C/10C Radius	C	36m/118'	
	9D/10D Radius	C	36m/118'	
E/W	Between AM & DV	F	79.9m/262'	Strict adherence to C/L
11	Between DT & H4	E	65m/213'	Strict adherence to C/L
12	Between H1/H10 & H4	E	65m/213'	Strict adherence to C/L
E/W	Between DV & H12B	E	65m/213'	
E/W/N/S	Between H12B & H18	E	65m/213'	Tow Operations Only


Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

CYYZ



CYYZ

PARKING AREAS (FEDEX)





Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

PARKING AREAS (FEDEX)

CYYZ

COMMUTER PARKING AREAS



COMMUTER PARKING AREAS

EFF 5 SEP 24

CYYZ

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

TORONTO/OSHAWA EXECUTIVE AIRPORT, ON
CYOO

AERODROME CHART

CY00

TORA FOR INTERSECTION DEPARTURES		
RWY	INTXN	TORA In ft
12	B	4447
30	B	4175

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 12 JUN 25

CY00

CYOO-AD

AERODROME CHART (DND)




AERODROME CHART (DND)

EFF 5 OCT 23

CYTR

PARKING AREAS (DND)




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

PARKING AREAS (DND)


EFF 2 OCT 25

AERODROME CHART



AERODROME CHART

				TFC – 122.8		ATF			
DECL DIST	02	20							
TORA	3525	3525							
TODA	4509	4509							
ASDA	3525	3525							
LDA	3525	3525							




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 17 APR 25

CYVV


MF

CYVV

CYVV-AD

AERODROME CHART

● ATIS – 134.5		● GND – 121.7		● TWR – 124.7		● TFC – 124.7		● MF*		ARR Detroit – 118.95 132.35 134.3 284.0 RADIO London – 123.37	
DECL	DISTS	07	25	12	30						
TORA		9000	9000	5150	5150						
TODA		9984	9330	5445	5445						
ASDA		9000	9000	5150	5150						
LDA		8098	7857	4580	4829						



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 07, 25: RVR 1200 (1/4sm)	NOT AUTHORIZED
TAKE-OFF MINIMA	
All Rwys: *	




AERODROME CHART

CYQG

AERODROME CHART

				TFC – 123.2		ATF			
DECL DIST	16	34							
TORA	3511	3511							
TODA	3511	3511							
ASDA	3511	3511							
LDA	3511	3511							




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 27 JAN 22

CKL3


AERODROME CHART



AERODROME CHART

CYKO

CARTE D'AÉRODROME



CARTE D'AÉRODROME


EFF 20 AVR 23

CYKO

ALMA, QC
CYTF

AERODROME CHART

AUTO – 123.17				☉ UNICOM – 122.35 ☉ TFC – 122.35		TML Bagotville – 127.2	
DECL DIST	13	31					
TORA	5000	5000					
TODA	5000	5000					
ASDA	5000	5000					
LDA	5000	5000					



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 14 JUL 22

CYTF

CYTF-AD

CARTE D'AÉRODROME




Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

CARTE D'AÉRODROME

EFF 14 JUIL 22

CYTF


AERODROME CHART



AERODROME CHART

CYEE

CARTE D'AÉRODROME




CARTE D'AÉRODROME

EFF 20 FÉV 25

CYEEY

AERODROME CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 7 OCT 21

CYLA

CARTE D'AÉRODROME




CARTE D'AÉRODROME

CYLA

AERODROME CHART (DND)

ATIS – 124.2 (En) 125.8 (Fr) 302.5		CLNC DEL – 119.0 384.5 GND – 121.7 275.8		TWR – 126.2 337.7		TML – 127.2 227.6	
DECL DISTS	11	29	18	36			
TORA	10000	10000	6029	6029			
TODA	10000	10000	6029	6029			
ASDA	10200	10200	6029	6029			
LDA	10000	10000	6029	6029			



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART (DND)

EFF 16 MAY 24

CYBG

CARTE D'AÉRODROME

ATIS – 125.8 (Fr) 124.2 (Ang) 302.5		CLNC DEL – 119.0 384.5 GND – 121.7 275.8		TWR – 126.2 337.7		TML – 127.2 227.6	
DIST DÉCLARÉES	11	29	18	36			
TORA	10000	10000	6029	6029			
TODA	10000	10000	6029	6029			
ASDA	10200	10200	6029	6029			
LDA	10000	10000	6029	6029			




CARTE D'AÉRODROME

EFF 16 MAI 24

CYBG

AERODROME CHART

AWOS – 125.85 (En) 128.15 (Fr)		RADIO Mont-Joli – 118.3				CTR Montreal – 134.65 227.2	
		MF					
DECL DIST	10	28					
TORA	6000	6000					
TODA	6984	6984					
ASDA	6000	6000					
LDA	6000	6000					



★ DEPARTURE PROCEDURE

Rwy 10 - ½ - To remain clear of CYA643 when active, flight between "YBC" **R-028** CCW to **R-263** beyond 17 DME prohibited below **7000**.
To remain clear of CYR630 when active, flight between "YBC" **R-028** CCW to **R-263** beyond 17 DME prohibited.
Note: Trees to 115 ASL aprx 0.2 NM past departure end of rwy, 750' LEFT and RIGHT of rwy centreline.

Rwy 28 - ½ - NO RIGHT turn below **600**.
To remain clear of CYA643 when active, flight between "YBC" **R-263** CW to **R-028** beyond 17 DME prohibited below **7000**.
To remain clear of CYR630 when active, flight between "YBC" **R-263** CW to **R-028** beyond 17 DME prohibited.
Note: Trees to 112 ASL aprx 0.1 NM past departure end of rwy, 690' LEFT of rwy centreline.


Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 15 JUN 23

CYBC

CARTE D'AÉRODROME




CARTE D'AÉRODROME

EFF 15 JUIN 23

CYBC

AERODROME CHART

AUTO – 122.05		UNICOM – 123.0 (AU)				RADIO Quebec – 123.55 DRCO			
						MF			
DECL	DISTS	13	31						
TORA		5983	5983						
TODA		5983	5983						
ASDA		5983	5983						
LDA		5983	5983						



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART


EFF 7 AUG 25

CYVB


CYVB



AUTO – 122.97				UNICOM – 122.15 (AU)		CTR Montreal – 132.35	
						MF	
DECL DIST	05	23					
TORA	5004	5004					
TODA	5004	5988					
ASDA	5004	5004					
LDA	5004	5004					



CARTE D'AÉRODROME



Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

CARTE D'AÉRODROME


EFF 12 AOÛT 21

CZBM

CHARLEVOIX, QC
CYML

AERODROME CHART

AUTO – 122.55 (En)					UNICOM – 123.0		CTR Montreal – 125.1 299.6	
					ATF			
DECL DISTS	14	32						
TORA	4501	4501						
TODA	5485	4501						
ASDA	4501	4501						
LDA	4501	4501						



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 29 DEC 22

CYML

CYML-AD

CARTE D'AÉRODROME




CARTE D'AÉRODROME

EFF 29 DÉC 22

CYML

AERODROME CHART

AUTO – 122.55 (En)				TFC – 123.5		ATF*			
DECL DIST	07	25							
TORA	4500	4500							
TODA	4500	4500							
ASDA	4500	4500							
LDA	4500	4500							




AERODROME CHART

EFF 16 MAY 24

CYHR

CARTE D'AÉRODROME




Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

CARTE D'AÉRODROME

CYHR

EFF 16 MAI 24

AERODROME CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 14 JUL 22

CYMT

CARTE D'AÉRODROME



Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés


CARTE D'AÉRODROME

EFF 14 JUIL 22

CYMT

AERODROME CHART

ATIS – 134.8 (En) 124.95 (Fr)		GND – 121.9		TWR – 118.4		TFC – 118.4		ATF*		TML Bagotville – 127.2 227.6	
DECL DISTS	06	24	12	30	18	36					
TORA	3735	3735	6085	6085	3597	3597					
TODA	4719	4719	6436	6085	4581	4581					
ASDA	3735	3735	6085	6085	3597	3597					
LDA	3735	3735	6085	6085	3597	3597					



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 25 JAN 24

CYRC

CARTE D'AÉRODROME

ATIS – 124.95 (Fr) 134.8 (Ang)		GND – 121.9		TWR – 118.4		TMC Bagotville – 127.2 227.6	
				TFC – 118.4		ATF*	
DIST DÉCLARÉES	06	24	12	30	18	36	
TORA	3735	3735	6085	6085	3597	3597	
TODA	4719	4719	6436	6085	4581	4581	
ASDA	3735	3735	6085	6085	3597	3597	
LDA	3735	3735	6085	6085	3597	3597	




CARTE D'AÉRODROME

EFF 25 JAN 24

AERODROME CHART

AUTO – 122.17				TFC – 123.2		MF*			
DECL DIST	14	32							
TORA	3789	3789							
TODA	3789	3789							
ASDA	3789	3789							
LDA	3789	3789							




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 17 JUN 21

CSU2

CARTE D'AÉRODROME



Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés


CARTE D'AÉRODROME

EFF 17 JUIN 21

CSU2

AERODROME CHART

AUTO – 122.55				UNICOM – 122.8		CTR Montreal – 132.35	
						MF	
DECL	DISTS	06	24				
TORA		6003	6003				
TODA		6003	6003				
ASDA		6003	6003				
LDA		6003	6003				



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 25 JAN 24

CSC3

CSC3

TAUX DE MONTÉE DE DÉPART V/V (FPM)

VITESSE SOL	90	120	140	160	180	200	250	300
210 pieds/NM	320	420	490	560	630	700	880	1050

PROCÉDURE DE DÉPART


Piste 06 - 1/2 -
Lorsque CYR606 est active: Monter entre caps **008°** et **308°** sens horaire pour demeurer à l'écart de CYR606.
Note: Arbres et ligne électrique jusqu'à 413 ASL aprx 0.1 NM passé l'extrémité de la piste de départ. Ligne électrique jusqu'à 483 ASL aprx 0.6 NM passé l'extrémité de la piste de départ.

Piste 24 - 1/2 - Requiert une pente de montée minimale de **210 pi/NM** jusqu'à **1000**. Monter sur cap **236°** jusqu'à **1000** BPOC. Lorsque CYR 606 est actif: Monter entre caps **308°** et **008°** sens antihoraire pour demeurer à l'écart de CYR606.
Note: Arbres jusqu'à 452 ASL par le travers de l'extrémité de la piste de départ, 450' à GAUCHE et à DROITE de l'axe de piste, et aprx 0.4 NM passé l'extrémité de la piste de départ.
ou
SPEC VIS - Effectuer une montée à vue pour survoler l'aéroport à **2000** ou plus haut BPOC.

Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

AERODROME CHART

AUTO – 122.97				UNICOM – 122.35 (AU)		CTR Montreal – 134.17 RADIO Quebec – 123.47	
DECL DIST		08	26				
TORA		4982	4982				
TODA		4982	4982				
ASDA		4982	4982				
LDA		4982	4982				



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART


EFF 17 APR 25

CTG3

DU ROCHER-PERCÉ (PABOK), QC
CTG3

CARTE D'AÉRODROME

AUTO – 122.97					 UNICOM – 122.35 (AU)		CTR Montreal – 134.17 RADIO Quebec – 123.47	
					ATF			
DIST DÉCLARÉES	08	26						
TORA	4982	4982						
TODA	4982	4982						
ASDA	4982	4982						
LDA	4982	4982						



Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

CARTE D'AÉRODROME

EFF 17 AVR 25

CTG3


CTG3-AD



CZEM-AD

EASTMAIN RIVER, QC
CZEM

				APRT RADIO – 122.1 TFC – 122.1		MF*			
DECL	DISTS	02	20						
TORA		3512	3512						
TODA		3512	3512						
ASDA		3512	3512						
LDA		3512	3512						



AERODROME CHART

CZEM

EFF 5 SEP 24

CZEM-AD

CARTE D'AÉRODROME

78 31.5 78 31.2

52 13.8 52 13.4 52 13.0

78 31.5 78 31.2

ALT 24 02 AS

199°

★

ALT 21 02 AS

019°

3512 x 100

gravier

CZEM
N52 13.58
W78 31.36

VARIATION
ANNUELLE DE 5° E

DEC 15 N
2013

MINIMUM DE DÉCOLLAGE

Pistes 02, 20: ★


ÉCHELLE EN PIEDS

1000 500 0 1000

Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

AERODROME CHART

AUTO – 122.55				TFC – 123.2		MF*	
DECL DIST	09	27					
TORA	3930	3930					
TODA	3930	3930					
ASDA	3930	3930					
LDA	3737	3736					



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 30 NOV 23

CEL8

CARTE D'AÉRODROME


AUTO – 122.55				TFC – 123.2		MF*			
DIST DÉCLARÉES	09	27							
TORA	3930	3930							
TODA	3930	3930							
ASDA	3930	3930							
LDA	3737	3736							



Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

AERODROME CHART

AUTO – 122.17				UNICOM – 123.0 (AU)		MF*	
DECL DIST	09	27					
TORA	4890	4890					
TODA	4890	4890					
ASDA	4890	4890					
LDA	4890	4890					



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 20 FEB 25

CTU2

CARTE D'AÉRODROME

AUTO – 122.17		UNICOM – 123.0 (AU)				MF*			
DIST DÉCLARÉES	09	27							
TORA	4890	4890							
TODA	4890	4890							
ASDA	4890	4890							
LDA	4890	4890							




CARTE D'AÉRODROME

CTU2

AERODROME CHART

AUTO – 127.8 (En) 124.9 (Fr)		GND – 123.02		RADIO Mont-Joli – 122.3		CTR Montreal – 134.17 RADIO Quebec – 123.47	
DECL DIST		10	28				
TORA	5488	5488					
TODA	5980	5980					
ASDA	5488	5488					
LDA	5488	5488					




AERODROME CHART

EFF 11 JUL 24

CYGP

CARTE D'AÉRODROME




Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

CARTE D'AÉRODROME

EFF 11 JUIL 24

AERODROME CHART

AWOS – 125.95 (En) 128.3 (Fr)				● RADIO Madeleine – 122.0			
				● TFC – 122.0		MF*	
DECL DIST	08	26					
TORA	4498	4498					
TODA	5098	5098					
ASDA	4498	4498					
LDA	4498	4498					




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 21 MAR 24

CYGV

HELIPORT CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


HELIPORT CHART

EFF 12 JUN 25

CIO2

CARTE D'HÉLIPORT

		UNICOM – 122.7				MF*			
DIST DÉCLARÉES									
TORA									
TODA									
ASDA									
LDA									




Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

CARTE D'HÉLIPORT


EFF 12 JUIN 25

CIO2

CARTE D'AÉRODROME



AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 25 FEB 21

CYGR

CYGR

*** PROCÉDURE DE DÉPART**

Piste 07 - ½
Note: Arbres et route jusqu'à 30 ASL à l'intérieur de 0,1 NM passé l'extrémité de la piste de départ.

Piste 16 - ½ - Requier une pente de montée minimale de **370pi/NM** jusqu'à **400**.
Note: Terrain jusqu'à 66 ASL par le travers de l'extrémité de la piste de départ, 350' à DROITE de l'axe de piste et aprx 200' passé l'extrémité de la piste de départ.

ou

SPEC VIS - Effectuer une montée à vue pour survoler l'aéroport à **700** ou plus haut BPOC.

Piste 25 - ½
Note: Arbres jusqu'à 60 ASL à l'intérieur de 0,2 NM passé l'extrémité de la piste de départ. Arbres jusqu'à 174 ASL aprx 0,6 NM passé l'extrémité de la piste de départ, 1400' à GAUCHE de l'axe de piste.

Piste 34 - ½
Note: Terrain jusqu'à 17 ASL à l'intérieur de 0,1 NM passé l'extrémité de la piste de départ.


TAUX DE MONTÉE DE DÉPART VV (FPM)

VITESSE SOL	90	120	140	160	180	200	250	300
370 pieds/NM	560	740	870	990	1110	1240	1550	1850

CARTE D'AÉRODROME CYGR
EFF 25 FÉV 21

AERODROME CHART

AWOS – 125.3 (En) 127.7 (Fr)		UNICOM – 122.1 TFC – 122.1				RADIO Quebec – 123.55			
		MF							
DECL DIST	06	24							
TORA	3520	3520							
TODA	3520	3520							
ASDA	3520	3520							
LDA	3520	3520							




AERODROME CHART

EFF 7 AUG 25

CYPH

CARTE D'AÉRODROME




Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

CARTE D'AÉRODROME

EFF 7 AOÛT 25

CYPH

AERODROME CHART




AERODROME CHART

EFF 20 APR 23

CYIK

CARTE D'AÉRODROME




Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

CYLU-AD

KANGIQSUALUJJUAQ (GEORGES RIVER), QC
CYLU

AERODROME CHART

				APRT RADIO – 122.1 TFC – 122.1		MF*			
DECL DIST	16	34							
TORA	3521	3521							
TODA	3521	3521							
ASDA	3521	3521							
LDA	3521	3521							



AERODROME CHART

EFF 10 SEP 20


CYLU

CYLU-AD

CYLU-AD

KANGIQSUALUJJUAQ (GEORGES RIVER), QC
CYLU

CARTE D'AÉRODROME



Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

CARTE D'AÉRODROME

EFF 10 SEP 20


CYLU

CYLU-AD

CYKG-AD

KANGIQSUJUAQ (WAKEHAM BAY), QC
CYKG

				APRT RADIO – 122.1 TFC – 122.1		RADIO Quebec – 123.47 DRCO	
				MF*			
DECL DISTS	14	32					
TORA	3520	3520					
TODA	3520	3520					
ASDA	3520	3520					
LDA	3520	3520					



AERODROME CHART


EFF 7 AUG 25

CYKG

CYKG-AD

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

CARTE D'AÉRODROME




CARTE D'AÉRODROME

EFF 7 AOÛT 25

CYKG

AERODROME CHART




AERODROME CHART


CYAS

EFF 15 JUN 23

CARTE D'AÉRODROME



				UNICOM – 122.8 (AU)		MF*			
DECL DIST	10	28							
TORA	6500	6500							
TODA	6500	6500							
ASDA	6500	6500							
LDA	6500	6500							




AERODROME CHART

CTP9

EFF 16 MAY 24

CARTE D'AÉRODROME




CARTE D'AÉRODROME

EFF 16 MAI 24

CTP9

CYVP

RADIO Quebec – 123.27 5680



CYVP


CYVP



CYVP

AERODROME CHART

AWOS – 124.35 (En) 125.15 (Fr)				RADIO La Grande – 122.2		RADIO Quebec – 123.47	
				MF*			
DECL DIST	03	21					
TORA	5082	5082					
TODA	6066	6066					
ASDA	5082	5082					
LDA	5082	5082					




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 16 MAY 24

CYGW

CARTE D'AÉRODROME



77 46.2

77 45.5

55 17.3

55 16.9

55 16.5

DEC 15° W
2024

VARIATION
ANNUELLE DE 11° E

ALT 33

ALT 39

40°

213°

033°

monte 0.4% premiers 2960'

Gravier

5082 x 150

CYGW

N55 16.92

W77 45.92

150' ASL

340

★PROCÉDURE DE DÉPART

Piste 03 - ½ - AUCUN virage à DROITE en dessous de **1300**.
Note: Arbres jusqu'à 75 ASL aprx 0.2 NM passé l'extrémité de la piste de départ 600' à DROITE de l'axe de piste.

Piste 21 - ½ - Requiert une pente de montée minimale de **360** pi/NM jusqu'à **300**. Monter sur cap **213°** jusqu'à **900** BPOC.
Note: Bâtiment jusqu'à 68 ASL aprx 500' passé l'extrémité de la piste de départ, 600' à GAUCHE de l'axe de piste. Arbres jusqu'à 190 ASL aprx 0.6 NM passé l'extrémité de la piste de départ, à GAUCHE et à DROITE de l'axe de piste.

ou
SPEC VIS - Effectuer une montée à vue pour survoler l'aéroport à **1500** ou plus haut BPOC.

TAUX DE MONTÉE DE DÉPART V/V (FPM)

VITESSE SOL	90	120	140	160	180	200	250	300
360 FT/NM	540	720	840	960	1080	1200	1500	1800

MINIMUM DE DÉCOLLAGE

Pistes 03; 21: ★

ÉCHELLE EN PIEDS

1000 0 1000


Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

CARTE D'AÉRODROME

EFF 16 MAI 24

CYGW

AERODROME CHART




AERODROME CHART

EFF 5 SEP 24

CYGL


CARTE D'AÉRODROME



CARTE D'AÉRODROME

CYGL


PARKING AREAS



PARKING AREAS

EFF 7 AUG 25

AIRES DE STATIONNEMENT




Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

AIRES DE STATIONNEMENT

EFF 7 AOÛT 25

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 20 FEB 25

CYAD

CYAD

VARIATION ANNUELLE DE 8° E

ALT 775

104°

Descend 0.56%

5009 x 150

gravier

CYAD
N53 34.31
W76 11.78

ALT 747

284°

AS

★ PROCÉDURE DE DÉPART

Piste 10 - 1/2
Note: Arbres jusqu'à 791 ASL par le travers de l'extrémité de la piste de départ, 300' à GAUCHE et à DROITE de l'axe de piste.

Piste 28 - 1/2
Note: Arbres jusqu'à 787 ASL par le travers de l'extrémité de la piste de départ, 200' à GAUCHE et 300' à DROITE de l'axe de piste.

MINIMUM DE DÉCOLLAGE

Pistes 10, 28: ★


ÉCHELLE EN PIEDS

1000 0 1000


Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

AERODROME CHART

AWOS – 118.45 (En) 119.65 (Fr)		UNICOM – 131.2 (AU)				RADIO Quebec – 123.55		
DECL DIST	09	27						
TORA	5009	5009						
TODA	5993	5993						
ASDA	5009	5009						
LDA	5009	5009						



CARTE D'AÉRODROME




CARTE D'AÉRODROME


EFF 30 NOV 23

CYAH

AERODROME CHART



CARTE D'AÉRODROME



Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés


CARTE D'AÉRODROME

EFF 5 OCT 23

CYFJ

AERODROME CHART

AWOS Natashquan – 126.25 (En) 125.3 (Fr)				UNICOM – 123.5 (AU) (Fr)			
				ATF*			
DECL DIST	11	29					
TORA	3933	3933					
TODA	3933	3933					
ASDA	3933	3933					
LDA	3933	3933					



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 29 DEC 22

CTT5

CARTE D'AÉRODROME

AWOS Natashquan – 125.3 (Fr) 126.25 (Ang)		UNICOM – 123.5 (AU) (Fr)		ATF*	
DIST DÉCLARÉES	11	29			
TORA	3933	3933			
TODA	3933	3933			
ASDA	3933	3933			
LDA	3933	3933			




CARTE D'AÉRODROME

EFF 29 DÉC 22

Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés


AERODROME CHART



AERODROME CHART


CSR8

CARTE D'AÉRODROME



CARTE D'AÉRODROME

AERODROME CHART



CYLQ

72 47.8 72 46.9

47 24.9 47 24.5 47 24.2

DEC 15° N 2020

VARIATION ANNUELLE DE 7° E

ALT 550

191°

61°

A

C

B

★

CYLQ N47 24.56 W72 47.34

5000 x 150

★

011°

10°

ALT 544

★

*** PROCÉDURE DE DÉPART**

Piste 01 - ½ - Requiert une pente de montée minimale de **400 pi/NM** jusqu'à **1600**.
Monter sur cap **011°** jusqu'à **1600** BPOC.
ou
SPEC VIS - Effectuer une montée à vue pour survoler l'aéroport à **1800** ou plus haut BPOC.
Note: Arbres jusqu'à 640 ASL par le travers de l'extrémité de la piste de départ, 50' à GAUCHE et DROITE de l'axe de piste et aprx 100' passé l'extrémité de la piste de départ.

Piste 19 - ½ - Requiert une pente de montée minimale de **370 pi/NM** jusqu'à **1800**.
Monter entre cap **211°** et **010°** sens horaire jusqu'à **2500** BPOC.
ou
SPEC VIS - Effectuer une montée à vue pour survoler l'aéroport à **1800** ou plus haut BPOC.
Note: Arbres jusqu'à 594 ASL aprx 100' passé l'extrémité de la piste de départ, 500' à GAUCHE et DROITE de l'axe de piste et aprx 0.1 NM passé l'extrémité de la piste de départ.

TAUX DE MONTÉE DE DÉPART V/V (FPM)

VITESSE SOL	90	120	140	160	180	200	250	300
370 pieds/NM	560	740	870	990	1110	1240	1550	1850
400 pieds/NM	600	800	940	1070	1200	1340	1670	2000

72 47.8 72 46.9

MINIMUM DE DÉCOLLAGE


Pistes 01; 19: ★

ÉCHELLE EN PIEDS

1000 0 1000

Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

AERODROME CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

CSE4


CARTE D'AÉRODROME



CARTE D'AÉRODROME

CSE4

AERODROME CHART




AERODROME CHART

EFF 11 JUL 24

CYDO

CARTE D'AÉRODROME



CARTE D'AÉRODROME


EFF 11 JUIL 24

CYDO

LEBEL-SUR-QUÉVILLON, QC
CSH4

AERODROME CHART

				CTR Montreal – 125.9	
				TFC – 123.2	
				ATF	
DECL DIST	15	33			
TORA	4212	4212			
TODA	4212	4212			
ASDA	4212	4212			
LDA	4212	4212			



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 30 NOV 23

CSH4

CSH4-AD

CARTE D'AÉRODROME




CARTE D'AÉRODROME

EFF 30 NOV 23


CSH4

AUTO – 128.15 (En) 124.35 (Fr)		RADIO Mont-Joli – 122.0				CTR Gander – 133.0	
DECL DIST	05	23					
TORA	4500	4500					
TODA	5484	5484					
ASDA	4500	4500					
LDA	4500	4500					




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

CARTE D'AÉRODROME



AERODROME CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 20 FEB 25

CYMW

CARTE D'AÉRODROME



Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés


CARTE D'AÉRODROME

EFF 20 FÉV 25

CYMW

AERODROME CHART

MET – 127.45 (En) 125.3 (Fr)				TFC – 122.8		RADIO Quebec – 123.55 DRCO	
				ATF			
DECL DIST	15	33					
TORA	5001	5001					
TODA	5985	5985					
ASDA	5001	5001					
LDA	5001	5001					



AERODROME CHART

EFF 20 FEB 25

CYNM

*** PROCÉDURE DE DÉPART**

Piste 15 - ½
Note: Arbres jusqu'à 1042 ASL aprx
 0,1 NM passé l'extrémité de départ
 de la piste.


Piste 33 - ½
Note: Arbres jusqu'à 1060 ASL par
 le travers de l'extrémité de départ
 de la piste, 400' à GAUCHE de l'axe
 de piste.

Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

MATANE/RUSSELL-BURNETT, QC
CYME

AERODROME CHART

				 UNICOM – 122.8			CTR Montreal – 134.65 227.2	
DECL DIST	09	27				ATF		
TORA	5500	5500						
TODA	5900	6500						
ASDA	5500	5500						
LDA	5500	5500						



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

CYME

CYME-AD

CYME

Diagram illustrating the profile view of the runway and climb profile for Pistes 09 and 27.

TAUX DE MONTÉE DE DÉPART V/V (FPM)

VITESSE SOL	90	120	140	160	180	200	250	300
370 pieds/NM	560	740	870	990	1110	1240	1550	1850
390 pieds/NM	590	780	910	1040	1170	1300	1630	1950

PROCÉDURE DE DÉPART

Piste 09 - ½ - Requiert une pente de montée minimale de **390** pi/NM jusqu'à **600**. Monter sur cap **090°** jusqu'à **1500** PBOC.
Note: Arbres jusqu'à 165 ASL par le travers de l'extrémité de la piste de départ, 200' à DROITE et 250' à GAUCHE de l'axe de piste et aprx 350' passé l'extrémité de la piste de départ.

ou
 SPEC VIS - Effectuer une montée à vue pour survoler l'aéroport à **2100** ou plus haut BPOC.

Piste 27 - ½ - Requiert une pente de montée minimale de **370** pi/NM jusqu'à **1100**. AUCUN virage en dessous de **1100** BPOC.
Note: Arbres jusqu'à 220 ASL aprx 0.2 NM passé l'extrémité de la piste de départ, 600' à GAUCHE de l'axe de piste.

ou
 SPEC VIS - Effectuer une montée à vue pour survoler l'aéroport à **2100** ou plus haut BPOC.

ÉCHELLE EN PIEDS


1000 0 1000

Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

CYYY-AD

MONT-JOLI, QC
CYYY

AERODROME CHART



AERODROME CHART

EFF 2 OCT 25


CYYY-AD

CYYY

CYYY-AD

MONT-JOLI, QC
CYYY

CARTE D'AÉRODROME




CARTE D'AÉRODROME

EFF 2 OCT 25

CYYY

CYYY-AD

AUTO – 123.42 (Fr)		UNICOM – 122.8				CTR Montreal – 126.57 RADIO Quebec – 123.47	
DECL	DISTS	08	26			ATF	
TORA		4002	4002				
TODA		4002	4002				
ASDA		4002	4002				
LDA		3805	4002				



CARTE D'AÉRODROME

TAUX DE MONTÉE DE DÉPART V/V (FPM)

VITESSE SOL	90	120	140	160	180	200	250	300
220 pieds/NM	330	440	520	590	660	740	920	1100
280 pieds/NM	420	560	660	750	840	940	1170	1400

VARIATION ANNUELLE DE 4° E

Piste 08 seuil décalé 197'

Piste 26 4002 x 75

CSD4
N46 33.89
W75 34.57

ALT 815

ALT 809

PROCÉDURE DE DÉPART

Piste 08 - ½ - Requiert une pente de montée minimale de **280 pi/NM** jusqu'à **1500**.
AUCUN virage à GAUCHE en dessous de **2400**.
Note: Arbres jusqu'à 896 ASL par le travers de l'extrémité de la piste de départ, 150' à GAUCHE et à DROITE de l'axe de piste.

Piste 26 - ½ - Requiert une pente de montée minimale de **220 pi/NM** jusqu'à **1300**.
Monter sur cap **257°** jusqu'à **2100** BPOC.
Note: Arbres jusqu'à 893 ASL par le travers de l'extrémité de la piste de départ, 150' à DROITE de l'axe de piste.


MINIMUM DE DÉCOLLAGE

ÉCHELLE EN PIEDS


0 1000

Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

AERODROME CHART



CARTE D'AÉRODROME



LOW VISIBILITY PROCEDURES

Operations in Reduced and Low Visibility Conditions

- Runway 06 is certified for use in low visibility operations (RVR600).
- Runway 24 is certified for use in reduced visibility conditions (RVR1200).
- Plan activation is mandatory when one of the RVR readings or the reported ground visibility is below $\frac{1}{2}$ SM. Runways 24 and 06 can be used.
- When the reading of one of the RVR readings or the reported ground visibility is less than $\frac{1}{4}$ SM while remaining at or above $\frac{1}{8}$ SM, runway 06 must be used.
- Only one aircraft movement (RVOP and LVOP) is authorised on the manoeuvring area. In low visibility operation (LVOP), it is mandatory that the "Follow Me" vehicle escorts the aircraft.
- With the exception of aircraft returning to aprons, movement of all traffic ceases when one of the RVR reading or the reported ground visibility is below $\frac{1}{8}$ SM.
- When the two RVR readings or the reported ground visibility increases and indicates $\frac{1}{2}$ SM or more, normal operations may resume.

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


PROCÉDURES EN CONDITIONS DE FAIBLE VISIBILITÉ

Opérations en conditions de visibilité réduite et faible

- La piste 06 est homologuée pour les opérations en conditions de visibilité faible (RVR600).
- La piste 24 est homologuée pour les conditions en conditions de visibilité réduite (RVR1200).
- Le plan est déclenché lorsque la lecture d'un des RVR ou la visibilité au sol signalée est inférieure à $\frac{1}{2}$ SM. Les pistes 24 ou 06 peuvent être utilisées.
- Lorsque la lecture d'un des RVR ou la visibilité signalée au sol est de moins de $\frac{1}{4}$ SM mais de plus de $\frac{1}{8}$ SM, la piste 06 doit être utilisée.
- Un seul mouvement d'aéronef à tout moment (RVOP et LVOP) est autorisé sur l'aire de manœuvre. En condition de faible visibilité (LVOP), il doit obligatoirement être escorté d'un véhicule « Follow Me ».
- À l'exception des mouvements associés au retour des aéronefs aux aires de trafic, toute circulation au sol est interrompue lorsque la lecture d'un des RVR ou la visibilité signalée au sol est de moins de $\frac{1}{8}$ SM.
- Lorsque la lecture des deux RVR ou que la visibilité signalée au sol augmente et indique $\frac{1}{2}$ SM ou plus, le retour aux opérations normales peut être initié.

Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

PARKING AREAS




PARKING AREAS

EFF 12 JUN 25

CYMX


AIRES DE STATIONNEMENT



AIRES DE STATIONNEMENT


EFF 12 JUIN 25

CYHU-AD
MONTREAL/MET (AÉROPORT MÉTROPOLITAIN DE MONTRÉAL), QC
AERODROME CHART **CYHU**



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

CYHU-AD
 MONTRÉAL/MET (AÉROPORT MÉTROPOLITAIN DE MONTRÉAL), QC
 CYHU



Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

CARTE D'AÉRODROME
 EFF 2 OCT 25

CYHU-AD


CYHU

AERODROME CHART

CYUL

ATIS – 133.7 (En) 127.5 (Fr)	CLNC DEL – 125.6 APRON – 122.27 (W) 122.07 (E) GND – 121.0 (W) 121.9 (E) 275.8	TWR – 119.3 119.9 124.3 267.1	DEP – 120.42 (S) (SE) (SW) 124.65 (W) (NW) (NE) 268.3 RADIO Quebec – 123.55
------------------------------	--	-------------------------------	--

DECL	DISTS	06L	24R	06R	24L			
TORA		11000	11000	9604	9890			
TODA		11000	11000	9604	9890			
ASDA		11000	11000	9604	9890			
LDA		11000	11000	9604	9604			



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 06L, 06R, 24L, 24R: RVR 1200	RWY 06L: RVR 600
TAKE-OFF MINIMA	SCALE IN FEET 2000 0 2000 4000
Rwys 06L; 06R; 24L; 24R: *	

AERODROME CHART

EFF 2 OCT 25

CYUL

AERODROME CHART (REDUCED TAKE-OFF RUNS)

CYUL

When authorized by ATC, intersection departures are available as follows:

RUNWAY	INTERSECTION	TORA
06L	B6	10197
	B4	7677
	B1	6002
	B2	5237
	B3	4902
	B5	2898
06R	A4	7851
	A2	5346
	A1	4342
	L	2427
	A3	2345
24L	A3	7345
	L	7226
	A1	5347
	A2	4343
	A4	1843
	A5	9604
	R	9604
24R	B5	8244
	B3	6243
	B2	5908
	B1	5145
	B4	3470
	B6	915


Departures from inner centerline of holding bay rwy 06R subtract 276' from declared distances.

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


CARTE D'AÉRODROME

ATIS – 127.5 (Fr) 133.7 (Ang)	CLNC DEL – 125.6 AIRE DE TRAFIC – 122.27 (W) 122.07 (E) GND – 121.0 (W) 121.9 (E) 275.8	TWR – 119.3 119.9 124.3 267.1	DEP – 120.42 (S) (SE) (SW) 124.65 (W) (NW) (NE) 268.3 RADIO Québec – 123.55
-------------------------------	--	-------------------------------	--

DIST DÉCLARÉES	06L	24R	06R	24L			
TORA	11000	11000	9604	9890			
TODA	11000	11000	9604	9890			
ASDA	11000	11000	9604	9890			
LDA	11000	11000	9604	9604			



Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

NIVEAU DE SERVICES DE LA PISTE	
RVO	LVO
PISTE 06L, 06R, 24L, 24R: RVR 1200	PISTE 06L: RVR 600
MINIMUM DE DÉCOLLAGE	
Pistes 06L; 06R; 24L; 24R: ★	

CARTE D'AÉRODROME

EFF 2 OCT 25

CYUL-AD-1

CYUL

CARTE D'AÉRODROME (DISTANCE DE ROULEMENT UTILISABLE)

CYUL

Lorsque autorisé par ATC, les départs d'intersection sont disponibles comme suit :

PISTE	INTERSECTION	TORA
06L	B6	10197
	B4	7677
	B1	6002
	B2	5237
	B3	4902
	B5	2898
06R	A4	7851
	A2	5346
	A1	4342
	L	2427
	A3	2345
24L	A3	7345
	L	7226
	A1	5347
	A2	4343
	A4	1843
	A5	9604
	R	9604
24R	B5	8244
	B3	6243
	B2	5908
	B1	5145
	B4	3470
	B6	915

Les départs de l'axe intérieur de la baie d'attente Piste 06R soustraire 276' des distances déclarées.

Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

TAXI CHART

Notes

Widebody Aircraft:

A380, A124, A346, B748 & B773 – Right turn prohibited from A4 or A2 to A.

A380, A124, A346, B748 & B773 – Left turn difficult from A1 to A. Use of A3 or A7 recommended.

A380, A340-500/600, A350-1000 & B777 – Right turn prohibited from A4 to D.

A380, AN124, A346, B748 – Caution for wingtip clearance when circulating on Twy A behind departing traffic on Twy A5.

Code F aircraft – Standard routes. Follow ATC and Apron Control instructions.

A380 – It is mandatory to use the procedures for runway widths of 58 m or less without paved shoulders. (All runways 60 m wide with 7.5 m shoulders: first meter paved, remaining, grass).

Minimum Rwy to Twy Separation			
	Rwy	Twy	Separation (m)
1	06L – 24R	B	225
2	06R – 24L	A	232
3	06L – 24R	North Ramp	210
4	06R – 24L	AM	233

Minimum Twy to Twy Separation			
	Twy	Twy	Separation (m)
1	I	H	195.9
2	K	J	195.8
3	A	D	85.6
4	M	B	91.1

Minimum Twy to Taxilane Separation			
	Twy	Taxilane	Separation (m)
1	North Ramp	South taxilane*	80.5
2	AM	East Holding point*	80.6
* closed during code F Aircraft operations			

Minimum Twy to Obstacle Separation			
	Twy	Obstacle	Separation (m)
1	B6	T395	50.9
2	A	Road 630*	47.5
3	North Ramp	Road E1 to E3*	43.3
4	North Ramp	Road, stands 17 to 27*	47.7
5	Ramp NW – SE	Road, stands 11B to 15*	47
6	Ramp NW – SE	Road, stands 15 to 15B*	42.5
* closed during code F Aircraft operations			

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

CARTE DE CIRCULATION

Notes

Avion gros-porteurs :

A380, A124, A346, B748 & B773 – Virage à droite interdit de A4 ou A2 vers A.

A380, A124, A346, B748 & B773 – Virage à gauche difficile de A1 vers A.
Utilisation de A3 ou A7 recommandée.

A380, A340-500/600, A350-1000 & B777 – Virage à droite interdit de A4 vers D.

A380, AN124, A346, B748 – Attention à la distance de dégagement des ailes lors du déplacement sur Twy A derrière le trafic au départ du Twy A5.

Aéronefs de code F – Routes normalisées. Suivre les instructions d'ATC et contrôle du tablier.

A380 – Il est obligatoire d'utiliser les procédures pour pistes de 58 m ou moins sans accotement pavé. (Pistes 60 m de largeur avec accotements de 7.5 m; premier mètre pavé, reste en gazon).

Dégagement minimum RWY à TWY			
	RWY	TWY	Dégagement (m)
1	06L – 24R	B	225
2	06R – 24L	A	232
3	06L – 24R	Rampe nord	210
4	06R – 24L	AM	233


Dégagement minimum TWY à TWY			
	TWY	TWY	Dégagement (m)
1	I	H	195.9
2	K	J	195.8
3	A	D	85.6
4	M	B	91.1

Dégagement minimum TWY à voie d'accès de poste de stationnement			
	TWY	Voie d'accès de poste de stationnement	Dégagement (m)
1	Rampe nord	Voie d'accès de poste de stationnement Sud*	80.5
2	AM	Point d'attente Est*	80.6
*Fermé pendant opérations d'aéronefs de code F			

Dégagement minimum TWY à obstacle			
	TWY	Obstacle	Dégagement (m)
1	B6	T395	50.9
2	A	Route 630*	47.5
3	Rampe nord	Route E1 à E3*	43.3
4	Rampe nord	Route, postes 17 à 27*	47.7
5	Rampe NW – SE	Route, postes 11B à 15*	47
6	Rampe NW – SE	Route, postes 15 à 15B*	42.5
*Fermé pendant opérations d'aéronefs de code F			

Source des données aéronautiques civiles pour le Canada : ©2025 NAV CANADA Tous droits réservés

CARTE DE CIRCULATION



CARTE DE CIRCULATION

CYUL

LOW VISIBILITY PROCEDURES

Low Visibility Procedures (RVR less than 1200 to 600 ft)**1. Application**

These procedures apply to ground movements of aircraft during low visibility conditions (Runway Visual Range [RVR] less than 1200 to 600 ft). Arrivals and departures below RVR 600 are not authorized. When weather conditions indicate visibility below RVR 1200 is imminent, procedures will be implemented to ensure the safe and efficient movement of aircraft. The following message will be added to the ATIS broadcast: **“LOW VISIBILITY PROCEDURES IN EFFECT”**

2. Surface Guidance and Control System

Surface guidance and control system have been installed to facilitate the ground movements of aircraft under low visibility conditions. This system, controlled by ATC, is:

- Taxiway centreline lights on holding bay 24R.
- Taxiway uni-directional centreline lights on taxiways A (between J and A4), A4 between A and the apron), B, B3, B4 (from B to the apron), B5, D, E (from the apron to I), H, I, J and K.
- Bi-directional centreline lights on the North ramp from taxiway B6 to A4, South ramp from B6 to gate 65, and East and West taxilanes up to gate 66.
- Stop Bars on all access to runway 06L/24R: on the holding bays of runways 06L and 24R, at the end of taxiway C before the intersection with runway 06L/24R and on taxiways B1, B2, B3, B4, B5, and B6 (illuminated under 1200 RVR).

NOTE: AT NO TIME SHALL A PILOT CROSS AN ILLUMINATED RED STOP BAR

- Runway guard lights on all access to runways: on the holding bays of runways 06L, 24R and 06R, at the end of taxiway C before the intersection with runway 06L/24R, and on taxiways A, A1, A2, A3, A4, A5, A7, B1, B2, B3, B4, B5, B6, L and R (illuminated whenever the associated runway is in use).

NOTE: The above mentioned taxiway centreline lights and stop bars may be used at or above 1200 RVR.

LOW VISIBILITY PROCEDURES

CYUL

3. Airport Surface Detection Equipment (ASDE)

Ground radar is used to monitor the position of aircraft and vehicles operating on the manoeuvring area. In the event of an ASDE failure, ATC may restrict low visibility operations.

4. “Follow me” Vehicle

A “Follow Me” vehicle will be provided on pilot's request.

5. Departure Routes

Runway 06L is the only one certified for take-offs during low visibility conditions (RVR less than 1200 to 600 ft). All departures under low visibility conditions will be on runway 06L. Intersection take-offs are not authorized.

Sequencing of aircraft ground movements for take-off: Do not request start, push back or taxi clearance until reported RVR is greater than:

Aircraft/Pilot Take-off Minima	Minimum RVR for Start
1200 RVR	1000 RVR
600 RVR	600 RVR

Unless otherwise advised by ATC, the following standard routes will be used, under low visibility conditions, for aircraft departing on runway 06L (see low visibility taxi chart).

From the main apron to the de-icing bay: aircraft will taxi on E and H or on D and K.

From the main apron to runway 06L: aircraft will taxi on the main apron to the holding bay runway 06L.

From the de-icing bay to runway 06L: aircraft will taxi on I, B, B4, and on the apron to the holding bay runway 06L.

From the de-icing bay to the main apron aircraft will taxi on taxiways J, A and A4.

From general aviation to 06L, aircraft will taxi on taxiway R, across threshold 24L, taxiways A5, A and A4, north side of the apron to the holding bay 06L.

6. Arrival Routes

Aircraft will exit runway 06L on taxiways B1, B3, B5 or holding bay 24R, taxiways B, B4 and then follow Apron Control instructions. Aircraft destined to the general aviation sector will exit the main apron at A4, and will taxi via runway 06R, and taxiways L and R.

LOW VISIBILITY TAXI CHART

(RVR LESS THAN 1200 TO 600 FT)


MONTRÉAL/PIERRE-ELLIOTT-TRUDEAU INTL, QC
CYUL

ATIS - 133.7 (En) 127.5 (Fr)	CLNC DEL - 125.6 APRON - 122.27 (W) 122.07 (E) GND - 121.0 (W) 121.9 (E) 275.8	TWR - 119.3 119.9 124.3 267.1
------------------------------	--	-------------------------------

LEGEND

- STOP BARS
- RUNWAY GUARD LIGHTS
- TAXIWAY CENTRELINE LIGHTS (BIDIRECTIONAL)
- DIRECTION OF AIRCRAFT MOVEMENTS


 ANNUAL RATE
 OF CHANGE 4° E



Multilateration:
 Keep transponder on
 at all times when taxiing.

(RVR LESS THAN 1200 TO 600 FT)
LOW VISIBILITY TAXI CHART

Procédures en conditions de faible visibilité (RVR en dessous de 1200 jusqu'à 600 pieds)

1. Application

Ces procédures s'appliquent aux aéronefs circulant au sol en conditions de faible visibilité (portée visuelle de piste [RVR] en dessous de 1200 jusqu'à 600 pieds). Les départs et les arrivées en dessous de 600 RVR ne sont pas autorisés. Lorsque les conditions météorologiques indiquent que la portée visuelle de piste pourrait descendre en dessous de 1200 RVR, les procédures suivantes seront mises en place afin d'assurer la sécurité et l'efficacité des mouvements d'aéronefs. Le message suivant sera alors diffusé l'ATIS : **« PROCÉDURES EN CONDITIONS DE FAIBLE VISIBILITÉ EN VIGUEUR »**.

2. Système de guidage et de contrôle de la circulation de surface

Un système de guidage et de contrôle de la circulation de surface a été mis en place afin de faciliter le mouvement des aéronefs en conditions de faible visibilité. Ce système, commandé par l'ATC, comprend :

- Des feux axiaux de sortie sur la baie d'attente 24R.
- Des feux axiaux unidirectionnels sur les voies de circulation A (entre J et A4), A4 (entre A et l'aire de trafic), B, B3, B4 (de B à l'aire de trafic), B5, D, E (de l'aire de trafic à I), H, I, J et K.
- Des feux axiaux bi-directionnels sur la rampe nord de la voie de circulation B6 à A4, sur la rampe sud entre B6 et la barrière 65, et sur les lignes de guidage est et ouest jusqu'à la barrière 66.
- Des barres d'arrêt sur tous les accès à la piste 06L/24R : dans les baies d'attente des pistes 06L et 24R, à l'extrémité de C avant l'intersection de la piste 06L/24R et sur les voies de circulation B1, B2, B3, B4, B5, et B6 (allumées en dessous de 1200 RVR).

Note : NE JAMAIS TRAVERSER UNE BARRE D'ARRÊT ALLUMÉE

- Des feux de protection de piste sur les accès de toutes les pistes : les baies d'attente des pistes 06L, 24R et 06R, à l'extrémité de C avant l'intersection de la piste 06L/24R, et sur les voies de circulation A, A1, A2, A3, A4, A5, A7, B1, B2, B3, B4, B5, B6, L et R (allumés en tout temps sur les accès des pistes en service).

Note : Les feux axiaux de voies de circulation et les barres d'arrêt sus-mentionnées pourraient être utilisés dans des conditions égales ou supérieure à 1200 RVR.

3. Radar de surveillance des mouvements de surface (ASDE)

Un radar de surveillance des mouvements de surface est utilisé pour la localisation des aéronefs et des véhicules sur les aires mouvements. En cas de panne de ce radar l'ATC peut restreindre les actions en conditions de faible visibilité.

4. Véhicule « Follow Me »

Un véhicule équipé d'une affiche « Follow Me » sera disponible à la demande des pilotes.

5. Trajets pour les départs

Seule la piste 06L est homologuée pour des décollages en conditions de faible visibilité (RVR en dessous de 1200 et pouvant atteindre 600 pieds). Tous les départs en conditions de faible visibilité se feront sur la piste 06L. Les décollages à partir d'intersections ne sont pas autorisés.

Mise en séquence des mouvements au sol d'aéronefs pour décollages : ne pas demander de démarrer les moteurs, de refouler ou une autorisation de circuler à moins que le RVR rapporté ne soit supérieur aux valeurs suivantes :

Minima de décollage du pilote ou de l'aéronef	RVR minimum pour démarrer les moteurs
1200 RVR	1000 RVR
600 RVR	600 RVR

À moins d'avis contraire de l'ATC, les trajets suivants seront utilisés en conditions de faible visibilité pour les aéronefs au décollage de la piste 06L (voir carte de circulation en conditions de faible visibilité).

Du tablier principal en direction de l'aire de dégivrage : les aéronefs circuleront sur les voies de circulation E et H ou D et K.

Du tablier principal en direction de la piste 06L : les aéronefs circuleront sur le tablier jusqu'à la baie d'attente de la piste 06L.

De l'aire de dégivrage en direction de la piste 06L : les aéronefs circuleront sur les voies de circulation I, B, B4, et le tablier jusqu'à la baie d'attente de la piste 06L.

De l'aire de dégivrage en direction du tablier principal : les aéronefs circuleront sur les voies de circulation J, A et A4.

De l'aviation générale, la voie de circulation R, traverser le seuil 24L, les voies de circulation A5, A et A4, voie de circulation du côté nord de l'aire de trafic jusqu'à la baie d'attente 06L.

6. Trajets pour les arrivées

Les aéronefs quitteront la piste 06L en utilisant les voies de circulation B1, B3, B5 ou par la baie d'attente de la piste 24R, les voies de circulation B, B4 puis suivront les instructions du contrôle du tablier. Les aéronefs se dirigeant à l'aviation générale quitteront l'aire de trafic à A4 et utiliseront la piste 06R, et les voies de circulation L et R.


CARTE DE CIRCULATION EN CONDITIONS DE FAIBLE VISIBILITÉ (RVR en dessous de 1200 jusqu'à 600 pieds) MONTRÉAL/PIERRE-ELLIOTT-TRUDEAU INTL, QC CYUL

ATIS – 127.5 (Fr) 133.7 (Ang)	CLNC DEL – 125.6 AIRE DE TRAFIC – 122.27 (W) 122.07 (E) GND – 121.0 (W) 121.9 (E) 275.8	TWR – 119.3 119.9 124.3 267.1
-------------------------------	--	-------------------------------

LÉGENDE

- ... BARRES D'ARRÊT
- == FEUX DE PROTECTION DE PISTE
- FEUX AXIAUX DE VOIES DE CIRCULATION (BIDIRECTIONNELS)
- SENS DE LA CIRCULATION

DEC 15 W
 2013
 VARIATION
 ANNUELLE DE 4° E



Multilatération:
 Laissez votre transpondeur
 allumé en tout temps lorsque
 vous circulez.


(RVR en dessous de 1200 jusqu'à 600 pieds)

CARTE DE CIRCULATION EN CONDITIONS DE FAIBLE VISIBILITÉ
 CYUL-GM-3C

CYUL
 EFF 2 OCT 25

PARKING CENTRE AREAS AND DE-ICING POSITIONS AND PROCEDURES

CYUL

DE-ICING CENTRE, Oct 1 - Apr 30

1. Contact MONTREAL DE-ICE on 123.425, no later than 30 min prior push-back, with de-icing type.
2. On Twys J or K, hold short of the de-icing pad and contact AEROMAG PAD CONTROL 122.525.
3. On Twy E hold short of H or I and contact AEROMAG PAD CONTROL on 122.525.
4. Follow AEROMAG PAD CONTROL instructions and guiding lines to the assigned de-icing bay and confirm "brakes set" when in position.
5. On AEROMAG PAD CONTROL instructions, contact ICEMAN on 123.125 & confirm aircraft configured for de-icing and engines at idle.
6. When de-icing is completed and on ICEMAN instructions only, contact AEROMAG PAD CONTROL on 122.525 before moving aircraft.
7. Exiting de-icing pad on AEROMAG PAD CONTROL instructions contact ground control:
on Twy J, holding short of Twy U,
on Twy K, holding short of Twy C,
on Twy H or I holding short of Twy E.

De-icing bays capacity:

- | | |
|-----------|--------------------------------|
| 1 & 3: | Maximum wingspan 36m (118'); |
| 2: | Maximum wingspan 80m (262'); |
| 4, 5 & 9: | Maximum wingspan 65m (213'); |
| 6 & 8: | Maximum wingspan 36m (118'); |
| 7: | Maximum wingspan 45.8m (150'); |

Note: May 1 - Sep 30 DE-ICING CENTRE used as apron area ctc 122.075.

PARKING CENTRE AREAS AND DE-ICING POSITIONS AND PROCEDURES

CYUL

EFF 12 JUN 25

ENGINE FAN BLADE ICE SHEDDING PROCEDURES

CYUL

The undertaking of aircraft engine run-up for engine fan-blade ice-shedding must be conducted on taxiway areas outlined in ENGINE FAN-BLADE ICE-SHEDDING PROCEDURES. Strict adherence to the center line is mandatory during engine fan-blade ice-shedding. The crew must make first contact on the clearance frequency (125.6 MHz), to provide the following information:

- De-Icing requirements
- Ice-shedding requirements before takeoff
- Runway run-up requirements on the runway before takeoff

In addition, the following elements needs be considered:

- The crew will communicate on the Ground frequency (121.9 MHz or 121.0 MHz) to report any changes that occur following initial contact. NAV CANADA must be informed if the ice-shedding procedure has been completed on taxiway Juliette.
- If the taxiway surface conditions are not suitable for the crew, communication must be made to ATC to arrange another location.

Departing Rwy 24R Ice-Shed Area (IS) see chart.

- IS1 Taxiway B short of holding bay 24R. Available for aircraft AGN V & smaller.
- IS2 Taxiway B short of taxiway B5. Available for aircraft AGN V & smaller.
- IS3 Taxiway B short of taxiway B3. Available for aircraft AGN IIIB & smaller.

Departing Rwy 06L Ice-Shed Area (IS) see chart.

- IS4 Taxiway B short of taxiway B4. Available for aircraft AGN V & smaller.

Departing Rwy 24L Ice-Shed Area (IS) see chart.

- IS5 Taxiway A short of taxiway A5. Available for aircraft AGN V & smaller.
- IS6 Taxiway A short of taxiway A3. Available for aircraft AGN IIIB & smaller.
- IS7 Taxiway A short of taxiway A1. Available for aircraft AGN V & smaller.
- IS8 Taxiway A short of taxiway A2. Available for aircraft AGN IIIB & smaller.

Departing Rwy 06R Ice-Shed Area (IS) see chart.

- IS9 Taxiway A short of taxiway C. Available for aircraft AGN V & smaller.
- IS10 Taxiway A short of taxiway A4. Available for aircraft AGN V & smaller.

Additional locations depending on operational needs.

- IS11 Facing East on taxiway C short of taxiway D. Available for aircraft AGN V & smaller.
- IS12 Facing West on taxiway C short of taxiway E. Available for aircraft AGN V & smaller.
- IS13 Facing East on taxiway J short of taxiway U. Available for the following aircraft belonging to AGN IIIB: all Embraer, CRJ and Airbus. No B737 group aircraft is authorized to perform the ice-shedding procedure on taxiway J.

ENGINE FAN BLADE ICE SHEDDING PROCEDURES

ATIS - 133.7 (En) 127.5 (Fr)

CLNC DEL - 125.6

APRON - 122.27 (W) 122.07 (E)



GND - 121.0 (W) 121.9 (E) 275.8

TWR - 119.3 119.9 124.3 267.1

LEGEND

••• STOP BARS

--- RUNWAY GUARD LIGHTS



SCALE IN FEET

1000 0 1000


ENGINE FAN BLADE ICE SHEDDING PROCEDURES

CYUL

EFF 2 OCT 25

AIRES DE STATIONNEMENT CENTRE et POSITIONS DE DÉGIVRAGE et PROCÉDURES

MONTRÉAL/PIERRE-ELLIOTT-TRUDEAU INTL, QC
CYUL



Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

CENTRE DÉGIVRAGE 1 oct - 30 avr

1. Contacter MONTRÉAL CENTRE DÉGIVRAGE sur 123.425, au plus tard 30 minutes avant le refoulement, et confirmer le type de dégivrage.
2. Sur Twys J ou K à l'écart du tablier de dégivrage, contacter AEROMAG CONTRÔLE DÉGIVRAGE sur 122.525.
3. Sur Twy E à l'écart de H ou I, contacter AEROMAG CONTRÔLE DÉGIVRAGE sur 122.525.
4. Suivez les instructions d'AEROMAG CONTRÔLE DÉGIVRAGE et les lignes de guidage jusqu'à la baie assignée et confirmer que les freins sont serrés après arrêt.
5. Sur instructions d'AEROMAG CONTRÔLE DÉGIVRAGE contacter ICEMAN sur 123.125 et confirmer que l'appareil est configuré pour le dégivrage et que les moteurs sont sur régime ralenti.
6. Lorsque le dégivrage est complété et seulement sur instructions du ICEMAN contacter AEROMAG CONTRÔLE DÉGIVRAGE sur 122.525 avant tout mouvement.
7. À la sortie du tablier de dégivrage, sur instructions d'AEROMAG CONTRÔLE DÉGIVRAGE, contacter le contrôle-sol:
sur Twy J, à l'écart Twy U:
sur Twy K, à l'écart Twy C:
sur Twy H ou à l'écart Twy E:

Capacité des baies

- | | |
|-----------|-----------------------------------|
| 1 & 3: | Envergure maximale 36m (118');) |
| 2: | Envergure maximale 80m (262');) |
| 4, 5 & 9: | Envergure maximale 65m (213');) |
| 6 & 8: | Envergure maximale 36m (118');) |
| 7: | Envergure maximale 45.8m (150');) |

Note: 1 mai - 30 sep CENTRE DÉGIVRAGE utilisé comme aire de trafic ctc 122.075.

AIRES DE STATIONNEMENT CENTRE et POSITIONS DE DÉGIVRAGE et PROCÉDURES

CYUL

PROCÉDURES D'ÉLIMINATION DE LA GLACE SUR LES AILETTES DE SOUFFLANTE

MONTRÉAL/PIERRE-ELLIOTT-TRUDEAU INTL, QC
CYUL

Les points fixes des moteurs d'avion pour l'élimination de la glace doivent être effectués sur certaines voies de circulation indiquées sur PROCÉDURES D'ÉLIMINATION DE LA GLACE SUR LES AILETTES DE SOUFFLANTE. Une bonne adhérence à l'axe central est obligatoire lors de l'élimination de la glace. L'équipage doit établir un premier contact sur la fréquence d'autorisation (125,6 MHz), afin de fournir les informations suivantes :

- Exigences de dégivrage
- Exigences en matière d'élimination de la glace avant le décollage
- Exigence de point fixe sur la piste avant le décollage

De plus, les éléments suivants devront être considérés :

- L'équipage devra communiquer sur la fréquence Sol (121.9 MHz ou 121.0 MHz) afin de signaler tout changement survenu suite au contact initial. NAV CANADA devra être informé si la procédure d'élimination de la glace a été complétée sur la voie de circulation Juliette.
- Si les conditions de la surface de la voie de circulation ne conviennent pas à l'équipage, une communication devra être effectuée auprès de ATC afin de prévoir un autre emplacement.

Départ de la piste 24R Élimination de la Glace (IS) voir carte.

- IS1 Sur la voie de circulation B à l'écart de la baie d'attente 24R. Disponible pour le AGN V et plus petit.
- IS2 Sur la voie de circulation B à l'écart de la voie de circulation B5. Disponible pour le AGN V et plus petit.
- IS3 Sur la voie de circulation B à l'écart de la voie de circulation B3. Disponible pour le AGN IIIB et plus petit.

Départ de la piste 06L Élimination de la Glace (IS) voir carte.

- IS4 Sur la voie de circulation B à l'écart de la voie de circulation B4. Disponible pour le AGN V et plus petit.

Départ de la piste 24L Élimination de la Glace (IS) voir carte.

- IS5 Sur la voie de circulation A à l'écart de la voie de circulation A5. Disponible pour le AGN V et plus petit.
- IS6 Sur la voie de circulation A à l'écart de la voie de circulation A3. Disponible pour le AGN IIIB et plus petit.
- IS7 Sur la voie de circulation A à l'écart de la voie de circulation A1. Disponible pour le AGN V et plus petit.
- IS8 Sur la voie de circulation A à l'écart de la voie de circulation A2. Disponible pour le AGN IIIB et plus petit.

Départ de la piste 06R Élimination de la Glace (IS) voir carte.

- IS9 Sur la voie de circulation A à l'écart de la voie de circulation C. Disponible pour le AGN V et plus petit.
- IS10 Sur la voie de circulation A à l'écart de A4. Disponible pour le AGN V et plus petit.

Emplacements supplémentaires selon les besoins opérationnels

- IS11 Face à l'est sur la voie de circulation C à l'écart de la voie de circulation D. Disponible pour le AGN V et plus petit.
- IS12 Face à l'ouest sur la voie de circulation C à l'écart de la voie de circulation E. Disponible pour le AGN V et plus petit.
- IS13 Face à l'est sur la voie de circulation J à l'écart de la voie de circulation U. Disponible pour les aéronefs du AGN IIIB suivants: tous les Embraer, CRJ et Airbus. Aucun aéronef du groupe B737 n'est autorisé à effectuer la procédure de délestage de glace sur la voie J.

Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

PROCÉDURES D'ÉLIMINATION DE LA GLACE SUR LES AILETTES DE SOUFFLANTE

MONTRÉAL/PIERRE-ELLIOTT-TRUDEAU INTL, QC
CYUL


ATIS - 127.5 (Fr) 133.7 (Ang)

CLNC DEL - 125.6
AIRE DE TRAFIC - 122.27 (W)
122.07 (E)
GND - 121.0 (W) 121.9 (E) 275.8

TWR - 119.3 119.9 124.3 267.1

LÉGENDE

- ... BARRES D'ARRÊT
- == FEUX DE PROTECTION DE PISTE



ÉCHELLE EN PIEDS


1000 0 1000

PROCÉDURES D'ÉLIMINATION DE LA GLACE SUR LES AILETTES DE SOUFFLANTE

CYUL

EFF 2 OCT 25

PARKING AREAS




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

PARKING AREAS

EFF 17 APR 25

CYUL

AIRES DE STATIONNEMENT




Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

AIRES DE STATIONNEMENT

EFF 17 AVR 25


CYUL

START BOXES



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

POINTS DE DÉPART




Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

POINTS DE DÉPART

EFF 2 OCT 25

CYUL

NORTH PARKING AREA



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


NORTH PARKING AREA

EFF 2 OCT 25

CYUL

AIRE DE STATIONNEMENT NORD

CYUL



Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés


AIRE DE STATIONNEMENT NORD

EFF 2 OCT 25

CYUL

PLAN OF OPERATIONS IN THE ABSENCE OF APRON CONTROL

CYUL



PLAN OF OPERATIONS IN THE ABSENCE OF APRON CONTROL

CYUL


EFF 2 OCT 25

CYUL-APD-4


Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

PLAN D'OPÉRATIONS EN L'ABSENCE DE CONTRÔLE SUR L'AIRE DE TRAFIC


CYUL



AWOS – 126.25 (En) 125.3 (Fr)				☉ RADIO Madeleine – 122.2		CTR Montreal – 134.82 RADIO Quebec – 123.85	
				☉ TFC – 122.2		MF*	
DECL DIST	14	32					
TORA	4495	4495					
TODA	5479	5479					
ASDA	4495	4495					
LDA	4495	4495					



CARTE D'AÉRODROME




CARTE D'AÉRODROME

EFF 11 JUIL 24

CYNA

AERODROME CHART


AUTO – 122.97		UNICOM – 131.7 (AU)				RADIO Quebec – 123.27		
DECL DIST	09	27						
TORA	5000	5000						
TODA	6000	6000						
ASDA	5000	5000						
LDA	5000	5000						




AERODROME CHART

EFF 5 SEP 24

CARTE D'AÉRODROME



AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 21 MAR 24

CYND

CARTE D'AÉRODROME

75 34.5 75 34 75 33.5

45 31.5 45 31 45 31

DEC 14° W
2003
VARIATION
ANNUELLE DE 2' E

CYND
N45 31.30
W75 33.82

6000 x 150

089°

ELEV
209

269°

AS

ELEV
211

HS 1

HS-1 - Visibilité bloquée
de la FSS et possibilité
d'incursion sur la piste.

1 2 3 4 5

★PROCÉDURE DE DÉPART

Piste 09 - ½
Note: Arbres jusqu'à 321 ASL à moins de 0.5 NM de l'extrémité de la piste de départ, 600' à GAUCHE et à DROITE de l'axe de piste. Ligne de transmission jusqu'à 344 ASL aprx 0.7 NM passé l'extrémité de la piste de départ, 1650' à DROITE de l'axe de piste.

Piste 27 - ½
Note: Terrain jusqu'à 253 ASL passé l'extrémité de la piste de départ. Arbres jusqu'à 260 ASL par le travers de l'extrémité de la piste de départ, 300' à GAUCHE de l'axe de piste et aprx 500' passé l'extrémité de la piste de départ. Arbres jusqu'à 308 ASL aprx 0.4 NM passé l'extrémité de la piste de départ, 750' à DROITE de l'axe de piste.

MINIMUM DE DÉCOLLAGE

ÉCHELLE EN PIEDS

1000 0 1000


Pistes 09; 27: ★

LÉGENDE

1 Les Ailes d'époque du Canada
2 Hangar 2
3 Hangar 3
4 Hangar 4
5 Aérogare/FBO/FSS

Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

AERODROME CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 17 APR 25

CYPN

CARTE D'AÉRODROME




CARTE D'AÉRODROME

EFF 17 AVR 25

CYPN

AUTO – 122.55		UNICOM – 131.7 (AU)		CTR Montreal – 132.25	
DECL DIST		17	35		ATF
TORA	4436	4436			
TODA	4436	4436			
ASDA	4436	4436			
LDA	4436	4436			




CSF3




AERODROME CHART

				TFC – 122.85		ATF	
DECL DIST	09	27					
TORA	3520	3520					
TODA	3520	3520					
ASDA	3520	3520					
LDA	3520	3520					



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

CARTE D'AÉRODROME




CARTE D'AÉRODROME

EFF 5 OCT 23

CPM3

AERODROME CHART

AWOS – 128.65 (En) 120.45 (Fr)				UNICOM – 123.5 TFC – 123.5		CTR Montreal – 132.27 RADIO Quebec – 123.27	
DECL	DISTS	01	19				
TORA		6299	6299				
TODA		7283	7283				
ASDA		6299	6299				
LDA		6299	6299				




AERODROME CHART

EFF 29 DEC 22

CYPX

CARTE D'AÉRODROME


AWOS – 120.45 (Fr) 128.65 (Ang)				UNICOM – 123.5 TFC – 123.5		CTR Montreal – 132.27 RADIO Quebec – 123.27	
DIST DÉCLARÉES	01	19					
TORA	6299	6299					
TODA	7283	7283					
ASDA	6299	6299					
LDA	6299	6299					



CARTE D'AÉRODROME

CYPX

AERODROME CHART




AERODROME CHART

EFF 14 JUL 22

CYHA

CARTE D'AÉRODROME



Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

CARTE D'AÉRODROME

CYHA

EFF 14 JUIL 22

QUÉBEC/JEAN LESAGE INTL, QC
CYQB

CYQB

*** DEPARTURE PROCEDURE**
Refer to DEPARTURE PROCEDURE page.

HOT SPOTS:
HS1: Taxiing south bound on twy B aircraft miss the stop line for 11/29.
HS2: Aircraft taxiing east bound on twy A must give priority to aircraft taxiing on twy D.
HS3: Taxiing north bound on twy D aircraft miss left turn twy E.

NOTE: Remain clear of CYR 603 and CYR 612 (5.5 NM North of apt).


LDA FOR LAND AND HOLD SHORT OPERATIONS (LAHSO)		
FROM	TO	LDA in ft
Thld Rwy 24	Short of Rwy 11-29	5434
Thld Rwy 29	Short of Rwy 06-24	3849

RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 06: RVR 1200 RWY 24: (¼ sm)	NOT AUTHORIZED
TAKE-OFF MINIMA	SCALE IN FEET
All Rwys: *	

CYQB

CYQB-AD

CARTE D'AÉRODROME



CARTE D'AÉRODROME

EFF 31 OCT 24

CYQB

REDUCED VISIBILITY PROCEDURES

Reduced Visibility Procedures (RVR less than 2600 to 1200 ft)**Reduced Visibility Operations - 24 hours**

Reduced Visibility Operations on runway 06-24: these are operations when reported visibility is less than RVR 2,600 feet or ½ statute mile and greater than or equal to RVR 1,200 feet or ¼ statute mile, per advisory circular CI 302-001.

Low visibility operations (LVOP) (below RVR 1200') are not permitted.

Departures & Arrivals**Follow-me car**

A "Follow-me" car will be available at all times, under any circumstances, upon a pilot's request. This service is available for one aircraft at a time based on first come, first served principles; some exceptions may apply.

During RVOP conditions, run-ups and towing will not be authorized on the maneuvering areas. Furthermore, vehicle access to the maneuver area during reduced visibility operations is restricted to essential operational functions only.

Night Only: When reported visibility is less than RVR 1800 or 3/8 SM, a "Follow-me" car is mandatory per advisory circular AC 302-004.

Operation Terms

20 minutes prior to a flight's departure time, the pilot shall contact NAV CANADA's ground controller to request a "Follow-me" car escort for taxiing on the manoeuvring area.

The pilot shall provide the following information:

- Exact position on the airfield (gate or FBO);
- Type of aircraft and airline;
- Flight departure time (if available);
- Runway used for take-off;

The "Follow-me" car will position itself 30m in front of the aircraft. Hazard lights will be activated when ready for taxiing and for the duration of the escort procedure.

Upon receiving authorization to proceed, the "Follow-me" car will follow the guide lines at no more than 30kph (16 knots) up to the desired destination.

Runway Level of Service

Rwy 06	RVR 1200
Rwy 24	(¼ sm)

PROCÉDURE D'OPÉRATIONS AVEC UNE VISIBILITÉ RÉDUITE

CYQB

**Procédure d'opérations avec une visibilité réduite
(RVR en-dessous de 2600 jusqu'à 1200 pieds)****Opérations visibilité réduite 24 heures**

Les opérations effectuées sur la piste 06-24 : lorsque la visibilité signalée est inférieure à un RVR 2600 ou ½ mille terrestre, mais supérieure ou égale à une RVR 1200 ou ¼ mille terrestre, est en conformité avec le circulaire CI 302-001.

Les opérations par faible visibilité (LVOP) (en bas de RVR 1200') ne sont pas permises.

Départs & Arrivées**Véhicule « Follow-me »**

Un véhicule « Follow-me » sera disponible en tout temps, pour toutes circonstances, à la demande des pilotes. Ce service s'applique pour un vol à la fois, sur une base de premier arrivé, premier servi, sauf exception.

Lors d'opérations RVOP, aucun remorquage ni essai moteur n'est permis sur les aires de manœuvre. De plus, l'accès par véhicule à l'aire de manœuvre lors de conditions de visibilité réduite sera restreint aux fonctions essentielles aux opérations seulement.

Nuit seulement : Lorsque la visibilité signalée est inférieure à une RVR 1800 ou 3/8 SM, un véhicule « Follow-me » est obligatoire en conformité avec le circulaire CI 302-004.

Conditions d'exploitation

20 minutes avant l'heure de départ ou à l'arrivée du vol, le pilote place une demande pour l'assistance d'un véhicule d'escorte « Follow-me » afin de circuler sur les aires de manœuvre en communiquant avec le contrôleur sol de NAV CANADA.

Le pilote doit fournir les informations suivantes:

- La position exacte sur le site (numéro de barrière ou FBO);
- Le type d'appareil et la compagnie aérienne;
- L'heure de départ du vol (si applicable);
- La destination sur le site (seuil de piste, numéro de barrière ou FBO);

Le véhicule « Follow-me » se présentera devant l'appareil à une distance de 30m et les feux de détresse (Hazard) seront activés afin de démontrer qu'il est prêt à circuler, et ce, pour toute la durée de l'escorte;


Après autorisation de circuler, le véhicule « Follow-me » suivra les lignes guides à une vitesse de 30 kph (16 nœuds) jusqu'à la destination demandée.

Niveau de service de la piste

Piste 06	RVR 1200
Piste 24	(¼ sm)

Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

PARKING AREAS




PARKING AREAS


EFF 27 JAN 22

CYQB


AIRES DE STATIONNEMENT




AERODROME CHART



CARTE D'AÉRODROME



AERODROME CHART



68 30

68 29.5

48 29

48 29

48 28.5

48 28.5

68 30

68 29.5

ANR 18 NM

2012

ANNUAL RATE OF CHANGE 8° E

DEPARTURE CLIMB RATE V/V (FPM)

GROUND SPEED	90	120	140	160	180	200	250	300
210 FT/NM	320	420	490	560	630	700	880	1050

4600 x 150

CYXK

N48 28.66

W68 29.78

AS

066°

ELEV 75

AS

246°

ELEV 71

* DEPARTURE PROCEDURE

Rwy 07 - ½ - Climb hdg 066° to 1700 BPOC.

Note: Trees to 121 ASL abeam departure end of rwy, 370' LEFT of rwy centreline and trees to 91' ASL abeam departure end of rwy, 260' RIGHT of rwy centreline.

Rwy 25 - ½ - Requires a minimum climb gradient of 210 ft/NM to 1600. Climb hdg 246° to 800 BPOC.

Note: Road to 90 ASL aprx 150' past departure end of rwy, 540' LEFT of rwy centreline.

or

SPEC VIS - Climb in visual conditions to cross the aprt at or above 1400 BPOC.

TAKE-OFF MINIMA

Rwys 07, 25: *

SCALE IN FEET

1000 0 1000


Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 7 AUG 25

CYXK


					RADIO Mont-Joli – 122.1		CTR Montreal – 134.65 227.2	
DIST DÉCLARÉES		07	25			MF*		
TORA	4600	4600						
TODA	4600	4600						
ASDA	4600	4600						
LDA	4600	4600						



CARTE D'AÉRODROME

CYXK

AERODROME CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 11 JUL 24


CYRI

CARTE D'AÉRODROME



AERODROME CHART

			● RADIO Rouyn – 122.2			RADIO Quebec – 123.55 5680		
			● TFC – 122.2			MF		
DECL DIST	16	34						
TORA	5000	5000						
TODA	5495	5815						
ASDA	5000	5000						
LDA	5000	5000						



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

CYRJ

EFF 26 DEC 24


CARTE D'AÉRODROME

				☑ RADIO Rouyn – 122.2 ☑ TFC – 122.2		RADIO Quebec – 123.55 5680 MF	
DIST DÉCLARÉES	16	34					
TORA	5000	5000					
TODA	5495	5815					
ASDA	5000	5000					
LDA	5000	5000					



Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

AERODROME CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 1 FEB 18

CYUY


CARTE D'AÉRODROME



Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

HELIPORT CHART

AUTO Charlevoix – 122.55 (En)				TFC – 123.2		ATF*		CTR Montreal – 125.1 299.6	
DECL DIST									
TORA									
TODA									
ASDA									
LDA									




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

HELIPORT CHART

CSG9

EFF 31 OCT 24

CARTE D'HÉLIPORT




Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

CARTE D'HÉLIPORT

CSG9

EFF 31 OCT 24

AERODROME CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART


EFF 20 FEB 25

CYZG

CARTE D'AÉRODROME




AWOS – 124.6 (En) 127.5 (Fr)				TFC – 122.2		RADIO Quebec – 123.47 126.7	
DECL DISTS	17	35					
TORA	5002	5002					
TODA	5986	5527					
ASDA	5002	5002					
LDA	5002	5002					



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

CARTE D'AÉRODROME



Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

CARTE D'AÉRODROME


EFF 27 JAN 22

CYKL

SEPT-ÎLES, QC
CYZV

AERODROME CHART

					RADIO – 118.1		CTR Montreal – 135.55 381.9 RADIO Quebec – 123.27	
					MF			
DECL DIST	09	27	13	31				
TORA	6523	6523	5771	5771				
TODA	7507	7507	6755	6755				
ASDA	6523	6523	5771	5771				
LDA	6523	6523	5771	5771				



		RUNWAY LEVEL OF SERVICE	
RVO		LVO	
RWY 09: RVR 1200 RWY 27: (¼ sm)		NOT AUTHORIZED	
TAKE-OFF MINIMA		SCALE IN FEET	
Rwys 09; 13; 27; 31: ★			

AERODROME CHART

EFF 2 OCT 25

CYZV

CYZV-AD

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

CARTE D'AÉRODROME

66 16.5 66 15.5

DEC 18° N
2024

VARIATION
ANNUELLE DE 10' E

ALT 170

127°

5771

CYZV
N50 13.40
W66 15.94

6523 x 150

086°

ALT 165

257'

FSS

ALT 174

307°

266°

ALT 174

AO

AD

50 13.8

50 13.1

50 13.1

66 16.5 66 15.5

*** PROCÉDURE DE DÉPART**

Piste 09 - ½
Note: Arbres jusqu' à 243 ASL aprx 0.2 NM passé l'extrémité de la piste de départ, 200' à GAUCHE et à DROITE de l'axe de piste. Tour jusqu'à 190 ASL aprx 0.2 NM passé l'extrémité de la piste de départ, 50' à GAUCHE de l'axe de piste.

Piste 13 - ½
Note: Arbres jusqu'à 240 ASL aprx 0.2 NM passé l'extrémité de la piste de départ, 500' à GAUCHE et à DROITE de l'axe de piste.

Piste 27 - ½
Note: Arbres jusqu'à 190 ASL aprx. 0.2 NM passé l'extrémité de la piste de départ, 550' à DROITE de l'axe de piste.

Piste 31 - ½
Note: Arbres jusqu'à 226 ASL aprx. 0.2 NM passé l'extrémité de la piste de départ, 400' à GAUCHE et à DROITE de l'axe de piste.

NIVEAU DE SERVICE DE LA PISTE	
RVO	LVO
PISTE 09: RVR 1200 PISTE 27: (¼ sm)	NON AUTORISÉ
MINIMUM DE DÉCOLLAGE	ÉCHELLE EN PIEDS
Pistes 09; 13; 27; 31: *	

Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

PARKING AREAS (PROCEDURES)

Parking spaces	Maximum wingspan (metres)	Maximum length (metres)	Restrictions	Largest aircraft allowed	Other aircraft allowed
RESERVED GATES					
1, 2, 3, 4	28.4	32.8	• Nose southwest • Mandatory pushback • Screened passengers primarily at parking spaces 1, 2 and 3 • Screened or unscreened passengers at parking space 4 • If aircraft at parking space 2, then parking space 1B is closed	DHC-8-Q400	DHC-8-300 Saab 340 B1900C B1900D
5	17.7	17.7	• Nose southwest • Mandatory pushback • Screened or unscreened passengers	B1900	B1900C B1900D
1A	35.8	39.5	• Screened passengers only • Arrival by twy A and B • Mandatory pushback	B737-800	All B737
1B	35.8	39.5	• No aircraft allowed at aircraft parking space 2 • Screened passengers only • Arrival by twy C and D • Mandatory pushback	B737-800	All B737
EAST PARKING - General Aviation CTC OPR 418-962-8211					
6, 8	17.7	17.7	• Nose to east or west with a preference facing west to facilitate pedestrian walking path	B1900D	King Air B200 B1900C C550
7	27.5	25.7	• Nose to east or west with a preference facing west to facilitate pedestrian walking path	DHC-8-300	
9	27.5	25.7	• Nose to east or west with a preference facing west to facilitate pedestrian walking path • Priority for Medevac at parking space	DHC-8-300	DHC-8-200 B1900D Challenger 605
10	17	18	• Nose to east or west with a preference facing west to facilitate pedestrian walking path	B1900C	King Air B200
12	17	18	• Nose to west	B1900C	King Air B200

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

PARKING AREAS (PROCEDURES)

CYZV

PARKING AREAS (PROCEDURES)

Parking spaces	Maximum wingspan (metres)	Maximum length (metres)	Restrictions	Largest aircraft allowed	Other aircraft allowed
WEST PARKING					
W1	40.4	34.4	• Power out is permitted for 737 only when parking spaces W2, 1, 1A and 1B are unoccupied • Power out is permitted for propeller when parking space W2 is unoccupied	B737-300	DHC-8-Q400 B1900
W2	40.4	34.4	• Reserved to C130 Hercules • Power out is permitted when parking space W1 is unoccupied	B737-800	C130 Hercules DHC-8-Q400
NORTH PARKING - General Aviation CTC OPR 418-962-8211					
Other parking spaces available in self-service Possible up to DHC-8-300 when parked at a 45° angle				DHC-8-300	


Notes:

- The movement guide line on the main apron is restricted to aircraft with wingspan of 36 m or less;
- The Hercules is not permitted on twy C and D; after landing on rwy 09, backtrack to twy A;
- If impossible to park according to marking, because operational constraints (wind etc.), use the NORTH parking (GENERAL AVIATION);
- North parking (GENERAL AVIATION) limited to the aircraft whose tail does not exceed:
 - 17 m when the tail is on the edge of the traffic area, or
 - 12 m when the tail is parked along the edge of the apron.

ATTENTION: Parking inside the perimeter only (white full lines) in order not to infringe the zoning of the runway, the taxiway or the parking spaces.

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

PARKING AREAS



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

PARKING AREAS

EFF 26 DEC 24

AIRES DE STATIONNEMENT (PROCÉDURES)

Postes de stationnement	Envergure maximale (mètre)	Longueur maximale (mètre)	Restrictions	Plus gros appareil permis	Autres appareils permis
BARRIÈRES RÉSERVÉES					
1, 2, 3, 4	28,4	32,8	• Nez sud-ouest • Refoulement obligatoire • Passagers fouillés principalement aux postes 1, 2 et 3 • Passagers fouillés ou non fouillés au poste 4 • Si appareil au poste 2 alors poste 1B fermé	DHC-8-Q400	DHC-8-300 Saab 340 B1900C B1900D
5	17,7	17,7	• Nez sud-ouest • Refoulement obligatoire • Passagers fouillés ou non fouillés	B1900	B1900C B1900D
1A	35,8	39,5	• Passagers fouillés seulement • Arrivée par twy A et B • Refoulement obligatoire	B737-800	Tous les B737
1B	35,8	39,5	• Aucun appareil autorisé au poste de stationnement 2 • Passagers fouillés seulement • Arrivée par twy C et D • Refoulement obligatoire	B737-800	Tous les B737
STATIONNEMENT EST - Aviation Générale - Pour réservation appeler EXP 418-962-8211					
6, 8	17,7	17,7	• Nez à l'est ou à l'ouest • Préférentiel nez à l'ouest pour le cheminement piétonnier	B1900D	King Air B200 B1900C C550
7	27,5	25,7	• Nez à l'est ou à l'ouest • Préférentiel nez à l'ouest pour le cheminement piétonnier	DHC-8-300	
9	27,5	25,7	• Nez à l'est ou à l'ouest • Préférentiel nez à l'ouest pour le cheminement piétonnier • Priorité au Medevac	DHC-8-300	DHC-8-200 B1900D Challenger 605
10	17	18	• Nez à l'est ou à l'ouest • Préférentiel nez à l'ouest pour le cheminement piétonnier	B1900C	King Air B200
12	17	18	• Nez à l'ouest	B1900C	King Air B200

Source des données aéronautiques civiles pour le Canada : ©2025 NAV CANADA Tous droits réservés

AIRES DE STATIONNEMENT (PROCÉDURES)

CYZV

AIRES DE STATIONNEMENT (PROCÉDURES)

Postes de stationnement	Envergure maximale (mètre)	Longueur maximale (mètre)	Restrictions	Plus gros appareil permis	Autres appareils permis
STATIONNEMENT OUEST					
W1	40,4	34,4	- Sortie sur pouvoir autorisé (power out) pour les B737 seulement si les postes W2, 1, 1A et 1B sont inoccupés - Sortie sur pouvoir autorisé (power out) pour les aéronefs à hélices si le poste W2 est inoccupé	B737-300	DHC-8-Q400 B1900
W2	40,4	34,4	- Réservé à C130 Hercules - Sortie sur pouvoir autorisé (power out) si le poste W1 est inoccupé	B737-800	C130 Hercules DHC-8-Q400
STATIONNEMENT NORD - Aviation Générale CTC EXP 418-962-8211					
Autres espaces disponibles en libre-service Possible jusqu'à DHC-8-300 lorsque stationné à angle 45°				DHC-8-300	


Notes :

- La ligne de guidage sur l'aire de trafic principale est restreinte aux appareils de 36 m ou moins d'envergure;
- Le Hercule n'est pas autorisé sur twy C et D; après atterrissage piste 09, circulation à rebours jusqu'au twy A;
- Si impossible de stationner selon le marquage, à cause de contraintes opérationnelles (vent etc.), utiliser le stationnement nord (AVIATION GÉNÉRALE);
- Stationnement nord (AVIATION GÉNÉRALE) restreint aux aéronefs dont l'empennage ne dépasse pas :
 - 17 m lorsque la queue est en bordure de l'aire de trafic, ou
 - 12 m lorsque la queue est stationnée en bordure nord du tablier.

ATTENTION : Stationnement à l'intérieur du périmètre (lignes blanches) seulement afin de ne pas enfreindre le zonage de la piste, de la voie de circulation ou les postes de stationnement.


Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

AIRES DE STATIONNEMENT



AERODROME CHART

AWOS – 126.25 (En) 128.15 (Fr)		UNICOM – 123.5				CTR Montreal – 132.55			
						MF			
DECL DIST	13	31							
TORA	5901	5901							
TODA	6885	6885							
ASDA	5901	5901							
LDA	5901	5901							




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 21 MAR 24

CYSC


CARTE D'AÉRODROME



CARTE D'AÉRODROME

EFF 21 MAR 24

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 10 SEP 20

CYIF

CARTE D'AÉRODROME

58 40.0 58 39.5 58 39.0

51 13.0 51 13.0

51 12.5 51 12.5

58 40.0 58 39.5 58 39.0

ALT 13

190°

(P2)

4595 x 100

CYIF
N51 12.59
W58 39.44

ALT 19

100°

(P2)

100

TAUX DE MONTÉE DE DÉPART V/V (FPM)

VITESSE SOL	90	120	140	160	180	200	250	300
360 pieds/NM	540	720	840	960	1080	1200	1500	1800

MINIMUM DE DÉCOLLAGE

Pistes 01, 19: ★

ÉCHELLE EN PIEDS

1000 0 1000

VARIATION ANNUELLE DE 13' E

DEC 19° N 2020

★PROCÉDURE DE DÉPART

Piste 01 - ½ - Requiert une pente de montée minimale de **360** pi/NM jusqu'à **700**. AUCUN virage à DROITE en dessous de **1200**.

Note: Arbres jusqu'à 45 ASL par le travers de l'extrémité de départ de la piste, à GAUCHE et à DROITE de l'axe de piste.

ou


SPEC VIS - Monter visuel au-dessus de l'aéroport jusqu'à **1200** BPOC.

Piste 19 - ½ - Monter sur cap **190°** jusqu'à **900** BPOC.


Note: Arbres jusqu'à 134 ASL par le travers de l'extrémité de départ de la piste, à GAUCHE et à DROITE de l'axe de piste.

Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

					UNICOM – 123.2		RADIO Quebec – 123.47	
		ATF						
DECL DISTS	10	28						
TORA	4494	4494						
TODA	5478	5478						
ASDA	4494	4494						
LDA	4494	4494						



CARTE D'AÉRODROME



Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés


CARTE D'AÉRODROME

EFF 23 FÉV 23

CTA4

AERODROME CHART

AUTO – 122.02				TFC – 122.8		CTR Montreal – 134.65 227.2	
						ATF	
DECL DIST	14	32					
TORA	3934	3934					
TODA	3934	3934					
ASDA	3934	3934					
LDA	3934	3934					




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 11 JUL 24

CYSZ

CARTE D'AÉRODROME




CARTE D'AÉRODROME

EFF 11 JUIL 24

CYSZ

AERODROME CHART

AUTO – 123.17				UNICOM – 122.15 (AU)		CTR Montreal – 132.35	
						MF	
DECL DIST	06	24					
TORA	5112	5112					
TODA	5299	6096					
ASDA	5112	5112					
LDA	5112	5112					




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 15 JUN 23


CYSG

CARTE D'AÉRODROME



AERODROME CHART

						TML Montreal – 125.15 268.3	
				TFC – 123.2		MF	
DECL DIST	02	20					
TORA	3823	3823					
TODA	3823	3823					
ASDA	3823	3823					
LDA	3397	3469					




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 12 JUN 25

CSU3

CARTE D'AÉRODROME




CARTE D'AÉRODROME

CSU3

EFF 12 JUIN 25

AERODROME CHART




AERODROME CHART

EFF 31 OCT 24


CYJN

CYJN



AERODROME CHART

				APRT RADIO – 122.1 TFC – 122.1		MF*			
DECL	DISTS	05	23						
TORA		3519	3519						
TODA		3519	3519						
ASDA		3519	3519						
LDA		3519	3519						




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 27 JAN 22

CYTQ

CARTE D'AÉRODROME




Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

CARTE D'AÉRODROME


EFF 27 JAN 22

CYTQ

AERODROME CHART




CARTE D'AÉRODROME



AERODROME CHART

MET – 120.27 (En) 124.82 (Fr)		UNICOM – 122.35				CTR Montreal – 128.22			
DECL DIST		05	23						
TORA		9006	9006						
TODA		9990	9990						
ASDA		9006	9006						
LDA		9006	9006						



AERODROME CHART


EFF 2 OCT 25

CYRQ

TROIS-RIVIÈRES, QC
CYRQ

CYRQ

MET – 124.82 (Fr) 120.27 (Ang)					UNICOM – 122.35		CTR Montreal – 128.22	
DIST DÉCLARÉES	05	23				MF		
TORA	9006	9006						
TODA	9990	9990						
ASDA	9006	9006						
LDA	9006	9006						



Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés


CARTE D'AÉRODROME

CYRQ

EFF 2 OCT 25

CYRQ-AD

AERODROME CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART


EFF 21 MAR 24

CYMU


CARTE D'AÉRODROME



AERODROME CHART



CARTE D'AÉRODROME



PARKING AREAS (PROCEDURES)

Parking spaces	Maximum wingspan (metres)	Maximum length (metres)	Restrictions	Largest aircraft allowed	Other aircraft allowed
1	38.1	47.3	• Medevac priority	B757-200	Other D code aircraft
1A	25.9	22.3	• Medevac priority	DHC-8-100	B1900D B200 B100
2	35.8	39.5	• Medevac priority	B737-800	B737-200 DHC-8-400 DHC-8-300 DHC-8-100 CV580 JS32
2A	17.6	17.6	• Medevac priority	B1900D	B100 B200
2B	35.8	39.5	• Regular flights only • Charters flights authorized to drop or pick passengers only. • Use 1, 1A, 2, 2A, R1, R2, R3, R4 for longer parking duration.	B737-800	DHC-8-400 DHC-8-300 DHC-8-100 CV580 JS32 B1900D B200 B100
3	35.8	39.5	• Regular flights only • Charters flights authorized to drop or pick passengers only. • Use 1, 1A, 2, 2A, R1, R2, R3, R4 for longer parking duration.	B737-800	B737-200 DHC-8-400 DHC-8-300 DHC-8-100 CV580 JS32 B1900D B200 B100
3A	25.9	22.3	• Regular flights only • Charters flights authorized to drop or pick passengers only. • Use 1, 1A, 2, 2A, R1, R2, R3, R4 for longer parking duration.	DHC-8-100	JS32 B1900D B200 B100
4	28.4	30.5	• Cargo or mining charters flight priority	B737-200	DHC-8-400 DHC-8-300 DHC-8-100 CV580 JS32 B1900D B200 B100

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

PARKING AREAS (PROCEDURES)


PARKING AREAS (PROCEDURES)

Parking spaces	Maximum wingspan (metres)	Maximum length (metres)	Restrictions	Largest aircraft allowed	Other aircraft allowed
5	28.4	30.5	• Cargo or mining charters flight priority	B737-200	DHC-8-400 DHC-8-300 DHC-8-100 CV580 JS32 B1900D B200 B100
5A	17.6	17.6	• Cargo or mining charters flight priority	B1900D	B100 B200
5B	17.6	17.6		B1900D	B100 B200
R1	14.0	12.0		B100	smaller
R2	14.0	12.0		B100	smaller
R3	14.0	12.0		B100	smaller
R4	14.0	12.0		B100	smaller

Note: If parking impossible along markings due operational constraints (wind, etc.), use parking areas 1, 1A, 2, 2A.

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

PARKING AREAS



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

PARKING AREAS

EFF 23 FEB 23

PARKING AREAS

Aircraft Parking Position

Position	Coordinates	Position	Coordinates
1	480308.23N 0774710.98W	3A	480310.86N 0774712.12W
1A-1	480307.64N 0774711.31W	4	480312.63N 0774712.54W
1A-2	480306.77N 0774710.62W	5	480314.60N 0774713.11W
2-1	480307.75N 0774711.37W	5A	480314.52N 0774713.04W
2-2	480307.68N 0774711.21W	5B	480314.96N 0774712.15W
2A	480308.20N 0774710.46W	R1	480315.91N 0774713.64W
2B	480308.97N 0774711.72W	R2	480316.01N 0774712.84W
3-1	480310.35N 0774712.12W	R3	480316.12N 0774712.03W
3-2	480310.23N 0774711.85W	R4	480316.22N 0774711.23W

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

PARKING AREAS

EFF 23 FEB 23

CYVO

AIRES DE STATIONNEMENT (PROCÉDURES)

Postes de stationnement	Envergure maximale (mètre)	Longueur maximale (mètre)	Restrictions	Plus gros avions permis	Autres avions permis
1	38.1	47.3	• Priorité Medevac	B757-200	Other D code aircraft
1A	25.9	22.3	• Priorité Medevac	DHC-8-100	B1900D B200 B100
2	35.8	39.5	• Priorité Medevac	B737-800	B737-200 DHC-8-400 DHC-8-300 DHC-8-100 CV580 JS32
2A	17.6	17.6	• Priorité Medevac	B1900D	B100 B200
2B	35.8	39.5	• Vols réguliers uniquement • Vols nolisés autorisés à déposer ou à prendre des passagers uniquement. • Utilisez 1, 1A, 2, 2A, R1, R2, R3, R4 pour une durée de stationnement prolongée.	B737-800	DHC-8-400 DHC-8-300 DHC-8-100 CV580 JS32 B1900D B200 B100
3	35.8	39.5	• Vols réguliers uniquement • Vols nolisés autorisés à déposer ou à prendre des passagers uniquement. • Utilisez 1, 1A, 2, 2A, R1, R2, R3, R4 pour une durée de stationnement prolongée.	B737-800	B737-200 DHC-8-400 DHC-8-300 DHC-8-100 CV580 JS32 B1900D B200 B100
3A	25.9	22.3	• Vols réguliers uniquement • Vols nolisés autorisés à déposer ou à prendre des passagers uniquement. • Utilisez 1, 1A, 2, 2A, R1, R2, R3, R4 pour une durée de stationnement prolongée.	DHC-8-100	JS32 B1900D B200 B100
4	28.4	30.5	• Priorité aux vols nolisés cargo ou miniers	B737-200	DHC-8-400 DHC-8-300 DHC-8-100 CV580 JS32 B1900D B200 B100

Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

AIRES DE STATIONNEMENT (PROCÉDURES)

EFF 5 SEP 24


AIRES DE STATIONNEMENT (PROCÉDURES)

Postes de stationnement	Envergure maximale (mètre)	Longueur maximale (mètre)	Restrictions	Plus gros avions permis	Autres avions permis
5	28.4	30.5	• Priorité aux vols nolisés cargo ou miniers	B737-200	DHC-8-400 DHC-8-300 DHC-8-100 CV580 JS32 B1900D B200 B100
5A	17.6	17.6	• Priorité aux vols nolisés cargo ou miniers	B1900D	B100 B200
5B	17.6	17.6		B1900D	B100 B200
R1	14.0	12.0		B100	smaller
R2	14.0	12.0		B100	smaller
R3	14.0	12.0		B100	smaller
R4	14.0	12.0		B100	smaller

Note : Si impossible de stationner selon le marquage, à cause de contraintes opérationnelles (vent etc.), utiliser les postes de stationnement 1, 1A, 2, 2A.

Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

AIRES DE STATIONNEMENT



AIRES DE STATIONNEMENT

EFF 23 FÉV 23

CYVO


AIRES DE STATIONNEMENT

Poste de stationnement d'aéronef

Position	Coordonnées	Position	Coordonnées
1	480308.23N 0774710.98W	3A	480310.86N 0774712.12W
1A-1	480307.64N 0774711.31W	4	480312.63N 0774712.54W
1A-2	480306.77N 0774710.62W	5	480314.60N 0774713.11W
2-1	480307.75N 0774711.37W	5A	480314.52N 0774713.04W
2-2	480307.68N 0774711.21W	5B	480314.96N 0774712.15W
2A	480308.20N 0774710.46W	R1	480315.91N 0774713.64W
2B	480308.97N 0774711.72W	R2	480316.01N 0774712.84W
3-1	480310.35N 0774712.12W	R3	480316.12N 0774712.03W
3-2	480310.23N 0774711.85W	R4	480316.22N 0774711.23W

Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

AWOS – 122.17		UNICOM – 123.35				CTR Montreal – 132.35		
						ATF		
DECL DIST	06	24						
TORA	5530	5530						
TODA	5530	5530						
ASDA	5530	5530						
LDA	5530	5530						




AERODROME CHART

EFF 12 JUN 25

CSR3

CARTE D'AÉRODROME



CARTE D'AÉRODROME


EFF 12 JUIN 25

CSR3

CYKQ-AD

WASKAGANISH, QC
CYKQ

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 25 APR 19

CYKQ

CYKQ-AD

CARTE D'AÉRODROME



▲ DÉCLIVITÉ

2016

VARIATION ANNUELLE DE 5' E

AS 062°

ALT 78

3511 x 100

gravier

CYKQ
N51 28.40
W78 45.50

AS 242°

ALT 77

* PROCÉDURE DE DÉPART

Piste 06 - ½

Note: Arbres jusqu'à 145 ASL passé l'extrémité de la piste de départ.

Piste 24 - ½

Note: Arbres jusqu'à 129 ASL passé l'extrémité de la piste de départ.


CARTE D'AÉRODROME

EFF 25 AVR 19

WEMINDJI ,QC
CYNOC

CYNC


● APRT RADIO – 122.1
● TFC – 122.1



CYNC

CYNC-AD

CARTE D'AÉRODROME




Source des données aéronautiques civiles pour le Canada : © 2025 NAV CANADA Tous droits réservés

CARTE D'AÉRODROME

CYNC

EFF 14 JUL 22


AERODROME CHART



AERODROME CHART

CZBF

AERODROME CHART




AERODROME CHART

EFF 14 JUL 22

CCE4

AERODROME CHART

MET – 128.75				TFC – 122.8		ATF*			
DECL DIST	08	26							
TORA	3937	3937							
TODA	3937	3937							
ASDA	3937	3937							
LDA	3937	3937							




AERODROME CHART

EFF 3 NOV 22

CYCA

AERODROME CHART




AERODROME CHART

EFF 20 FEB 25

CYCL

AERODROME CHART

AWOS Mary's Harbour – 122.55				TFC – 122.8		ATF*			
DECL DIST	09	27							
TORA	2502	2502							
TODA	2502	2502							
ASDA	2502	2502							
LDA	2502	2502							




AERODROME CHART

EFF 21 MAR 24

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 2 OCT 25


CYYG

AERODROME CHART

AWOS – 118.95				TFC – 123.5		CTR Gander – 126.02	
				ATF			
DECL DIST	13	31					
TORA	5500	5500					
TODA	5500	5500					
ASDA	5500	5500					
LDA	5500	5500					



RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 13, 31: (¼sm)	NOT AUTHORIZED
TAKE-OFF MINIMA	
Rwys 13; 31: *	



AERODROME CHART


EFF 27 JAN 22

CZUM

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

				TFC – 123.2		CTR Gander – 132.1 289.4	
				ATF			
DECL DIST	07	25					
TORA	3935	3935					
TODA	3935	3935					
ASDA	3935	3935					
LDA	3935	3935					




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 26 DEC 24

CCZ3

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 17 APR 25

CCQ3

DEER LAKE, NL
CYDF

AERODROME CHART

DECL DIST		07		25													
TORA		8005		8005													
TODA		8989		8989													
ASDA		8005		8005													
LDA		8005		8005													

RADIO - 122.2 239.6
 CTR Gander - 134.6
 MF

GROUND SPEED	90	120	140	160	180	200	250	300
290 FT/NM	440	580	680	780	870	970	1210	1450

*** DEPARTURE PROCEDURE**
Rwy 07 - ½ - NO LEFT turn below **1400**.
Note: Trees to 138 ASL aprx 0.1 NM past departure end of rwy, 550' LEFT and RIGHT of rwy centreline.

Rwy 25 - ½ - Requires a minimum climb gradient of **290 ft/NM** to **1900**. Climb rwy hdg to **1200 BPOC**.

SPEC VIS - Climb in visual conditions to cross the aprt at or above **1300 BPOC**
Note: Trees to 117 ASL aprx 0.1 NM past departure end of rwy, 600' LEFT and RIGHT of rwy centreline.

RUNWAY LEVEL OF SERVICE

RVO	LVO
RWY 07, 25: (¼ sm)	NOT AUTHORIZED

TAKE-OFF MINIMA

Rwys 07, 25: ★		SCALE IN FEET

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 5 SEP 24

CYDF


CYDF-AD

CYID-AD

DIGBY MUNICIPAL AIRPORT, NS
CYID

AERODROME CHART

		UNICOM – 122.8				CTR Moncton – 123.9			
		ATF							
DECL DIST	06	24							
TORA	3957	3957							
TODA	3957	3957							
ASDA	3957	3957							
LDA	3957	3957							



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 27 JAN 22

CYID

CYID-AD

AERODROME CHART




AERODROME CHART

CYES

AERODROME CHART

				TFC – 123.2		CTR Gander – 132.1	
DECL DIST		06	24			ATF	
TORA		4008	4008				
TODA		4008	4008				
ASDA		4008	4008				
LDA		4008	4008				




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 31 OCT 24

CCP2

AERODROME CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

FREDERICTON INTL, NB
CYFC

AERODROME CHART

ATIS – 127.55 AWOS – 127.55		GND – 121.7			TWR – 119.0 RADIO Saint John – 119.0		CTR Moncton – 124.3 270.8	
DECL DISTS		09	27	15	33	MF		
TORA	8005	8005	7000	7000				
TODA	8399	8530	7984	7394				
ASDA	8005	8005	7000	7000				
LDA	8005	8005	7000	7000				



RVO		LVO	
RWY 09: RVR 1200 RWY 15, 27, 33: (1/4 sm)		NOT AUTHORIZED	
TAKE-OFF MINIMA		SCALE IN FEET	
Rwys 09;15;27;33: ★			

AERODROME CHART

EFF 2 OCT 25

CYFC

CYFC-AD

GANDER INTL, NL
CYQX

ATIS - 124.8		GND - 121.9 275.8		TWR - 118.1 236.6		DEP - 132.1	
DECL DIST	03	21	13	31			
TORA	10200	10200	8900	8900			
TODA	10607	11184	9527	9884			
ASDA	10500	10200	8900	8900			
LDA	10200	10200	8900	8900			

*** DEPARTURE PROCEDURE**

Rwy 03 - 1/2
Note: Trees to 518 ASL aprx 0.2 NM past departure end of rwy.

Rwy 13 - 1/2
Note: Trees to 506 ASL aprx 0.1 NM past departure end of rwy, 480' LEFT of rwy centreline.

Rwy 21 - 1/2
Note: Trees to 472 ASL aprx 0.1 NM past departure end of rwy.

Rwy 31 - 1/2
Note: Trees to 538 ASL aprx 0.2 NM past departure end of rwy.

HOT SPOTS
 HS 1 - Twy A & Twy C Intxn.
 Flight school and heli tlc congestion point.


SCALE IN FEET
 2000 0 2000

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

CYQX

CYQX-AD

PARKING AREAS



PARKING AREAS


EFF 26 DEC 24

CYQX

AERODROME CHART (DND)

ATIS – 128.1 340.8		CLNC DEL – 118.1 336.5		TWR – 119.1 236.6		● TML – 119.5 267.1	
		GND – 121.9 275.8				● CTR Gander – 120.4 267.1	

DECL DIST	08	26	15	33				
TORA	11052	11052	9584	9584				
TODA	11052	11052	9584	9584				
ASDA	11202	12052	9724	9734				
LDA	11052	11052	9584	9584				




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART (DND)

EFF 5 OCT 23

AERODROME CHART

AUTO - 122.17				TFC - 123.2		CTR Moncton - 124.3	
DECL DIST		06	24			ATF	
TORA		3009	3009				
TODA		3009	3009				
ASDA		3009	3009				
LDA		3009	3009				



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART


EFF 3 NOV 22

CCN2

GREENWOOD, NS
CYZX

AERODROME CHART (DND)

ATIS – 128.85 244.3 GND – 133.75 289.4		CLNC DEL – 128.02 283.9		TWR – 119.5 324.3		TML – 120.6 335.9	
DECL DIST	08	26	12	30			
TORA	7999	7999	7999	7999			
TODA	7999	7999	7999	7999			
ASDA	7999	7999	7999	7999			
LDA	7999	7999	7999	7999			



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART (DND)

EFF 21 MAR 24

CYZX

CYZX-AD

● ATIS - 128.85 244.3 CLNC DEL - 128.02 283.9
GND - 133.75 289.4

VAR 17° W 2022
ANNUAL RATE OF CHANGE 8" E

LEGEND
⑩.....Parking positions
R.....Taxiways
8.....Hangar numbers

INS/ONS/VLF WAYPOINTS
15, 16 - N44 59.2 W64 54.5
17, 18 - N44 58.9 W64 54.9
19, 20 - N44 59.0 W64 54.9
22 - N44 59.1 W64 54.9
24, 25 - N44 58.9 W64 54.7
26 - N44 59.1 W64 54.8
27, 28 - N44 59.1 W64 54.7
29, 30 - N44 59.2 W64 54.7
32 - N44 59.2 W64 54.6
*34, 35, 36 - N44 59.0 W64 54.7
*37 - N44 59.1 W64 54.8
*38, 39 - N44 59.1 W64 54.7
* - inside hangar

14 HGR PARKING SPOTS
50, 51 - N44 58.9 W64 54.6
52, 53 - N44 58.9 W64 54.5
54 - N44 58.8 W64 54.5
55 - N44 58.9 W64 54.4

INS/ONS/VLF WAYPOINT
33 - N44 58.8 W64 55.8


INS/ONS/VLF WAYPOINTS
1, 2, 3 - N44 59.2 W64 54.3
*4 - N44 59.2 W64 54.3
*5, 6, 7
*8, 9 - N44 59.2 W64 54.2
13 - N44 59.1 W64 54.1
14 - N44 59.1 W64 53.9
40 - N44 59.2 W64 54.1
41, 42, 43
44, 45, 46 - N44 59.2 W64 54.1
E/12 Hgr - N44 59.2 W64 53.9
* - inside hangar

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

CHQE-HP

HALIFAX (QE II HEALTH SCIENCES CENTRE), NS
CHQE

HELIPORT CHART




HELIPORT CHART

CHQE

EFF 7 AUG 25

CHQE-HP

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 2 OCT 25

CYHZ

LOW VISIBILITY PROCEDURES

Low Visibility Procedures (RVR less than 1200 ft to 600 ft)**Application**

These procedures apply to ground movements of aircraft arriving and departing under low visibility conditions. Arrivals and departures below RVR 600 are not authorized. When weather conditions indicate visibility below RVR 1200 is imminent, procedures will be implemented restricting aircraft and vehicle operations on the manoeuvring area. The following message will be added to the ATIS broadcast: "LOW VISIBILITY PROCEDURES IN EFFECT".

General

The approved taxi route from the Apron is shown on the Low Visibility Taxi Chart. Taxiway centreline lights will be illuminated in taxiway A, G, F, across Rwy 14, taxiway L to the stop bar.

Departures

When low visibility procedures are in effect, Rwy 23 is the only runway certified for low visibility operations.

Take-off roll cannot commence prior to the displaced threshold location, where the runway is served by high intensity white runway edge lights.

Sequencing of Aircraft Ground Movements for Take-off

Pilots must follow instructions on Sequencing of Ground Movements for Take-Off as described in CAP GEN Operating Minima.

Do not call for taxi clearance until the reported RVR is a minimum of 600.

Runway Level of Service	
Rwy	Certification
23	RVR 600

Stop Bar/Guard Light System

Each taxiway/runway entrances onto Rwy 05/23 is equipped with a stop bar consisting of red inset lights. Also, installed on either side of the stop bars located at the taxiway entrances onto Rwy 05/23 there are yellow flashing runway guard lights (Wig Wags). When the red stop bar lights are illuminated, green lead on lights beyond the stop bar are extinguished. When ATC issues a clearance to proceed onto the runway, the red stop bar lights will be extinguished and the green lead on lights beyond the stop bar will be illuminated. The stop bar is reset automatically as the aircraft moves onto the runway.


AT NO TIME SHALL A PILOT CROSS AN ILLUMINATED RED STOP BAR**Arrivals**

Arrivals are permitted on Rwy 23 for approved operators down to RVR 600. Twy J and Twy B are the approved exit routes. Landing aircraft traversing to Aprons I, II or III must exit Rwy 23 on Twy B or Twy J.


LOW VISIBILITY TAXI CHART
(RVR LESS THAN 1200 TO 600 FT)

HALIFAX/STANFIELD INTL, NS
CYHZ

ATIS – 121.0	CLNC DEL – 123.95	TWR – 118.4 236.6
	GND – 121.9 275.8	



During Low Visibility Conditions	
Declared Distances	23
TORA	10139
TODA	10828



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


DE-ICING OPERATIONS

De-icing Operations

1. Ctc de-icing provider 30 min prior to dep if de-icing is rqrd. Notify de-icing provider of parking location, planned runway for dep and any special treatments prior to pushback: ICEMAN 122.950 OR 902-410-7748.
2. De-icing provider will assign de-ice pad and advise when ready.
3. DO NOT PUSH prior to assigned de-ice pad being ready.
4. To mitigate congestion on the APN, QUEUING for de-icing is NOT ACCEPTABLE.
5. Monitor Halifax GND 121.9 for all APN movement.
6. Follow instructions to designated de-ice pad.
7. Advise ICEMAN immediately once brakes set, aircraft configured and engines at idle.
8. After de-icing, configure aircraft for taxi, however, DO NOT MOVE AIRCRAFT.
9. Once instructed, contact Halifax GND 121.9 for taxi.

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

PARKING AREAS (APRON I)




PARKING AREAS (APRON I)

EFF 7 AUG 25

CYHZ

PARKING AREAS (APRON III)



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

PARKING AREAS (APRON III)

EFF 2 OCT 25

CYHZ

PARKING AREAS

Aircraft Parking Positions (APRON I and APRON III)

Position	Coordinates	Position	Coordinates
2A	445302.98N 0633052.10W	27A	445319.47N 0633053.96W
2B	445302.13N 0633052.82W	28	445320.86N 0633056.99W
2C	445301.48N 0633053.58W	38	445322.05N 0633059.23W
2D	445300.69N 0633053.64W	42	445323.13N 0633058.20W
2E	445300.44N 0633054.46W	46	445323.78N 0633057.09W
3	445304.04N 0633051.05W	46A	445324.28N 0633058.02W
5	445304.27N 0633049.25W	52	445313.84N 0633050.79W
6	445303.29N 0633048.01W	53	445316.87N 0633051.96W
7	445304.04N 0633047.06W	54	445318.43N 0633051.97W
10	445305.23N 0633047.89W	56	445319.62N 0633052.85W
12	445306.13N 0633049.44W	57	445319.79N 0633054.31W
12A	445305.77N 0633049.37W	57A	445319.47N 0633053.96W
14	445307.77N 0633049.44W	58	445320.86N 0633056.99W
15	445310.18N 0633049.62W	301	445200.49N 0633155.58W
16	445311.01N 0633049.87W	302	445202.77N 0633158.95W
18	445312.29N 0633050.58W	303	445204.43N 0633201.74W
20	445315.81N 0633051.21W	304	445206.75N 0633204.61W
22	445313.84N 0633050.79W	305	445210.05N 0633204.26W
23	445316.87N 0633051.96W	306	445212.05N 0633202.77W
24	445318.43N 0633051.97W	307	445215.83N 0633200.10W
26	445319.62N 0633052.85W	308	445217.05N 0633157.79W
27	445319.79N 0633054.31W		


Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

PARKING AREAS

EFF 7 AUG 25

CYHZ

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART


EFF 7 OCT 21

CYHO

CLH7-HP

LONG HARBOUR RIVER, NL
CLH7

HELIPORT CHART



HELIPORT CHART

EFF 30 JAN 20

CLH7

CLH7-HP

LONG POND, NL
CCX2

● ATIS St. John's - 128.0				TFC - 123.2		CTR Gander - 133.15	
DECL DISTS						ATF	
TORA							
TODA							
ASDA							
LDA							

CCX2
N47 30.98
W52 58.86
ELEV 42

NAR 17° N
2024
ANNUAL RATE
OF CHANGE 11° E

TAKE-OFF MINIMA
NOT ASSESSED


SCALE IN FEET
100 0 100

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

CCX2

CCX2-HP

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

CYFT

MARYS HARBOUR, NL
CYMH

AERODROME CHART

MET – 122.55				TFC – 122.8			ATF*	
DECL DISTS	11	29						
TORA	2545	2545						
TODA	2545	2545						
ASDA	2545	2545						
LDA	2545	2545						



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 26 DEC 24

CYMH

CYMH-AD

AERODROME CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 20 APR 23

CYCH

CYQM-AD
MONCTON/GREATER MONCTON ROMÉO LEBLANC INTL, NB
CYQM



AERODROME CHART
EFF 16 MAY 24

CYQM

CYQM-AD


Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

PARKING AREAS (Apron VIII)

ATIS – 128.65	APRON – 122.07 GND – 121.8 275.8
---------------	-------------------------------------

Note:
De-icing Apron VIII - Prior to pushback, broadcast intentions and monitor all movements on Apron Advisory 122.075. Proceed to De-icing pad.

Itinerant Aircraft wishing to use Apron VIII ctc Airport Security 506-856-5429 - 2hr PNR.




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

PARKING AREAS (Apron VIII)

EFF 16 MAY 24

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 7 OCT 21

CYDP


AERODROME CHART

				TFC – 122.8		CTR Gander – 135.4	
				ATF*			
DECL DIST	12	30					
TORA	2500	2500					
TODA	2500	2500					
ASDA	2500	2500					
LDA	2500	2500					




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART




AERODROME CHART

EFF 5 SEP 24

CYPD

AERODROME CHART

AWOS Mary's Harbour – 122.55				TFC – 122.8		ATF*			
DECL DIST	12	30							
TORA	2497	2497							
TODA	2497	2497							
ASDA	2497	2497							
LDA	2497	2497							




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 21 MAR 24

CCP4

AERODROME CHART




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 20 FEB 25

CCD4

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

CCZ2

EFF 20 APR 23

AERODROME CHART

AWOS – 118.2					TFC – 122.75		MF			
DECL DIST	11	29								
TORA	1500	1500								
TODA	1500	1500								
ASDA	1500	1500								
LDA	1500	1500								



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 17 APR 25

CSB2

AERODROME CHART

					RADIO – 118.5 236.6		CTR Moncton – 124.3 270.8	
					MF			
DECL DIST	05	23	14	32				
TORA	7201	7201	5100	5100				
TODA	7857	7726	5100	6084				
ASDA	7201	7201	5100	5100				
LDA	7004	7004	5100	5100				




RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 05, 23: RVR 1200 RWY 14, 32: (¼ sm)	RWY 05, 23: RVR 600
TAKE-OFF MINIMA	
Rwys 05;14; 23; 32:★	SCALE IN FEET 1000 0 1000 2000

AERODROME CHART

EFF 21 MAR 24

CYSJ

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

CDA5

EFF 17 APR 25

REDUCED/LOW VISIBILITY PROCEDURES

**REDUCED VISIBILITY PROCEDURES (RVR less than 2600 ft (1/2 sm) to 1200 ft (1/4 sm))
and LOW VISIBILITY PROCEDURES (RVR less than 1200 to 600 ft)****Application**

These procedures apply to ground movements of aircraft departing under reduced and low visibility conditions.

Departures below RVR 600 are not authorized.

When weather conditions indicate visibility below RVR 2600, procedures will be implemented restricting aircraft and vehicle operations on the movement area. The following message will be added to the advisory: "REDUCED VISIBILITY PROCEDURES IN EFFECT" or "LOW VISIBILITY PROCEDURES IN EFFECT"

General**REDUCED VISIBILITY TAXI ROUTES**

Taxi routes during reduced visibility operations are exclusive to the following routes:

1. Route 1 - Twy C, Rwy 14/32. For departure Rwy 05/23, continue Twy A to Rwy 05/23.
2. Route 2 - Twy I, Rwy 14/32. For departure Rwy 05/23, continue Twy A to Rwy 05/23.
3. Route 3 - Twy B, Rwy 14/32. For departure Rwy 05/23, continue Twy A to Rwy 05/23.

Aircraft restricted to one on the maneuvering area at any time during reduced visibility operations.

LOW VISIBILITY TAXI ROUTES

Taxi routes during low visibility operations are exclusive to the following routes:

1. Route 1 - Twy C, Rwy 14/32, Twy A - to Rwy 05/23.
2. Route 2 - Twy I, Rwy 14/32, Twy A - to Rwy 05/23.
3. Route 3 - Twy B, Rwy 14/32, Twy A - to Rwy 05/23.

Aircraft restricted to one on the maneuvering area at any time during low visibility operations.

When RVR falls below 600, movement of all aircraft ceases.

Rwy 14/32 will be used for taxiing purposes only during low visibility conditions.

DEPARTURES

Rwy 14/32 and Rwy 05/23 for departures in reduced visibility conditions.

Rwy 05/23 will be used for departures in low visibility conditions.

During RVOP/LVOP departure clearance or Pre-Taxi validation will not be given to any requesting aircraft if any other aircraft has been issued an approach or departure clearance until:

- either the arriving aircraft has landed and reported off the manoeuvring area or
- a departing aircraft is in contact with the Moncton Area Control Centre.

Take-Off roll cannot commence prior to the displaced threshold location where the runway is served by high intensity white runway edge lights.

Modified Declared Distances During RVOP/LVOP

RWY 05		RWY 23	
TORA	7004	TORA	7004
TODA	7660	TODA	7529
ASDA	7004	ASDA	7004

REDUCED/LOW VISIBILITY PROCEDURES

REDUCED/LOW VISIBILITY PROCEDURES

**REDUCED VISIBILITY PROCEDURES (RVR less than 2600 ft (1/2 sm) to 1200 ft (1/4 sm))
and LOW VISIBILITY PROCEDURES (RVR less than 1200 to 600 ft)****Sequencing of Ground Movements for Take-off**

Pilots must follow instructions on Sequencing of Ground Movements for Take-Off as described in CAP GEN Operating Minima.

All aircraft are to obtain an IFR clearance or Pre-Taxi validation through the Saint John FSS prior to taxiing from any apron at Saint John Airport and are required to use the designated taxi routes.

Departing aircraft taxiing from a hangar along Twy B during RVOP or LVOP are required to taxi via Twy B to Rwy 14/32, Twy A to Rwy 05/23.

Do not request IFR clearance or Pre-Taxi validation until the RVR is greater than 600.

Guard Light System

Yellow flashing runway guard lights (Wig Wags) are installed at the Twy A entrance onto Rwy 05/23, Twy B onto Rwy 14/32, and Twy C and Twy I onto Rwy 14/32. When the twy edge lights are illuminated, the guard lights are turned on.

ARRIVALS

Arrivals are permitted on all runways for RVR 2600 ft (1/2 sm) to 1200 ft (1/4 sm). Twy A, Rwy 14/32, Twy B or Twy C and Twy A, Rwy 14/32, Twy I are the approved exit routes in RVOP.

Arrivals are not authorized in LVOP conditions.

RUNWAY LEVEL OF SERVICE

RWY	Certification	RWY	Certification
05	RVR 600	14	¼ sm
23	RVR 600	32	¼ sm

Note: Departing aircraft taxiing from a private hangar will be advised that RVOP or LVOP conditions are in effect. FSS will maintain one-in and one-out movements and will request aircraft access the designated taxi route.

REDUCED/LOW VISIBILITY PROCEDURES


CYSJ

CYAY-AD

ST. ANTHONY, NL
CYAY

AERODROME CHART

AWOS – 118.65					RADIO Deer Lake – 122.3		CTR Gander – 133.0	
		MF						
DECL DIST	10	28						
TORA	4003	4003						
TODA	4987	4987						
ASDA	4003	4003						
LDA	4003	4003						



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

RUNWAY LEVEL OF SERVICE	
RVO	LVO
RWY 10, 28: (½sm)	NOT AUTHORIZED
TAKE-OFF MINIMA	
Rwy 10: ½ Rwy 28: ★	


AERODROME CHART

CYAY

EFF 15 JUN 23

CYAY-AD

AERODROME CHART



LOW VISIBILITY PROCEDURES

Low Visibility Procedures (RVR less than 1200 ft to 600 ft)**Application**

These procedures apply to ground movements of aircraft departing under low visibility conditions. Arrivals and departures below RVR 600 are not authorized. When weather conditions indicate visibility below RVR 1200 is imminent, procedures will be implemented restricting aircraft and vehicle operations on the manoeuvring area.

General**Low Visibility Taxi Routes**

Standard taxi routes are shown on the Low Visibility Taxi Chart, taxiway surfaces are painted with enhanced yellow and black centreline markings, in addition, taxiways B, C, G, H, J, M and Runway 16/34 are equipped with green centreline lights.

Airport Surface Detection Equipment (ASDE)

Ground radar is used to monitor the position of aircraft operating on the manoeuvring area, in the event of an ASDE failure, ATC will restrict low visibility operations to one aircraft on the manoeuvring area at a time.

Departures

When low visibility procedures are in effect, Runway 10/28 is the only runway certified for low visibility operations. Intersection takeoffs are not authorized.

Sequencing of Aircraft Ground Movements for Take-off

Do not request start, push-back or call for taxi clearance until the reported RVR is greater than:

Aircraft/Pilot Take-off minima	Minimum RVR for start
1200 RVR	1000 RVR
600 RVR	600 RVR

Stop Bar/Guard Light System


Each taxiway/runway entrance onto runway 10/28 is equipped with a stop bar consisting of red in-set lights and red elevated lights located at the taxi holding position. Yellow flashing runway guard lights (Wig Wags) are installed at each side of the stop bar location. When the red stop bar lights are illuminated, green lead on lights beyond the stop bar are extinguished. When ATC issues a clearance to proceed onto the runway, the red stop bar lights will be extinguished and the green lead on lights beyond the stop bar will be illuminated. The stop bar is reset automatically as the aircraft moves onto the runway. In the event of stop bar/guard light failure, ATC will restrict operations in low visibility operations to one aircraft on the maneuvering area at a time.

“AT NO TIME SHALL A PILOT CROSS AN ILLUMINATED RED STOP BAR”

“Follow me” service is available via Pilot request to ATC.

LOW VISIBILITY TAXI CHART RWY 10/28
(RVR LESS THAN 1200 TO 600 FT)

ST. JOHN'S INTL, NL
CYYT



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

DE-ICING OPERATIONS

De-icing Procedures

1. Contact ICEMAN thirty minutes prior to push back on 129.2 MHz.
2. Contact ST JOHN'S GND after pushback for taxi to CDF.
3. Hold short of CDF on H.
4. ST JOHN'S GND will advise the flight crew to contact ICEMAN on 129.2 MHz when the aircraft has taxied to the proper entry point.
5. ICEMAN will then delegate bay assignment & entry instructions. Expect frequency change to de-icing bay frequencies.
6. De-icing bay frequencies;
Bay 1 – Contact IDS on 122.950 MHz
Bay 2 – Contact IDS on 130.125 MHz
Bay 3/4 – Contact IDS on 128.950 MHz
7. Flight crews are advised to exercise discretion at all times while on the CDF. Directional signage and taxi lines on the CDF must be followed by flight crews at all times.
8. After de-icing is complete, return to 129.2 MHz for pad exit instructions. Flight crews must advise ICEMAN that all equipment and de-icing personnel are away from the aircraft and have returned to their designated safety zones.
9. ICEMAN will instruct the aircraft to hold its position on the CDF and contact ST JOHN'S GND on 121.9 MHz.
10. Aircraft to hold its position until ST JOHN'S GND issues further taxi instructions from the CDF.

Notes:


- Aircraft intending on returning to any apron after de-icing must drip dry for 25 minutes on CDF.
- Single engine taxi not permitted from CDF.
- Engine run-ups are not permitted on CDF.
- Contact 709-753-9742 for de-icing if Icehouse unavailable.

De-icing Bay Restrictions

1. BAY 1 – Maximum wingspan for de-icing operations 35.8m (117ft).
2. BAY 2 – Maximum wingspan for de-icing operations 35.8m (117ft).
Note: BAY 3 is closed/unusable when BAY 2 is occupied.
3. BAY 3 – Maximum wingspan for de-icing operations 79.75m (262ft).
Note: BAYS 2 and 4 are closed/unusable when BAY 3 is occupied.
4. BAY 4 – Maximum wingspan for de-icing operations 35.8m (117ft).
Note: BAY 3 is closed/unusable when BAY 4 is occupied.


Note: The above noted maximum wingspans are intended to protect adjacent de-icing bays, safety zones and the apron taxiway. Exceedances of these values are permitted but must be evaluated and approved by the airport authority to ensure special operating procedures are communicated and implemented.

CENTRAL DE-ICING FACILITY



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

PARKING AREAS



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

PARKING AREAS

EFF 10 AUG 23

PARKING AREAS

Aircraft Parking Position

Position	Coordinates	Position	Coordinates
1	473650.35N 0524440.68W	10A	473645.88N 0524426.85W
1A	473651.02N 0524441.44W	10B	473645.89N 0524426.33W
1B	473650.16N 0524441.21W	11	473644.25N 0524427.22W
2	473650.20N 0524438.40W	11A	473644.30N 0524426.35W
3	473649.46N 0524435.92W	12	473642.77N 0524426.95W
6	473648.80N 0524433.55W	12A	473642.79N 0524426.54W
7	473648.66N 0524431.53W	R1	473641.29N 0524426.75W
7A	473648.94N 0524431.61W	R2	473640.12N 0524426.35W
7B	473648.94N 0524430.84W	W2	473650.70N 0524444.16W
8	473648.17N 0524429.43W	W3	473651.43N 0524445.80W
8A	473648.38N 0524428.95W	W4	473652.63N 0524443.45W
9	473647.34N 0524427.81W	W4A	473652.57N 0524442.97W
9A	473647.29N 0524427.56W	W5	473653.57N 0524442.35W
10	473645.75N 0524427.23W		


Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

CYSL-AD

ST. LEONARD, NB
CYSL

AERODROME CHART

		UNICOM – 122.7				CTR Boston – 124.75 239.05		
		ATF						
DECL DIST	18	36						
TORA	5026	5026						
TODA	5026	5026						
ASDA	5026	5026						
LDA	5026	5026						



AERODROME CHART


CYSL

EFF 19 MAY 22

CYSL-AD

AERODROME CHART

AWOS Mary's Harbour – 122.55				TFC – 122.8		ATF*			
DECL DIST	05	23							
TORA	2208	2208							
TODA	2208	2208							
ASDA	2208	2208							
LDA	2208	2208							




Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 20 APR 23

CCK4

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART


EFF 5 SEP 24

CCS3

CYJT-AD

STEPHENVILLE DYMOND AIRPORT, NL
CYJT

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART


EFF 21 MAR 24

CYJT

CYJT-AD

AERODROME CHART

AUTO – 122.55		UNICOM – 122.95 (AU)				CTR – 124.4 384.8			
						ATF			
DECL	DISTS	05	23						
TORA		8000	8000						
TODA		8000	8000						
ASDA		8000	8000						
LDA		8000	8000						



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART


EFF 7 OCT 21

CYSU

CYQY-AD

SYDNEY/J.A. DOUGLAS MCCURDY, NS
CYQY

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 2 OCT 25

CYQY

CYQY-AD

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 27 JAN 22

CYTN

WABUSH, NL
CYWK

● ATIS - 128.12		● CLNC DEL - 122.6		● RADIO - 122.0 296.2		CTR Montreal - 132.25 RADIO Quebec - 123.37	
● MET - 128.12				● TFC - 122.0 296.2		MF	
DECL	DISTS	18	36				
TORA	6002	6002					
TODA	6652	6986					
ASDA	6002	6002					
LDA	6002	6002					

Diagram illustrating the Runway Level of Service (RVS) for Runway 18/36, showing the runway layout, dimensions, and associated data.

Key Data Points:

- Runway Length: 6002 x 150
- Runway Width: 36
- Runway Level of Service: RVS
- Runway Type: Rwy 18, 36; (1/4 sm)
- Runway Status: NOT AUTHORIZED
- Runway Minima: TAKE-OFF MINIMA
- Runway Scale: SCALE IN FEET (0 to 2000)
- Runway Elevation: ELEV 1794, ELEV 1809
- Runway Angle: 179°, 353°
- Runway Width: 36
- Runway Level of Service: RVS
- Runway Type: Rwy 18, 36; (1/4 sm)
- Runway Status: NOT AUTHORIZED
- Runway Minima: TAKE-OFF MINIMA
- Runway Scale: SCALE IN FEET (0 to 2000)
- Runway Elevation: ELEV 1794, ELEV 1809
- Runway Angle: 179°, 353°
- Runway Width: 36

Additional Information:

- Runway Level of Service: RVS
- Runway Type: Rwy 18, 36; (1/4 sm)
- Runway Status: NOT AUTHORIZED
- Runway Minima: TAKE-OFF MINIMA
- Runway Scale: SCALE IN FEET (0 to 2000)
- Runway Elevation: ELEV 1794, ELEV 1809
- Runway Angle: 179°, 353°
- Runway Width: 36

* DEPARTURE PROCEDURE
Refer to DEPARTURE PROCEDURE Page.

Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved


AERODROME CHART

EFF 23 FEB 23

CYWK

CYWK-AD

AERODROME CHART



AERODROME CHART


EFF 12 JUN 25

CCC2

CYQI-AD

YARMOUTH, NS
CYQI

AERODROME CHART



Source of Canadian Civil Aeronautical Data: © 2025 NAV CANADA All rights reserved

AERODROME CHART

EFF 10 AUG 23

CYQI

CYQI-AD