


STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAO

TRANSITION ALT 14 000
TRANSITION LVL FL 140

SEOUL DEP 125.15 121.4
124.8
INCHEON TWR 118.2 118.8
132.8

SEOUL/Incheon Int'l(RKSI)
RWY 15L/R
RNAV BINIL 1C
RNAV BOPTA 1C

Note : Departure under ICAO Flight Procedures.



Change : New procedure.

OFFICE OF CIVIL AVIATION

AIRAC AIP AMDT 5/21B
Effective : 1600UTC 16 JUN 2021

SEOUL/Incheon Intl(RKSI)
RWY 15L/R
RNAV BINIL 1C, RNAV BOPTA 1C

AERONAUTICAL DATA TABULATION

Standard Instrument Departure Procedure Coding Tables

RNAV BINIL 1C										
Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	Remarks
001	CF	CG050	-	15L-140(131.3) 15R-138(129.7)	7.7	R	-5 000	-	37°22'18.4"N 126°35'07.0"E	-
002	TF	CG100	-	169 (160.9)	6.4	-	-10 000	-	37°16'16.3"N 126°37'43.8"E	-
003	TF	CP100	-	224 (215.3)	9.9	-	-	-	37°08'11.8"N 126°30'35.8"E	-
004	TF	HP100	-	278 (269.6)	7.6	-	-10 000	-	37°08'07.8"N 126°21'03.5"E	-
005	TF	HP120	-	278 (269.5)	13.0	-	+12 000	-	37°07'59.2"N 126°04'48.1"E	-
006	TF	BELTU	-	296 (287.9)	14.1	-	+FL 170	-	37°12'18.0"N 125°47'59.0"E	-
007	TF	BINIL	-	302 (293.2)	29.5	-	-	-	37°23'49.2"N 125°13'59.3"E	-

RNAV BOPTA 1C										
Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	Remarks
001	CF	CG050	-	15L-140(131.3) 15R-138(129.7)	7.7	R	-5 000	-	37°22'18.4"N 126°35'07.0"E	-
002	TF	CG100	-	169 (160.9)	6.4	-	-10 000	-	37°16'16.3"N 126°37'43.8"E	-
003	TF	CD120	-	190 (181.1)	8.8	-	-13 000 +9 000	-	37°07'27.8"N 126°37'31.2"E	-
004	TF	HD130	-	190 (181.1)	5.7	-	-13 000	-	37°01'44.4"N 126°37'23.0"E	-
005	TF	HD140	-	188 (179.5)	8.6	-	+14 000	-	36°53'08.6"N 126°37'29.0"E	-
006	TF	BOPTA	-	191 (182.6)	9.0	-	+FL 170	-	36°44'06.4"N 126°36'58.4"E	-

Change : New procedure.


STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAO

TRANSITION ALT 14 000
TRANSITION LVL FL 140

SEOUL DEP 125.15
121.4
124.8
INCHEON TWR 118.2
118.8

SEOUL/Incheon Intl(RKSI)
RWY 15L/R
RNAV OSPOT 1C
RNAV EGOBA 1C

Note : Departure under ICAO Flight Procedures.



SEOUL/Incheon Intl(RKSI)
RWY 15L/R
RNAV OSPOT 1C, RNAV EGOBA 1C

AERONAUTICAL DATA TABULATION

Standard Instrument Departure Procedure Coding Tables

RNAV OSPOT 1C										
Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	Remarks
001	CF	CG050	-	15L-140(131.3) 15R-138(129.7)	7.7	R	-5 000	-	37°22'18.4"N 126°35'07.0"E	-
002	TF	CG100	-	169 (160.9)	6.4	-	-10 000	-	37°16'16.3"N 126°37'43.8"E	-
003	TF	CG101	-	095 (086.1)	12.5	-	-	-	37°17'06.9"N 126°53'22.3"E	-
004	TF	CG130	-	157 (148.6)	8.2	-	+13 000	-	37°10'05.7"N 126°58'43.0"E	-
005	TF	SOT	-	159 (150.1)	5.1	-	+FL 150	-	37°05'39.7"N 127°01'54.0"E	-
006	TF	CG200	-	157 (148.3)	11.9	-	+FL 200	-	36°55'29.2"N 127°09'43.6"E	-
007	TF	OSPOT	-	128 (119.9)	10.4	-	+FL 230	-	36°50'18.1"N 127°20'54.9"E	-

RNAV EGOBA 1C										
Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	Remarks
001	CF	CG050	-	15L-140(131.3) 15R-138(129.7)	7.7	R	-5 000	-	37°22'18.4"N 126°35'07.0"E	-
002	TF	CG100	-	169 (160.9)	6.4	-	-10 000	-	37°16'16.3"N 126°37'43.8"E	-
003	TF	CG101	-	095 (086.1)	12.5	-	-	-	37°17'06.9"N 126°53'22.3"E	-
004	TF	CK100	-	092 (083.5)	11.2	-	-	-	37°18'22.7"N 127°07'21.4"E	-
005	TF	CK099	-	080 (071.7)	6.3	-	-10 000	-	37°20'21.2"N 127°14'52.0"E	-
006	TF	EGOBA	-	044 (035.3)	10.9	-	-11 000	-	37°29'14.7"N 127°22'45.9"E	-

Change : New procedure.


STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAO

TRANSITION ALT 14 000
TRANSITION LVL FL 140

SEOUL DEP 125.15
121.4
124.8
INCHEON TWR 118.2
118.8

SEOUL/Incheon Intl(RKSI)
RWY 15L/R
SEL 1S
SOT 1S

Note : Departure under ICAO Flight Procedures.



GENERAL INFORMATION

- CG in excess of 3.3% necessary and also strict adherence to CG required for airspace, ATC and noise abatement purposes.
 - SEL 1S minimum CG 5.5% to 7 000 ft.
 - SOT 1S minimum CG 6.0% to FL 170.
- If unable to comply with flight restrictions, advise ATC well before departure for alternatives.
- Step climb : Due to interaction with other routes, do NOT climb above 7 000 ft unless cleared by ATC.

SEL(ANYANG) ONE SIERRA DEPARTURE

TAKE OFF RWY 15L : Climb on R 153 NCN , thence...

TAKE OFF RWY 15R : Climb straight ahead, at NCN D6 turn left onto R 153 NCN, thence...
at NCN D10 turn left to intercept R 254 SEL and proceed to SEL, fly by SEL.
Cross SEL D11 at or above 5 400 ft and SEL D6 at 7 000 ft until instructed by ATC.

SOT(SONGTAN) ONE SIERRA DEPARTURE

TAKE OFF RWY 15L : Climb on R 153 NCN, thence...

TAKE OFF RWY 15R : Climb straight ahead, at NCN D6 turn left onto R 153 NCN, thence...
at NCN D12 turn left to intercept R 310 SOT and proceed SOT. At or above 6 500 ft
by SOT D16, at or above 11 000 ft by SOT and at or above FL 150 by
SOT D8 on A582 or B576. Maintain 7 000 ft until instructed by ATC.

Change : New procedure.

OFFICE OF CIVIL AVIATION

AIRAC AIP AMDT 5/21B
Effective : 1600UTC 16 JUN 2021

INTENTIONALLY

LEFT

BLANK


STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAO

TRANSITION ALT 14 000
TRANSITION LVL FL 140

SEOUL DEP 125.15 121.4
INCHEON TWR 118.2 118.8
132.8

SEOUL/Incheon Int'l(RKSI)
RWY 16L/R
RNAV BINIL 1H
RNAV BOPTA 1H

Note : Departure under ICAO Flight Procedures.



Change : New procedure.

SEOUL/Incheon Intl(RKSI)

RWY 16L/R

RNAV BINIL 1H, RNAV BOPTA 1H

AERONAUTICAL DATA TABULATION

Standard Instrument Departure Procedure Coding Tables

RNAV BINIL 1H										
Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	VPA/RDH
001	CF	HD050	-	161-158(149.5) 168-155(146.3)	4.0	R	-5 000	-	37°23'08.6"N 126°29'03.7"E	-
002	TF	HD100	-	173 (164.8)	6.6	-	-10 000	-	37°16'47.0"N 126°31'13.0"E	-
003	TF	HP100	-	232 (223.3)	11.9	-	-10 000	-	37°08'07.8"N 126°21'03.5"E	-
004	TF	HP120	-	278 (269.5)	13.0	-	+12 000	-	37°07'59.2"N 126°04'48.1"E	-
005	TF	BELTU	-	296 (287.9)	14.1	-	+FL 170	-	37°12'18.0"N 125°47'59.0"E	-
006	TF	BINIL	-	302 (293.2)	29.5	-	-	-	37°23'49.2"N 125°13'59.3"E	-

RNAV BOPTA 1H										
Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	VPA/RDH
001	CF	HD050	-	161-158(149.5) 168-155(146.3)	4.0	R	-5 000	-	37°23'08.6"N 126°29'03.7"E	-
002	TF	HD100	-	173 (164.8)	6.6	-	-10 000	-	37°16'47.0"N 126°31'13.0"E	-
003	TF	HD120	-	170 (161.8)	11.4	-	+13 000 +9 000	-	37°05'56.6"N 126°35'39.9"E	-
004	TF	HD130	-	170 (161.8)	4.4	-	-13 000	-	37°01'44.4"N 126°37'23.0"E	-
005	TF	HD140	-	188 (179.5)	8.6	-	+14 000	-	36°53'08.6"N 126°37'29.0"E	-
006	TF	BOPTA	-	191 (182.6)	9.0	-	+FL 170	-	36°44'06.4"N 126°36'58.4"E	-

Change : New procedure.


STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAO

TRANSITION ALT 14 000
TRANSITION LVL FL 140

SEOUL DEP 125.15
121.4
124.8
INCHEON TWR 118.2
118.8

SEOUL/Incheon Int'l(RKSI)
RWY 16L/R
RNAV OSPOT 1H
RNAV EGOBA 1H

Note : Departure under ICAO Flight Procedures.



SEOUL/Incheon Intl(RKSI)

RWY 16L/R

RNAV OSPOT 1H, RNAV EGOBA 1H

AERONAUTICAL DATA TABULATION

Standard Instrument Departure Procedure Coding Tables

RNAV OSPOT 1H										
Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	VPA/ RDH
001	CF	HD050	-	16L-158(149.5) 16R-155(146.3)	4.0	R	-5 000	-	37°23'08.6"N 126°29'03.7"E	-
002	TF	HD100	-	173 (164.8)	6.6	-	-10 000	-	37°16'47.0"N 126°31'13.0"E	-
003	TF	CG100	-	104 (095.6)	5.2	-	-	-	37°16'16.3"N 126°37'43.8"E	-
004	TF	CG101	-	095 (086.1)	12.5	-	-	-	37°17'06.9"N 126°53'22.3"E	-
005	TF	CG130	-	157 (148.6)	8.2	-	+13 000	-	37°10'05.7"N 126°58'43.0"E	-
006	TF	SOT	-	159 (150.1)	5.1	-	+FL 150	-	37°05'39.7"N 127°01'54.0"E	-
007	TF	CG200	-	157 (148.3)	11.9	-	+FL 200	-	36°55'29.2"N 127°09'43.6"E	-
008	TF	OSPOT	-	128 (119.9)	10.4	-	+FL 230	-	36°50'18.1"N 127°20'54.9"E	-

RNAV EGOBA 1H										
Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	VPA/ RDH
001	CF	HD050	-	16L-158(149.5) 16R-155(146.3)	4.0	R	-5 000	-	37°23'08.6"N 126°29'03.7"E	-
002	TF	HD100	-	173 (164.8)	6.6	-	-10 000	-	37°16'47.0"N 126°31'13.0"E	-
003	TF	CG100	-	104 (095.6)	5.2	-	-	-	37°16'16.3"N 126°37'43.8"E	-
004	TF	CG101	-	095 (086.1)	12.5	-	-	-	37°17'06.9"N 126°53'22.3"E	-
005	TF	CK100	-	092 (083.5)	11.2	-	-	-	37°18'22.7"N 127°07'21.4"E	-
006	TF	CK099	-	080 (071.7)	6.3	-	-10 000	-	37°20'21.2"N 127°14'52.0"E	-
007	TF	EGOBA	-	044 (035.3)	10.9	-	-11 000	-	37°29'14.7"N 127°22'45.9"E	-

Change : New procedure.

OFFICE OF CIVIL AVIATION

AIRAC AIP AMDT 5/21B
Effective : 1600UTC 16 JUN 2021


STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAO

TRANSITION ALT 14 000
TRANSITION LVL FL 140

SEOUL DEP 125.15
121.4
124.8
INCHEON TWR 118.2
118.8

SEOUL/Incheon Intl(RKSI)
RWY 15L/R RADAR 5S
RWY 16L/R RADAR 3U

Note : Departure under ICAO Flight Procedures.



GENERAL INFORMATION

1. 6.0% CG required until FL 150 for ATC and airspace purpose.
2. Pilot shall use caution not to penetrate prohibited or restricted areas around airport.
3. Aircraft may experience delay due to airspace use coordination, traffic volume, and so on.

RADAR FIVE SIERRA DEPARTURE

TAKE OFF RWY 15L : Climb HDG 139°, expect radar vector to airway. Maintain 7 000 ft until instructed by ATC.
TAKE OFF RWY 15R : Climb HDG 138°, expect radar vector to airway. Maintain 7 000 ft until instructed by ATC.

No radio procedure : If no radio contact with ATC, squawk 7600 , and unless otherwise instructed by ATC, proceed as follows.

- to SOT via R 315 SOT for A582, B576
- to intercept Y644 to POLEG, EGOBA, KARBU for G597
- to intercept R 290 SOT to BINIL or proceed direct to HP100, HP120, BELTU to BINIL for G597 as appropriate.

Pilot shall proceed as described above prior to reaching NCN D20 or R 235 SEL due to airspace.

RADAR THREE UNIFORM DEPARTURE

TAKE OFF RWY 16L : Climb HDG 170°, expect radar vector to airway. Maintain 7 000 ft until instructed by ATC.
TAKE OFF RWY 16R : Climb HDG 169°, expect radar vector to airway. Maintain 7 000 ft until instructed by ATC.

No radio procedure : If no radio contact with ATC, squawk 7600, and unless otherwise instructed by ATC proceed as follows.

- to SOT via R 307 SOT for A582, B576
- to intercept Y644 to POLEG, EGOBA, KARBU for G597
- to intercept R 290 SOT to BINIL or proceed direct to HP100, HP120, BELTU to BINIL for G597 as appropriate.

Pilot shall proceed as described above prior to reaching WNG D14 due to airspace.

Change : New procedure.

OFFICE OF CIVIL AVIATION

AIRAC AIP AMDT 5/21B
Effective : 1600UTC 16 JUN 2021

INTENTIONALLY

LEFT

BLANK


STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAO

TRANSITION ALT 14 000
TRANSITION LVL FL 140

SEOUL DEP 125.15
121.4
124.8
INCHEON TWR 118.2
118.8

SEOUL/Incheon Int'l(RKSI)
RWY 33L/R
RNAV NOPIK 1A
RNAV BOPTA 1A

Note : Departure under ICAO Flight Procedures.



Change : Amended phrase(AD140 → AP140).

SEOUL/Incheon Intl(RKSI)
RWY 33L/R
RNAV NOPIK 1A, RNAV BOPTA 1A

AERONAUTICAL DATA TABULATION

Standard Instrument Departure Procedure Coding Tables

RNAV NOPIK 1A

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	VPA/ RDH	Navigation specification	Remarks
001	CF	AD020	-	33L-335(326.5) 33R-333(324.7)	7.0	L	+2 000	-	37°34'45.1"N 126°21'19.0"E	-	RNAV 1	-
002	TF	AD050	-	279 (270.3)	7.0	-	+5 000	-	37°34'46.7"N 126°12'30.6"E	-	RNAV 1	-
003	TF	AP140	-	253 (244.2)	23.9	-	+14 000	-	37°24'16.9"N 125°45'21.4"E	-	RNAV 1	-
004	TF	NOPIK	-	278 (269.1)	5.1	-	+FL 160	-	37°24'12.0"N 125°39'05.0"E	-	RNAV 1	-

RNAV BOPTA 1A

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	VPA/ RDH	Navigation specification	Remarks
001	CF	AD020	-	33L-335(326.5) 33R-333(324.7)	7.0	L	+2 000	-	37°34'45.1"N 126°21'19.0"E	-	RNAV 1	-
002	TF	AD050	-	279 (270.3)	7.0	-	+5 000	-	37°34'46.7"N 126°12'30.6"E	-	RNAV 1	-
003	TF	YD070	-	207 (198.7)	10.8	-	+9 000	-	37°24'31.4"N 126°08'09.0"E	-	RNAV 1	-
004	TF	YD100	-	140 (131.1)	7.5	-	+11 000	-	37°19'35.0"N 126°15'14.0"E	-	RNAV 1	-
005	TF	YD130	-	140 (131.2)	12.0	-	+FL 150	-	37°11'39.7"N 126°26'32.1"E	-	RNAV 1	-
006	TF	YD160	-	168 (159.1)	10.0	-	+FL 180	-	37°02'19.6"N 126°30'58.2"E	-	RNAV 1	-
007	TF	YD190	-	174 (165.2)	10.0	-	+FL 190	-	36°52'38.3"N 126°34'10.0"E	-	RNAV 1	-
008	TF	BOPTA	-	174 (165.2)	8.8	-	+FL 210	-	36°44'06.4"N 126°36'58.4"E	-	RNAV 1	-

Change : Amended phrase(AD140 → AP140).


STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAO

TRANSITION ALT 14 000
TRANSITION LVL FL 140

SEOUL DEP 125.15
121.4
124.8
INCHEON TWR 118.2
118.8

SEOUL/Incheon Int'l(RKSI)
RWY 33L/R
RNAV OSPOT 1A
RNAV EGOBA 1A

Note : Departure under ICAO Flight Procedures.



Change : New procedure.

SEOUL/Incheon Intl(RKSI)
RWY 33L/R
RNAV OSPOT 1A, RNAV EGOBA 1A

AERONAUTICAL DATA TABULATION

Standard Instrument Departure Procedure Coding Tables

RNAV OSPOT 1A

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	VPA/RDH	Navigation specification	Remarks
001	CF	AD020	-	33L-335(326.5) 33R-333(324.7)	7.0	L	+2 000	-	37°34'45.1"N 126°21'19.0"E	-	RNAV 1	-
002	TF	AD050	-	279 (270.3)	7.0	-	+5 000	-	37°34'46.7"N 126°12'30.6"E	-	RNAV 1	-
003	TF	YD070	-	207 (198.7)	10.8	-	+9 000	-	37°24'31.4"N 126°08'09.0"E	-	RNAV 1	-
004	TF	YD100	-	140 (131.1)	7.5	-	+11 000	-	37°19'35.0"N 126°15'14.0"E	-	RNAV 1	-
005	TF	YD130	-	140 (131.2)	12.0	-	+FL 150	-	37°11'39.7"N 126°26'32.1"E	-	RNAV 1	-
006	TF	YG160	-	124 (115.8)	10.0	-	+FL 180	-	37°07'18.5"N 126°37'44.9"E	-	RNAV 1	-
007	TF	OSPOT	-	124 (115.9)	38.5	-	-	-	365°01'8.1"N 127°20'54.9"E	-	RNAV 1	-

RNAV EGOBA 1A

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	VPA/RDH	Navigation specification	Remarks
001	CF	AD020	-	33L-335(326.5) 33R-333(324.7)	7.0	L	+2 000	-	37°34'45.1"N 126°21'19.0"E	-	RNAV 1	-
002	TF	AD050	-	279 (270.3)	7.0	-	+5 000	-	37°34'46.7"N 126°12'30.6"E	-	RNAV 1	-
003	TF	YD070	-	207 (198.7)	10.8	-	+9 000	-	37°24'31.4"N 126°08'09.0"E	-	RNAV 1	-
004	TF	YD100	-	140 (131.1)	7.5	-	+11 000	-	37°19'35.0"N 126°15'14.0"E	-	RNAV 1	-
005	TF	YK130	-	099 (090.6)	9.8	-	+13 000	-	37°19'28.6"N 126°27'31.1"E	-	RNAV 1	-
006	TF	YK170	-	099 (090.7)	12.1	-	+FL 170	-	37°19'18.2"N 126°42'38.8"E	-	RNAV 1	-
007	TF	YK210	-	099 (090.8)	14.3	-	-	-	37°19'05.3"N 127°00'31.4"E	-	RNAV 1	-
008	TF	EGOBA	-	069 (060.1)	20.4	-	-	-	37°29'14.7"N 127°22'45.9"E	-	RNAV 1	-

Change : New procedure.


STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAO

TRANSITION ALT 14 000
TRANSITION LVL FL 140

SEOUL DEP 125.15
121.4
124.8
INCHEON TWR 118.2
118.8

SEOUL/Incheon Intl(RKSI)
RWY 33L/R
RNAV OSPOT 1E
RNAV EGOBA 1E

Note : Departure under ICAO Flight Procedures.



SEOUL/Incheon Intl(RKSI)
RWY 33L/R
RNAV OSPOT 1E, RNAV EGOBA 1E

AERONAUTICAL DATA TABULATION

Standard Instrument Departure Procedure Coding Tables

RNAV OSPOT 1E

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	VPA/RDH	Navigation specification	Remarks
001	CF	EG020	-	33L-336(327.0) 33R-333(324.7)	5.5	R	-	-230	37°33'31.6"N 126°22'24.5"E	-	RNAV 1	-
002	TF	EG040	-	353 (344.2)	5.1	-	+4 000	-230	37°38'27.4"N 126°20'39.1"E	-	RNAV 1	-
003	TF	EG055	-	079 (070.3)	5.2	-	-5 500	-	37°40'12.7"N 126°26'50.5"E	-	RNAV 1	-
004	TF	EG070	-	119 (110.0)	5.0	-	+7 000	-	37°38'29.2"N 126°32'48.6"E	-	RNAV 1	-
005	TF	EG140	-	146 (137.6)	18.5	-	+14 000	-	37°24'47.5"N 126°48'26.5"E	-	RNAV 1	-
006	TF	EG160	-	151 (142.9)	7.0	-	+FL 160	-	37°19'11.6"N 126°53'44.6"E	-	RNAV 1	-
007	TF	OSPOT	-	151 (142.9)	36.1	-	+FL 210	-	36°50'18.1"N 127°20'54.9"E	-	RNAV 1	-

RNAV EGOBA 1E

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	VPA/RDH	Navigation specification	Remarks
001	CF	EG020	-	33L-336(327.0) 33R-333(324.7)	5.5	R	-	-230	37°33'31.6"N 126°22'24.5"E	-	RNAV 1	-
002	TF	EG040	-	353 (344.2)	5.1	-	+4 000	-230	37°38'27.4"N 126°20'39.1"E	-	RNAV 1	-
003	TF	EG055	-	079 (070.3)	5.2	-	-5 500	-	37°40'12.7"N 126°26'50.5"E	-	RNAV 1	-
004	TF	EG070	-	119 (110.0)	5.0	-	+7 000	-	37°38'29.2"N 126°32'48.6"E	-	RNAV 1	-
005	TF	EG140	-	146 (137.6)	18.5	-	+14 000	-	37°24'47.5"N 126°48'26.5"E	-	RNAV 1	-
006	TF	SEL	-	098 (089.7)	5.8	-	+FL 160	-	37°24'49.0"N 126°55'42.1"E	-	RNAV 1	-
007	TF	EGOBA	-	087 (078.3)	22.0	-	+FL 210	-	37°29'14.7"N 127°22'45.9"E	-	RNAV 1	-

Change : New procedure.


STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAO

TRANSITION ALT 14 000
TRANSITION LVL FL 140

SEOUL DEP 125.15
121.4
124.8
INCHEON TWR 118.2
118.8

SEOUL/Incheon Intl(RKSI)
RWY 33R/L
SEL 2A, SOT 1A

Note : Departure under ICAO Flight Procedures.



GENERAL INFORMATION

- CG in excess of 3.3% necessary for Airspace and ATC purposes.
 - 1.1 SOT 1A minimum CG 4.9% to FL 170.
- After NCN D5, 15 degree bank angle recommended during turn for noise abatement and pilot should use caution not to penetrate prohibited area. (RK P518)
- If unable to comply with flight restrictions, advise ATC well before departure for alternatives.
- Step climb : Due to interaction with other routes, do NOT climb above 7 000 ft unless cleared by ATC.
- Pilot shall use caution not to make early or lead turn prior to reaching NCN D5.

SEL(ANYANG) TWO ALPHA DEPARTURE

TAKE OFF RWY 33L/R : Climb straight ahead, at NCN D5 turn left to intercept R 278 SEL and cross.
R 278 SEL/D28 then proceed to SEL. Maintain 7 000 ft until instructed by ATC.

SOT(SONGTAN) ONE ALPHA DEPARTURE

TAKE OFF RWY 33L/R : Climb straight ahead, at NCN D5 turn left to intercept R 305 SOT and cross
R 305 SOT/D40 then proceed to SOT. Maintain 7 000 ft until instructed by ATC.

Change : New procedure.

OFFICE OF CIVIL AVIATION

AIRAC AIP AMDT 5/21B
Effective : 1600UTC 16 JUN 2021

INTENTIONALLY

LEFT

BLANK


STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAO

TRANSITION ALT 14 000
TRANSITION LVL FL 140

SEOUL DEP 125.15
121.4
124.8
INCHEON TWR 118.2
118.8

SEOUL/Incheon Intl(RKSI)
RWY 34L/R
RNAV NOPIK 1Y
RNAV BOPTA 1Y

Note : Departure under ICAO Flight Procedures.



Change : New procedure.

SEOUL/Incheon Intl(RKSI)
RWY 34L/R
RNAV NOPIK 1Y, RNAV BOPTA 1Y

AERONAUTICAL DATA TABULATION

Standard Instrument Departure Procedure Coding Tables

RNAV NOPIK 1Y												
Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	VPA/ RDH	Navigation specification	Remarks
001	CF	YD020	-	34L-323(314.5) 34R-318(309.7)	34L-3.0 34R-2.9	L	-	-230	37°30'13.3"N 126°22'07.7"E	-	RNAV 1	Bank angle 20°
002	TF	YD040	-	280 (271.8)	8.9	-	+4 000	-	37°30'29.6"N 126°10'56.9"E	-	RNAV 1	-
003	TF	YP080	-	245 (236.7)	11.0	-	+8 000	-	37°24'26.5"N 125°59'24.4"E	-	RNAV 1	-
004	TF	NOPIK	-	278 (269.2)	16.2	-	+13 000	-	37°24'12.0"N 125°39'05.0"E	-	RNAV 1	-

RNAV BOPTA 1Y												
Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	VPA/ RDH	Navigation specification	Remarks
001	CF	YD020	-	34L-323(314.5) 34R-318(309.7)	34L-3.0 34R-2.9	L	-	-230	37°30'13.3"N 126°22'07.7"E	-	RNAV 1	Bank angle 20°
002	TF	YD040	-	280 (271.8)	8.9	-	+4 000	-	37°30'29.6"N 126°10'56.9"E	-	RNAV 1	-
003	TF	YD070	-	209 (200.5)	6.4	-	+7 000	-	37°24'31.4"N 126°08'09.0"E	-	RNAV 1	-
004	TF	YD100	-	140 (131.1)	7.5	-	+10 000	-	37°19'35.0"N 126°15'14.0"E	-	RNAV 1	-
005	TF	YD130	-	140 (131.2)	12.0	-	+13 000	-	37°11'39.7"N 126°26'32.1"E	-	RNAV 1	-
006	TF	YD160	-	168 (159.1)	10.0	-	+FL 160	-	37°02'19.6"N 126°30'58.2"E	-	RNAV 1	-
007	TF	YD190	-	174 (165.2)	10.0	-	+FL 190	-	36°52'38.3"N 126°34'10.0"E	-	RNAV 1	-
008	TF	BOPTA	-	174 (165.2)	8.8	-	+FL 210	-	36°44'06.4"N 126°36'58.4"E	-	RNAV 1	-

Change : New procedure.


STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAO

TRANSITION ALT 14 000
TRANSITION LVL FL 140

SEOUL DEP 125.15
121.4
124.8
INCHEON TWR 118.2
118.8

SEOUL/Incheon Int'l(RKSI)
RWY 34L/R
RNAV OSPOT 1Y
RNAV EGOBA 1Y

Note : Departure under ICAO Flight Procedures.



Change : New procedure.

SEOUL/Incheon Intl(RKSI)
RWY 34L/R
RNAV OSPOT 1Y, RNAV EGOBA 1Y

AERONAUTICAL DATA TABULATION

Standard Instrument Departure Procedure Coding Tables

RNAV OSPOT 1Y

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	VPA/RDH	Navigation specification	Remarks
001	CF	YD020	-	34L-323(314.5) 34R-318(309.7)	34L-3.0 34R-2.9	L	-	-230	37°30'13.3"N 126°22'07.7"E	-	RNAV 1	Bank angle 20°
002	TF	YD040	-	280 (271.8)	8.9	-	+4 000	-	37°30'29.6"N 126°10'56.9"E	-	RNAV 1	-
003	TF	YD070	-	209 (200.5)	6.4	-	+7 000	-	37°24'31.4"N 126°08'09.0"E	-	RNAV 1	-
004	TF	YD100	-	140 (131.1)	7.5	-	+10 000	-	37°19'35.0"N 126°15'14.0"E	-	RNAV 1	-
005	TF	YD130	-	140 (131.2)	12.0	-	+13 000	-	37°11'39.7"N 126°26'32.1"E	-	RNAV 1	-
006	TF	YG160	-	124 (115.8)	10.0	-	+FL 160	-	37°07'18.5"N 126°37'44.9"E	-	RNAV 1	-
007	TF	OSPOT	-	124 (115.9)	38.5	-	-	-	36°50'18.1"N 127°20'54.9"E	-	RNAV 1	-

RNAV EGOBA 1Y

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	VPA/RDH	Navigation specification	Remarks
001	CF	YD020	-	34L-323(314.5) 34R-318(309.7)	34L-3.0 34R-2.9	L	-	-230	37°30'13.3"N 126°22'07.7"E	-	RNAV 1	Bank angle 20°
002	TF	YD040	-	280 (271.8)	8.9	-	+4 000	-	37°30'29.6"N 126°10'56.9"E	-	RNAV 1	-
003	TF	YD070	-	209 (200.5)	6.4	-	+7 000	-	37°24'31.4"N 126°08'09.0"E	-	RNAV 1	-
004	TF	YD100	-	140 (131.1)	7.5	-	+10 000	-	37°19'35.0"N 126°15'14.0"E	-	RNAV 1	-
005	TF	YK130	-	099 (090.6)	9.8	-	+13 000	-	37°19'28.6"N 126°27'31.1"E	-	RNAV 1	-
006	TF	YK170	-	099 (090.7)	12.1	-	+FL 170	-	37°19'18.2"N 126°42'38.8"E	-	RNAV 1	-
007	TF	YK210	-	099 (090.8)	14.3	-	-	-	37°19'05.3"N 127°00'31.4"E	-	RNAV 1	-
008	TF	EGOBA	-	069 (060.1)	20.4	-	-	-	37°29'14.7"N 127°22'45.9"E	-	RNAV 1	-

Change : New procedure.


STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAO

TRANSITION ALT 14 000
TRANSITION LVL FL 140

SEOUL DEP 125.15
121.4
124.8
INCHEON TWR 118.2
118.8

SEOUL/Incheon Intl(RKSI)
RWY 33L/R RADAR 3A
RWY 34L/R RADAR 3D

Note : Departure under ICAO Flight Procedures.



GENERAL INFORMATION

1. 6.0% CG required until FL 150 for ATC and airspace purpose.
2. Pilot shall use caution not to penetrate prohibited or restricted areas around airport.
3. Aircraft may experience delay due to airspace use coordination, traffic volume, and so on.

RADAR THREE ALPHA DEPARTURE

TAKE OFF RWY 33L/R : Climb on RWY HDG until NCN D6.0(SEL D29.1), turn left HDG 270° expect radar vector to airway.

No radio procedure : If no radio contact with ATC, squawk 7600, and unless otherwise instructed by ATC proceed as follows.

- fly south to join R 269 SEL to SEL or proceed direct to YD100 then SEL for G597
- fly south to join G597 to NOPIK
- fly south to YD100, YD130 and OSPOT for A582
- fly south to YD100, YD130, YD160, YD190 and BOPTA for BEDES via Z51.

Pilot shall remain within NCN D16 (SEL D40 or 17 NM from Airport as appropriate) during on HDG 270°.

RADAR THREE DELTA DEPARTURE

TAKE OFF RWY 34L/R : Climb HDG 300° until WNG D6.0(SEL D27.9), turn left HDG 250° expect radar vector to airway. Maintain 3 000 ft until instructed by ATC.

No radio procedure : If no radio contact with ATC, squawk 7600, and unless otherwise instructed by ATC proceed as follows.

- fly south to join R 269 SEL to SEL or proceed direct to YD100 then SEL for G597
- fly south to join G597 to NOPIK
- fly south to YD100, YD130 and OSPOT for A582
- fly south to YD100, YD130, YD160, YD190 and BOPTA for BEDES via Z51.

Pilot shall remain within NCN D16 (SEL D40 or 17 NM from Airport as appropriate) during on HDG 250°.

Change : New procedure.

OFFICE OF CIVIL AVIATION

AIRAC AIP AMDT 5/21B
Effective : 1600UTC 16 JUN 2021

INTENTIONALLY

LEFT

BLANK