


**INSTRUMENT
APPROACH
CHART**

AERODROME ELEV 42 ft
HEIGHTS RELATED TO
THR RWY 18 - ELEV 42 ft

POHANG APP 124.25
120.2
ULSAN TWR 118.75

ULSAN/Ulsan(RKPU)
RNP Y RWY 18

Note : Approach under U.S TERPS.




RECOMMENDED PROFILE(FAA)	THR RWY 18	5	4	3	2.2
Final Approach Gradient 6.58%, 400 ft/NM	ALT(HGT)	2 092 (2 050)	1 692 (1 650)	1 292 (1 250)	990 (948)

TRANSITION ALT 14 000
TRANSITION LVL FL 140

MISSED APPROACH

Climb on track of 172° to PU406 then LEFT turn on track of 094° to HAEGU and HOLD at 5 000 ft.



CATEGORY			MDA(H)				Rate of descent				
STA	LNAV	FULL	990 (948)	A	B	C	D	V/V fpm	400	600	800
		ALS INOP		3 600 m	3 900 m	3 900 m	N/A				
				4 000 m	4 300 m	4 300 m	N/A				

Change : Information of course/track, OBST, MOCA and Withdrawal of USN VOR/DME information.

ULSAN/Ulsan(RKPU)
RNP Y RWY 18
HOLDING PROCEDURE

AERONAUTICAL DATA TABULATION

Instrument Approach Procedure Coding Tables

RNP Y RWY 18

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	VPA/RDH	Navigation specification	Remarks
001	IF	MAKKY	-	-	-	-	+5 000	-	35°52'18.8"N 129°15'35.8"E	-	RNP APCH	IAF
002	TF	SEDMO	-	173(164.4)	4.0	-	+4 000	-	35°48'27.1"N 129°16'55.0"E	-	RNP APCH	IF
003	TF	PU402	-	173(164.4)	4.4	-	+3 000	-	35°44'14.2"N 129°18'21.4"E	-	RNP APCH	SDF
004	TF	BINJO	-	173(164.4)	2.6	-	+2 400	-	35°41'43.5"N 129°19'12.8"E	-	RNP APCH	FAF
005	TF	PU403	-	172(163.7)	2.6	-	+1 300	-	35°39'15.5"N 129°20'05.6"E	-	RNP APCH	SDF
006	TF	IGMEL	Y	172(163.7)	1.0	-	+990	-	35°38'17.7"N 129°20'26.4"E	-3.77/50	RNP APCH	MAPt
007	TF	PU406	-	172(163.7)	7.1	-	-	-	35°31'29.1"N 129°22'52.3"E	-	RNP APCH	-
008	TF	HAEGU	Y	094(085.6)	7.9	-	-	-	35°32'06.7"N 129°32'32.3"E	-	RNP APCH	-
009	HIM	HAEGU	Y	300(292.1)	-	R	@5 000	-200	35°32'06.7"N 129°32'32.3"E	-	RNP APCH	1 min (Outbound timing)

HOLDING PROCEDURE

Holding Identification	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(T)	Time (min)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	VPA/RDH	Navigation specification	Remarks
RNP Y RWY 18	HIM	SEDMO	Y	173(164.4)	1.0	L	-5 000 +4 000	-200	35°48'27.1"N 129°16'55.0"E	-	RNAV 1	-

Change : Information of course/track for SEDMO, PU402, BINJO(172° → 173°).


**INSTRUMENT
APPROACH
CHART - ICAO**

AERODROME ELEV 42 ft
HEIGHTS RELATED TO
THR RWY 18 - ELEV 42 ft

POHANG APP 124.25
120.2
ULSAN TWR 118.75

ULSAN/Ulsan(RKPU)
RNP Z RWY 18(AR)


Note : Approach under ICAO Flight Procedures.



MISSED APPROACH

Climb on track of 184° to PU407 then LEFT turn on track of 094° to PU408 then LEFT turn on track of 064° to HAEGU and Hold at 5 000 ft.
* DA to RW180 1.8 NM.

TRANSITION ALT 14 000
TRANSITION LVL FL 140



								Knots	60	90	120	150	180
CATEGORY		DA(H)	A	B	C	D	Rate of descent	V/V fpm	329	494	658	823	987
RNP 0.3	FULL	690 (648)	3 100 m				* Timing Not authorized for defining MAPt. * Circling Not authorized.						
	ALS INOP		3 400 m										

Change : Information of course/track, OBST, coordinates and Withdrawal of USN VOR/DME information and Amended phrase.

AERONAUTICAL DATA TABULATION

Instrument Approach Procedure Coding Tables

RNP Z RWY 18 (AR)

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	VPA/RDH	Navigation specification	Remarks
001	IF	MAKKY	-	-	-	-	+5 000	-220	35°52'18.8"N 129°15'35.8"E	-	-	IAF
002	TF	SEDMO	-	173(164.4)	4.0	-	+4 000	-220	35°48'27.1"N 129°16'55.0"E	-	0.5	IF
003	TF	PU402	-	173(164.4)	4.4	-	+2 800	-220	35°44'14.2"N 129°18'21.4"E	-	0.5	
004	TF	KALUS	-	173(164.4)	2.7	-	+2 000	-165	35°41'37.4"N 129°19'14.9"E	-	0.3	FAF Bank Angle 18°
005	TF	GODIS	-	161(152.9)	2.4	L	+1 218	-165	35°39'30.7"N 129°20'34.3"E	-3.10	0.3	Bank Angle 18°
006	RF	RIMTA	-	-	0.8	R	+944	-165	35°38'42.4"N 129°20'50.7"E	-3.10	0.3	Bank Angle 18°
007	TF	RW180	Y	184(176.1)	2.6	-	-	-165	35°36'08.9"N 129°21'03.5"E	-3.10/60	0.3	-
008	TF	PU407	-	184(176.1)	6.7	-	-	-220	35°29'30.2"N 129°21'36.8"E	-	1.0	
009	TF	PU408	-	094(086.1)	5.7	L	-	-220	35°29'53.2"N 129°28'33.2"E	-	1.0	Bank Angle 18°
010	TF	HAEGU	Y	064(055.7)	3.9	L	+5 000	-220	35°32'06.7"N 129°32'32.3"E	-	1.0	Bank Angle 18°
011	HM	HAEGU	Y	300(292.1)	-	R	@5 000	-200	35°32'06.7"N 129°32'32.3"E	-	RNP APCH	1 min (Outbound timing)

RF arc center Identifier	Coordinates
ARC01	35°38'33.8"N 129°18'18.0"E

Change : Information of course/track for SEDMO, PU402, KALUS(172° → 173°).


**INSTRUMENT
APPROACH
CHART**

AERODROME ELEV 42 ft
HEIGHTS RELATED TO
THR RWY 18 - ELEV 42 ft

POHANG APP 124.25
120.2
ULSAN TWR 118.75


ULSAN/Ulsan(RKPU)
VOR RWY 18

Note : Approach under U.S TERPS.



TRANSITION ALT 14 000
TRANSITION LVL FL 140

RECOMMENDED PROFILE(FAA)	DME USN	5	4	3	2.8
Final Approach Gradient 6.45%, 392 ft/NM	ALT(HGT)	1 947 (1 906)	1 556 (1 514)	1 164 (1 122)	1 080 (1 038)



CATEGORY		MDA(MDH)	A	B	C	D		Knots	60	90	120	150	180
STA	FULL	1 090 (1 048)	3 600 m		4 600 m	N/A	Rate of descent	V/V fpm	392	588	784	980	1 175
	ALS INOP		4 000 m		4 900 m	N/A	* Timing Not authorized for defining MAPt. * Circling Not authorized.						

Change : Information of course/track, OBST, MOCA and Establishment of coordinates for USN VOR/DME.

ULSAN/Ulsan(RKPU)
VOR RWY 18


AERONAUTICAL DATA TABULATION

VOR Approach to RWY 18 from MAKKY		
Fix/point		Coordinates
MAKKY(IAF)	R 353 USN / 17.00 NM USN	35°52'18.8"N 129°15'35.8"E
SEDMO(IF)	BRG 172.64° / 13.00 NM USN	35°48'27.1"N 129°16'55.0"E
D10.1 USN(SDF)	BRG 172.64° / 10.10 NM USN	35°45'39.1"N 129°17'51.8"E
D8.0 USN(SDF)	BRG 172.64° / 8.00 NM USN	35°43'37.6"N 129°18'33.5"E
D5.9 USN(FAF)	BRG 172.64° / 5.90 NM USN	35°41'36.0"N 129°19'15.1"E
D3.3 USN(SDF)	BRG 172.64° / 3.28 NM USN	35°39'04.4"N 129°20'07.0"E
D2.3 USN(MAPt)	BRG 172.64° / 2.26 NM USN	35°38'05.4"N 129°20'27.1"E
THR RWY 18		35°36'08.89"N 129°21'03.54"E
USN VOR/DME		35°35'54.6"N 129°21'11.8"E
D3.0 USN	BRG 190.62° / 3.00 NM USN	35°33'01.3"N 129°20'11.6"E
HAEGU	BRG 93.43° / 10.00 NM USN	35°32'06.7"N 129°32'32.3"E

Change : Information of BRG.

ULSAN/Ulsan(RKPU)
ILS Y or LOC Y RWY 36

129°40'E



TRANSITION	ALT	14 000
TRANSITION	LVL	FL 140

[illegible]

CATEGORY			DA(DH)/ MDA(MDH)	A	B	C	D														
STA	CAT-I (CG 2.5%)	FULL	710	3 000 m				Rate of descent	Knots	60	90	120	150	180							
		ALS INOP	(682)	3 700 m																	
	CAT-I (CG 5.0%)	FULL	246	800 m																	
		ALS INOP	(218)	1 200 m																	
	LOC	FULL	750	2 700 m											* Timing Not authorized for defining MAPt. * Circling Not authorized.						
		ALS INOP	(722)	3 400 m																	

AIP AMDT 1/22

AERONAUTICAL DATA TABULATION

ILS/LOC Y Approach to RWY 36 from HAEGU		
Fix/point		Coordinates
HAEGU(IAF)	R 120 USN / 10.00 NM USN	35°32'06.7"N 129°32'32.3"E
D9.3 IULS(IF)	BRG 4.31° / 9.30 NM IULS	35°25'54.7"N 129°21'54.8"E
D4.3 IULS(FAF LOC ONLY)	BRG 4.31° / 4.30 NM IULS	35°30'57.6"N 129°21'29.5"E
D1.3 IULS(MAPt LOC ONLY)	BRG 4.31° / 1.30 NM IULS	35°33'55.7"N 129°21'14.7"E
THR RWY 36		35°35'04.15"N 129°21'08.95"E
IULS DME		35°35'13.8"N 129°21'12.2"E
USN VOR/DME		35°35'54.6"N 129°21'11.8"E
IULS LOC		35°36'16.3"N 129°21'02.9"E
D1.0 USN	BRG 4.31° / 1.00 NM USN	35°36'53.8"N 129°20'59.8"E
SEDMO	BRG 352.68° / 13.00 NM USN	35°48'27.1"N 129°16'55.0"E

Change : Information of name for instrument approach procedure(ILS → ILS Y).


**INSTRUMENT
APPROACH
CHART - ICAO**

AERODROME ELEV 42 ft
HEIGHTS RELATED TO
THR RWY 36 - ELEV 28 ft

POHANG APP 124.25
120.2
ULSAN TWR 118.75

ULSAN/Ulsan(RKPU)
ILS Z or LOC Z RWY 36

Note : Approach under ICAO Flight Procedures.




RECOMMENDED PROFILE(LOC ONLY)	DME IULS	6	5	4	3	2.3
Final Approach Gradient 5.28%, 321 ft/NM	ALT(HGT)	1 950 (1 922)	1 620 (1 592)	1 300 (1 272)	980 (952)	750 (722)

TRANSITION ALT 14 000
TRANSITION LVL FL 140

MISSED APPROACH

Climb on HDG 004° to USN 1 DME, then LEFT turn to intercept R 353 USN to SEDMO.
Hold at SEDMO at 4 000 ft.

* Missed APCH turn limited to MAX 200 kt IAS when 2.5% CG apply.



CATEGORY			DA(DH)/ MDA(MDH)	A	B	C	D							
STA	CAT-I (CG 2.5%)	FULL	710	3 000 m					Knots	60	90	120	150	180
		ALS INOP	(682)	3 700 m										
	CAT-I (CG 5.0%)	FULL	246	800 m			Rate of descent	V/V fpm	318	478	637	796	955	
		ALS INOP	(218)	1 200 m										
	LOC	FULL	750	2 700 m			* Timing Not authorized for defining MAPt * Circling Not authorized.							
		ALS INOP	(722)	3 400 m										

Change : Information of name for instrument approach procedure(ILS → ILS Z).

ULSAN/Ulsan(RKPU)
ILS Z or LOC Z RWY 36

AERONAUTICAL DATA TABULATION

ILS/LOC Z Approach to RWY 36 from HAEGU			
Fix/point		Coordinates	
HAEGU(IAF)		35°32'06.7"N	129°32'32.3"E
PU501(SDF)		35°26'18.1"N	129°29'02.9"E
LUKLI(IF)	BRG 4.31° / 9.30 NM IULS	35°25'54.4"N	129°21'54.8"E
D4.3 IULS(FAF LOC ONLY)	BRG 4.31° / 4.30 NM IULS	35°30'57.6"N	129°21'29.5"E
D1.3 IULS(MAPt LOC ONLY)	BRG 4.31° / 1.30 NM IULS	35°33'55.7"N	129°21'14.7"E
THR RWY 36		35°35'04.15"N	129°21'08.95"E
IULS DME		35°35'13.8"N	129°21'12.2"E
USN VOR/DME		35°35'54.6"N	129°21'11.8"E
IULS LOC		35°36'16.3"N	129°21'02.9"E
D1.0 USN	BRG 4.31° / 1.00 NM USN	35°36'53.8"N	129°20'59.8"E
SEDMO	BRG 352.68° / 13.00 NM USN	35°48'27.1"N	129°16'55.0"E

Change : Information of name for instrument approach procedure(ILS → ILS Z).


**INSTRUMENT
APPROACH
CHART - ICAO**

AERODROME ELEV 42 ft
HEIGHTS RELATED TO
THR RWY 36 - ELEV 28 ft

POHANG APP 124.25
120.2
ULSAN TWR 118.75

ULSAN/Ulsan(RKPU)
RNP RWY 36


Note : Approach under ICAO Flight procedure.



TRANSITION ALT 14 000
TRANSITION LVL FL 140

MISSED APPROACH

Climb to 4 000 ft on track of 355° to SEDMO.



								Knots	60	90	120	150	180	
CATEGORY			DA(H)/MDA(H)	A	B	C	D	Rate of descent	V/V fpm					
STA	LNAV/VNAV	FULL	760	2 700 m				* Timing Not authorized for defining MAPt. * Circling Not authorized.		319	478	637	796	956
		ALS INOP	(732)	3 400 m										
	LNAV	FULL	910	3 300 m										
		ALS INOP	(882)	4 000 m										

* Timing Not authorized for defining MAPt.
* Circling Not authorized.

Change : Information of course/track, OBST and Withdrawal of USN VOR/DME information and Establishment of MOCA.

ULSAN/Ulsan(RKPU)
RNP RWY 36
HOLDING PROCEDURE

AERONAUTICAL DATA TABULATION

Instrument Approach Procedure Coding Tables

RNP RWY 36

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	VPA/RDH	Navigation specification	Remarks
001	IF	HAEGU	-	-	-	-	+5 000	-	35°32'06.7"N 129°32'32.3"E	-	RNP APCH	IAF
002	TF	PU501	-	214(206.2)	6.5	-	+3 500	-	35°26'18.1"N 129°29'02.9"E	-	RNP APCH	SDF
003	TF	LUKLI	-	274(266.2)	5.8	-	+2 500	-	35°25'54.4"N 129°21'54.8"E	-	RNP APCH	IF
004	TF	DOOBU	-	004(356.1)	5.0	-	+1 400	-	35°30'55.3"N 129°21'29.7"E	-	RNP APCH	FAF
005	TF	ONAPU	Y	004(356.1)	3.0	-	+910	-	35°33'54.4"N 129°21'14.8"E	-3.00/50	RNP APCH	MAPt
006	TF	SEDMO	Y	355(346.4)	14.9	-	-	-	35°48'27.1"N 129°16'55.0"E	-	RNP APCH	-
007	HM	SEDMO	Y	173 (164.4)	-	-	-5 000 +4 000	-	35°48'27.1"N 129°16'55.0"E	-	RNP APCH	1 min (Outbound timing)

HOLDING PROCEDURE

Holding Identification	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(T)	Time (min)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	VPA/RDH	Navigation specification	Remarks
RNP RWY 36	HM	HAEGU	Y	300 (292.1)	1.0	R	@5 000	-200	35°32'06.7"N 129°32'32.3"E	-	RNAV 1	-

Change : Information of course/track for PU051, LUKLI, SEDMO.


**INSTRUMENT
APPROACH
CHART - ICAO**

AERODROME ELEV 42 ft
HEIGHTS RELATED TO
THR RWY 36 - ELEV 28 ft

POHANG APP 124.25
120.2
ULSAN TWR 118.75

ULSAN/Ulsan(RKPU)
VOR RWY 36

Note : Approach under ICAO Flight Procedures.




RECOMMENDED PROFILE	DME USN	5	4	3
Final Approach Gradient 5.24%, 318 ft/NM	ALT(HGT)	1 400 (1 372)	1 080 (1 052)	760 (732)

TRANSITION ALT 14 000
TRANSITION LVL FL 140

MISSED APPROACH

Climb direct to USN then proceed on R 353 USN to SEDMO and Hold at 4 000 ft.



CATEGORY		MDA(MDH)	A	B	C	D		Knots	60	90	120	150	180
STA	FULL	760 (732)	2 700 m				Rate of descent	V/V fpm	318	477	636	795	954
	ALS INOP		3 400 m				* Timing Not authorized for defining MAPt. * Circling Not authorized.						

Change : Information of course/track, OBST, MOCA and Establishment of coordinates for USN VOR/DME.

ULSAN/Ulsan(RKPU)
VOR RWY 36

AERONAUTICAL DATA TABULATION

VOR Approach to RWY 36 from HAEGU		
Fix/point		Coordinates
HAEGU(IAF)	R 120 USN / 10.00 NM USN	35°32'06.7"N 129°32'32.3"E
D10.0 USN(IF)	BRG 5.63° / 10.00 NM USN	35°25'54.3"N 129°21'44.9"E
D5.0 USN(FAF)	BRG 5.63° / 5.00 NM USN	35°30'54.4"N 129°21'28.4"E
D2.0 USN(MAPt)	BRG 5.63° / 2.00 NM USN	35°33'54.5"N 129°21'18.5"E
THR RWY 36		35°35'04.15"N 129°21'08.95"E
USN VOR/DME		35°35'54.6"N 129°21'11.8"E
SEDMO	BRG 352.68° / 13.00 NM USN	35°48'27.1"N 129°16'55.0"E

Change : Information of BRG and DIST.